

Canon Inc.

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 2-1, Kaji-cho 1 chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

imageRUNNER ADVANCE DX C3826i Platen (For EU)



%The Cassette Feeding Unit is excluded.

Functional unit

Per unit product

System boundary

■ final products □intermediate products Raw Material acquisition, Production, Distribution, Use & maintenance, and End-of-Life stage

Main specifications of the product

Model name: imageRUNNER ADVANCE DX C3826i Platen (For EU)

Multi Functional Printer

(Electrophotography)

- •Up to 26ipm(A4)
- •Duplex printing
- •Weight: approx. 68.1kg

Company Information

Canon Inc. 30-2, Shimomaruko 3-chome, Ohta-ku, Tokyo 146-8501, Japan +81-3-3758-2111

EU)	Registration#	JR-AI-22099C	
	PCR number	PA-590000-AI-04	
	PCR name	Imaging input and/or output equipment	
	Publication date	7/15/2022	
	Verification date	7/6/2022	
	Verification method	System certificaion	
	Verification#	JV-AI-22099C	
	Expiration date	7/5/2027	
	PCR review was conducted by:		
	Approval date	11/8/2019	
	PCR review panel chair	Masayuki Kanzaki	
		Sustainable Management Promotion Organization	
	Third party verifier*		
		Hiroyuki Uchida	
	Independent verification of data & declaration in accordance with ISO/TS14067		
	□internal ■external		

*Auditor's name is stated if system certification has been performed.

Registration number : JR-AI-22099C



Carbon Footprint of Products **CFP** Declaration

Registration number : JR-AI-22099C

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 2-1, Kaji-cho 1 chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

3. Supplementary environmental information

·Complies with the EU RoHS Directive (2011/65/EU) and its amendments


Manufactured at ISO 14001 certified

including 2015/863/EU.

factories.

1. Quantification results, and contents of the declaration					
CFP quantification unit : Per unit puroduct					
	Parameter		Unit		
CF	P Quantification results	950	kg-CO ₂ eq		
_	Raw material acquisition	690	kg-CO ₂ eq		
Breakdown	Production	31	kg-CO ₂ eq		
akd	Distribution	63	kg-CO ₂ eq		
Brei	Use & maintenance	77	kg-CO ₂ eq		
	End-of-Life	91	kg-CO ₂ eq		
1	/alue on CFP mark	950	kg-CO ₂ eq		
Unit	for the value on CFP mark	Per unit puroduct			

*Quantification results may slightly differ from the sum of the breakdown due to rounding of fractions.



4. Interpretation

•CO2 emission in Raw material acquisition is the largest as 72%. It is important to reduce the size and weight, and to use low environmental impact materials.

•CO2 emission in End-of-Life is the second largest as 10%. It is important to reduce the size and weight, and improving recycling rates.

•We evaluated the CFP with Canon's own data of raw materials weight and the general basic unit for the parts because it is difficult to collect the data for a couple of thousands of parts. Accordingly, the results may be different from the specific product specification.

As such, please be advised that this result would be a rough estimate.

5. Assumptions of secondary data used

IDEA v2.1.3, and registered data of Japan EPD Program by SuMPO, JLCA data v1.07 are used.

6. Remarks

- For data quantification, please refer to PCR and Rules on quantification and declaration.

- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied. (Reference URL : https://ecoleaf-label.jp/regulation/)

- The CFP only addresses the single impact category of climate change and does not assess other potential social, economic and environmental impacts arising from the provision of a product.