



Carbon Footprint of Products  
CFP Declaration

Registration number : JR-AI-22052C

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization  
2-1, Kaji-cho 1 chome, Chiyoda-ku, Tokyo Japan  
<https://ecoleaf-label.jp/>

Canon Inc.

imageRUNNER ADVANCE DX 4825i 1PDS(For US)



※The Cassette Feeding Unit is excluded.

Functional unit

Per unit product

System boundary

final products     intermediate products

Raw Material acquisition, Production, Distribution,

Use & maintenance, and End-of-Life stage

Main specifications of the product

Model name: imageRUNNER ADVANCE DX 4825i 1PDS(For US)

Specifications

- Multi Functional Printer (Electrophotography)
- Print Speed : Up to 25 ipm (A4)
- Duplex printing
- Weight: approx.72.56kg(Toner bottle not included)

Company Information

Canon Inc.  
30-2, Shimomaruko 3-chome, Ohta-ku,  
Tokyo 146-8501, Japan  
+81-3-3758-2111

Registration#	JR-AI-22052C
PCR number	PA-590000-AI-04
PCR name	Imaging input and/or output equipment
Publication date	10/28/2022
Verification date	10/17/2022
Verification method	System certificaion
Verification#	JV-AI-22052C
Expiration date	10/16/2027

PCR review was conducted by:

Approval date	4/1/2022
PCR review panel chair	Masayuki Kanzaki Sustainable Management Promotion Organization

Third party verifier\*

	Hiroyuki Uchida
--	-----------------

Independent verification of data & declaration in accordance with ISO/TS14067

internal     external

\*Auditor's name is stated if system certification has been performed.

Registration number : JR-AI-22052C



1. Quantification results, and contents of the declaration

CFP quantification unit : Per unit puroduct


Parameter			Unit
<b>CFP Quantification results</b>		<b>1000</b>	<b>kg-CO<sub>2</sub>eq</b>
Breakdown	Raw material acquisition	760	kg-CO <sub>2</sub> eq
	Production	24	kg-CO <sub>2</sub> eq
	Distribution	62	kg-CO <sub>2</sub> eq
	Use & maintenance	56	kg-CO <sub>2</sub> eq
	End-of-Life	100	kg-CO <sub>2</sub> eq
<b>Value on CFP mark</b>		<b>1000</b>	<b>kg-CO<sub>2</sub>eq</b>
<b>Unit for the value on CFP mark</b>		<b>Per unit puroduct</b>	

\*Quantification results may slightly differ from the sum of the breakdown due to rounding of fractions.

3. Supplementary environmental information

- Complies with the EU RoHS Directive (2011/65/EU) and its amendments including 2015/863/EU.
- Manufactured at ISO 14001 certified factories.

2. Additional information



Calculated in the following conditions;

- Printing paper is not considered.
- The standard scenario for Multifunction Device (EP type).
- US market.
- Print volume: 90,000 sheets.
- The applied Energy Star program version is 3.0.

4. Interpretation

- CO2 emission in Raw material acquisition is the largest as 76%. It is important to reduce the size and weight, and to use low environmental impact materials.
  - CO2 emission in End-of-Life is the second largest as 10%. It is important to reduce the size and weight, and improving recycling rates.
  - We evaluated the CFP with Canon's own data of raw materials weight and the general basic unit for the parts because it is difficult to collect the data for a couple of thousands of parts. Accordingly, the results may be different from the specific product specification.
- As such, please be advised that this result would be a rough estimate.

5. Assumptions of secondary data used

IDEA v2.1.3, and registered data of Japan EPD Program by SuMPO, JLCA data v1.10 are used.

6. Remarks

-

- For data quantification, please refer to PCR and Rules on quantification and declaration.
- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied.  
(Reference URL : <https://ecoleaf-label.jp/regulation/>)
- The CFP only addresses the single impact category of climate change and does not assess other potential social, economic and environmental impacts arising from the provision of a product.