Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

Canon Inc.

imageRUNNER ADVANCE DX 4935i 1PDS(For US)



**The Cassette Feeding Unit is excluded.

Functional unit

Per unit product

System boundary

■ final products □intermediate products

Raw Material acquisition, Production, Distribution,

Use & maintenance, and End-of-Life stage

Main specifications of the product

Model name

imageRUNNER ADVANCE DX 4935i 1PDS(For US)

Specifications

- Multi Functional Printer (Electrophotography)
- BW
- Print Speed : Up to 35 ipm (LTR)
- Max paper size : 320x450mm(SRA3) (12 5/8"x17 3/4")
- Print/copy/scan/Duplex printing/ADF
- Weight: approx.72.56kg(Toner bottle not included)

Company Information

Canon Inc.

30-2, Shimomaruko 3-chome, Ohta-ku, Tokyo 146-8501, Japan +81-3-3758-2111

3	
PCR number	PA-590000-AI-07
PCR name	Imaging input and/or output equipment
Publication date	7/7/2023
Verification date	6/30/2023
Verification method	System certificaion
Verification#	JV-AI-23161C
Expiration date	6/29/2028

PCR review was conducted by:

Approval date		4/24/2023
	PCR review	Masayuki Kanzaki
	panel chair	Sustainable Management Promotion Organization

Third party verifier*

Hiroyu	ki U	Ich	ΙÍC	la
--------	------	-----	-----	----

Independent verification of data & declaration in accordance with ISO/TS14067

□internal	■ external	
	■ external	

Registration number: JR-AI-23161C

^{*}Auditor's name is stated if system certification has been performed.

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

1. Quantification results, and contents of the declaration CFP quantification unit:


Parameter			Unit	
CF	P Quantification results	990	kg-CO₂eq	
_	Raw material acquisition	720	kg-CO₂eq	
N N	Production	32	kg-CO₂eq	
gkdc	Distribution	63	kg-CO₂eq	
Breakdown	Use & maintenance	83	kg-CO₂eq	
"	End-of-Life	97	kg-CO₂eq	
Value on CFP mark		990	kg-CO₂eq	
Unit for the value on CFP mark		Per unit product		

^{*}Quantification results may slightly differ from the sum of the breakdown due to rounding of fractions.

3. Supplementary environmental information

- Complies with the EU RoHS Directive (2011/65/EU) and its amendments including 2015/863/EU.
- Manufactured at ISO 14001 certified factories.

2. Additional information



Calculated in the following conditions;

- · Printing paper is not considered.
- The standard scenario for Multifunction Device (EP type).
- · US market.
- · Print volume: 182,400 sheets.
- The applied Energy Star program version is 3.0.

4. Interpretation

- CO2 emission in Raw material acquisition is the largest as 72%. It is important to reduce the size and weight, and to use low environmental impact materials.
- CO2 emission in End-of-Life is the second largest as 10%. It is important to reduce the size and weight, and improving recycling rates.
- We evaluated the CFP with Canon's own data of raw materials weight and the general basic unit for the parts because it is difficult to collect the data for a couple of thousands of parts. Accordingly, the results may be different from the specific product specification.

As such, please be advised that this result would be a rough estimate.

5. Assumptions of secondary data used

IDEA v2.1.3, and registered data of Japan EPD Program by SuMPO, JLCA data v1.13 are used.

6. Remarks

- -
- For data quantification, please refer to PCR and Rules on quantification and declaration.
- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied. (Reference URL : https://ecoleaf-label.jp/regulation/)
- The CFP only addresses the single impact category of climate change and does not assess other potential social, economic and environmental impacts arising from the provision of a product.

Registration number: JR-AI-23161C