



Carbon Footprint of Products

CFP Declaration

Registration number : JR-AI-23366C

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization
14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan
<https://ecoleaf-label.jp/>

Canon Inc.

imageCLASS X MF1440(For US)



Functional unit

Per unit product

System boundary

final products intermediate products

Raw Material acquisition, Production, Distribution, Use & maintenance, and End-of-Life stage

Main specifications of the product

Model name

imageCLASS X MF1440(For US)

Specifications

- Multi Functional Device (Electrophotography)
- BW
- Print Speed : Up to 42 ipm (LTR)
- Max paper size : LGL
- Print/copy/scan/FAX/Duplex printing/ADF
- Weight: approx.15.52kg(Cartridge not included)

Company Information

Canon Inc.
30-2, Shimomaruko 3-chome, Ohta-ku,
Tokyo 146-8501, Japan
+81-3-3758-2111

Registration#	JR-AI-23366C
PCR number	PA-590000-AI-08
PCR name	Imaging input and/or output equipment
Publication date	10/24/2023
Verification date	10/18/2023
Verification method	Product-by-product
Verification#	JV-AI-23366
Expiration date	10/17/2028
PCR review was conducted by:	
Approval date	9/1/2023
PCR review panel chair	Masayuki Kanzaki Sustainable Management Promotion Organization

Third party verifier*

Kazuo Naito

Independent verification of data & declaration in accordance with ISO/TS14067

internal external

*Auditor's name is stated if system certification has been performed.

Registration number : JR-AI-23366C

**1. Quantification results, and contents of the declaration**


CFP quantification unit :

Parameter			Unit
CFP Quantification results		460	kg-CO₂eq
Breakdown	Raw material acquisition	170	kg-CO ₂ eq
	Production	7	kg-CO ₂ eq
	Distribution	12	kg-CO ₂ eq
	Use & maintenance	250	kg-CO ₂ eq
	End-of-Life	24	kg-CO ₂ eq
Value on CFP mark		460	kg-CO₂eq
Unit for the value on CFP mark		Per unit product	

*Quantification results may slightly differ from the sum of the breakdown due to rounding of fractions.

3. Supplementary environmental information

- Complies with the EU RoHS Directive (2011/65/EU) and its amendments including 2015/863/EU.
- Manufactured at ISO 14001 certified factories.

2. Additional information

Calculated in the following conditions;

- Printing paper is not considered.
- The standard scenario for Multifunction Device (EP type).
- US market.
- Print volume: 259,200 sheets.
- The applied Energy Star program version is 3.0.

4. Interpretation

- CO₂ emission in Use & maintenance is the largest as 54%. It is important to save energy during product usage, to make the life time of consumables(e.g. drum) longer and to reduce amount of toner used when printing. The condition in this CFP evaluation can be different from the one which the user operates under. A choice of the use condition (print mode, print conditions and so on) can reduce the CO₂ emission during Use & maintenance stage.
 - CO₂ emission in Raw material acquisition is the second largest as 37%. It is important to reduce the size and weight, and to use low environmental impact materials.
 - We evaluated the CFP with Canon's own data of raw materials weight and the general basic unit for the parts because it is difficult to collect the data for a couple of thousands of parts. Accordingly, the results may be different from the specific product specification.
- As such, please be advised that this result would be a rough estimate.

5. Assumptions of secondary data used

IDEA v2.1.3, and registered data v1.13 of Japan EPD Program by SuMPO are used.

6. Remarks

-

- For data quantification, please refer to PCR and Rules on quantification and declaration.
- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied.
(Reference URL : <https://ecoleaf-label.jp/regulation/>)
- The CFP only addresses the single impact category of climate change and does not assess other potential social, economic and environmental impacts arising from the provision of a product.