Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

Japan EPD Program by SuMPO





Functional unit

Per unit of product

System boundary

■ final products □intermediate products Raw material acquisition,Production,Distribution, Use & maintenance,End-of-Life

Main specifications of the product

Model name : ES-C220 Main Specifications

- Sheet-fed scanner(Without Flat-bed) For Parsonal
- Scanning Speed : Simplex or Duplex, 30ppm(60ppm)
- Scanning Size : 215.9mm × 3,048mm
- Scanning Resolution : 50~1200dpi (1dpi pitch)
- Scanning Method CIS
- *This product is destined for North America

Company Information

Seiko Epson Corporation http://www.epson.com/ http://www.epson.jp/contact/(Japanese) 3-3-5 Owa, Suwa-Shi, Nagano,392-0001, Japan TEL 81-266-52-5353 (Japan)

Registration#	JR-AI-23338E			
PCR number	PA-590000-AI-8			
PCR name	Imaging input and/or output equipment			
Publication date	11/2/2023			
Verification date	10/16/2023			
Verification method	Product-by-product			
Verification#	JV-AI-23338			
Expiration date	10/15/2028			
PCR review was conducted by:				
Approval date	9/1/2023			
PCR review	Masayuki Kanzaki			
panel chair	(Sustainable Management Promotion Organization)			

Third party verifier*

Tetsuya Okuyama

Independent verification of data & declaration in accordance with ISO14025

□internal

external

*Auditor's name is stated if system certification has been performed.

Registration number : JR-AI-23338E



EcoLeaf

Registration number : JR-AI-23338E

Type III Environmental Declaration(EPD)

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

1. Results of life cycle i	mpact as	sessment	(LCIA)						
			0%	20% 4	·0% 6	50% 80	% 100		
Global warming IPCC2013 GWP100a	40	kg-CO2eq		70%		3%	21% <mark>4%</mark>		
Acidification	0.024	kg-SO2eq			87%	3% -/	8% 2%		
Resources consumption	0.0030	kg-Sbeq			98%		% - 2% -0%		
Raw material acquisition Production Distribution Use & maintenance End-of-Life									
stage Parameter	Unit	Total	Raw material acquisition	Production	Distribution	Use & maintenance	End-of-Life		
Global warming IPCC2013 GWP100a	kg-CO ₂ eq	4.0E+01	2.8E+01	1.1E+00	1.1E+00	8.6E+00	1.5E+00		
Acidification	kg-SO ₂ eq	2.4E-02	2.1E-02	8.5E-05	1.9E-03	7.1E-04	3.7E-04		
Resources consumption	kg-Sbeq	3.0E-03	2.9E-03	2.7E-06	4.8E-06	6.2E-05	1.1E-06		

2. Life cycle inventory analysis (LCI)					
Parameter		Unit			
Non-renewable material resources	2.0E+00	kg			
Renewable material resources	4.3E+00	kg			

3. Material composition						
Material		Unit				
Steel	10	%				
SUS	0	%				
Aluminum	0	%				
Other metal	9	%				
Plastic	38	%				
Rubber	1	%				
Glass	1	%				
Paper and wood	23	%				
Circuit Board	6	%				
Others	11	%				

5. Additional explanation

Product destination: North America

- Calculation method of use stage (scenario)*

- Expected usage : 5 years

- Scans per day : 64 sheets / day (8 scans / day)
- Workdays per month : 20 days / month
- Working days per year : 240 days / year
- Total scans : 9,600 times (76,800 sheets) / 5 years

*For the load calculations during the Use & maintenance stage, scenarios were set up under the above conditions to match the user's actual usage conditions.

6-1. Supplementary environmental information

- This product and main compornents are produced in our ISO 14001 certified factories.

- Compliant with the International Energy Star Program Ver.3.0.

- It also complies with the European RoHS Directive.

7. Assumptions of secondary data used

We used IDEA v2.1.3 and SuMPO Environmental Label Program registration intensity v1.13.

8. Remarks

- For data quantification, please refer to PCR and Rules on quantification and declaration.

- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied. (Reference URL : https://ecoleaf-label.jp/regulation/)

Registration number : JR-AI-23338E