### Sumpo EPD VERIFIED

#### SuMPO EPD

# Type III Environmental Declaration (EPD)

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo

Japan EPD Program by SuMPO

https://ecoleaf-label.jp/

Registration number: JR-AJ-23025E

## S OSAKA STEEL CO.,LTD.

## **Angles**



#### **Functional unit**

1 t

#### **System boundary**

☐ final products ■ intermediate products

Production Stage and optional supplementary information

#### Main specifications of the product

Production sites: Sakai Works,

Nishi-Nippon Kumamoto Works

#### Main standards:

JIS G 3101 (SS400, SS540)

JIS G 3106 (SM400A, SM400B, SM490A, SM490B)

JIS G 3136 (SN400A, SN400B, SN490B)

Shapes: Angles

Sizes (mm):

 $L20\times20\times3\sim L150\times150\times15$  [Equal angles]

L90×75×9~L150×100×15 [Unequal angles]

#### **Company Information**

OSAKA STEEL CO., LTD.

	Registration#	JR-AJ-23025E
s	PCR number	PA-180000-AJ-06
	PCR name	Steel products for construction use
	Publication date	12/25/2023
	Verification date	11/21/2023
	Verification method	Product-by-product
	Verification#	JV-AJ-23025
s	Expiration date	11/20/2028

#### PCR review was conducted by:

Approval date	5/10/2023		
PCR review	Yasunari Matsuno		
panel chair	Chiba University		

#### Third party verifier\*

Wataru Kawamura

Independent verification of data & declaration in accordance with ISO14025 and ISO21930.

□internal **■** external

Production&Technical Control Div. Technical Control Group

TEL: +81-6-6204-0300 https://www.osaka-seitetu.co.jp/en/contact/

Registration number: JR-AJ-23025E

<sup>\*</sup>Auditor's name is stated if system certification has been performed.



### SuMPO EPD

# Type III Environmental Declaration (EPD)

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan

https://ecoleaf-label.jp/

## 1. Results of life cycle impact assessment (LCIA)

Registration number: JR-AJ-23025E

stage Parameter	[A1~A3] + [D]	[A1~A3]	Unit
Global warming IPCC2013 GWP100a	930	760	kg-CO2eq
Acidification	0.69	0.43	kg-SO2eq
Eutrophication	0.0039	0.00079	kg-PO43-eq




Table Legend

[A1~A3]:sum of [A1],[A2]and[A3](cradle to gate)

 $[A1 \sim A3] + [D]$ : sum of [A1], [A2], [A3] and [D] (cradle to gate with allocation for scrap recycling)

stage Parameter	Unit	[A1~A3]	[A1]Raw mterial supply	[A2] Transport to factory	【A3】 Manufacturing	【D】 Recycling potential
Global warming IPCC2013 GWP100a	kg-CO <sub>2</sub> eq	7.6E+02	2.2E+02	2.3E+01	5.2E+02	1.7E+02
Ozone layer destruction	kg-CFC-11eq	2.2E-06	2.1E-06	1.9E-10	3.6E-08	3.1E-08
Acidification	kg-SO₂eq	4.3E-01	1.7E-01	7.2E-02	1.8E-01	2.6E-01
Photochemical ozone	kg-C <sub>2</sub> H <sub>4</sub> eq	1.3E-02	1.9E-03	1.3E-04	1.1E-02	3.7E-02
Eutrophication	kg-PO <sub>4</sub> 3-eq	7.9E-04	2.3E-06	1.6E-13	7.9E-04	3.1E-03

#### 2. Life cycle inventory analysis (LCI) Parameter Unit Non-renewable material resources 3.1E+01 kg Non-renewable energy resources 1.2E+04 MJ Renewable material resources 2.1E+02 kg 2.6E+02 MJ Renewable primary energy Consumption of freshwater 5.9E-01 $m^3$

3. Material composition				
Material		Unit		
iron [Fe]	≧96.0	%		
carbon [C]	≦0.30	%		
silicon [Si]	≦0.55	%		
manganese [Mn]	≦1.65	%		
phosphorus [P]	≦0.050	%		
sulfur [S]	≦0.050	%		

4. Waste to disposal			
Parameter		Unit	
Hazardous waste	0.0E+00	kg	
Non-hazardous waste.	1.2E+02	kg	

#### **5.** Additional explanation

■ [A3] Manufacturing

- 1) Each LCI includes allocation for scrap recycling as an optional supplementary information 【D】 at table.1. Recycling rate (RR) used in this calculation is 93.0% (calculated based on ISO 20915/JIS Q20915 and using Japan data in 2018 from Japan Iron and Steel Federation and Japan Steel Can Recycling Association).
- 2) Scenarios of transport to site follow the PCR.
- 3) Each item (except iron) in table 3 is the maximum value of all product standards covered by this EPD. However, the iron content in each product is never less than 96.0%, and the contents of other components are adjusted.
- 4) Primary data collected in 2021. The source of the unit power consumption is the average of 10 electric power suppliers of Japan in 2014.



# SuMPO EPD Type III Environmental Declaration (EPD)

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

Registration number: JR-AJ-23025E

#### 6-1. Supplementary environmental information

Each production site is certified to ISO 14001. (Certification Number E729)

6-2. Regulated hazardous substances				
Substance	CAS No.	Reference to standards or regulations		
manganese [Mn]	7439-96-5	Industrial Safety and Health Act		

#### 7. Assumptions of secondary data used

We use the IDEA v2.1.3 data and steel scrap data(JP-AJ-0001) from the Japan Iron and Steel Federation.

#### 8. Remarks

Date of change 2025/02/14 from the EcoLeaf mark to the SuMPO EPD mark.

- For data quantification, please refer to PCR and Rules on quantification and declaration.
- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied. (Reference URL : https://ecoleaf-label.jp/regulation/)

Registration number: JR-AJ-23025E