EcoLeaf
Type III Environmental Declaration (EPD)
Registration number： JR-AJ-23014E-A

Japan EPD Program by SuMPO
Sustainable Management Promotion Organization
14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan
https ://ecoleaf-label.jp

NIPPON STEEL | NIPPON STEEL CORPORATION

BLACK ZAM™ for Constructions

Functional unit

1 t

System boundary

☐ final products ■intermediate products

Production Stage and optional supplementary infomation

Main specifications of the product

Production sites : Setouchi Works

Main standards :
NIPPON STEEL
See Table 8.Remarks for details.

Type : Coil、Sheet

Main sizes(unit ㎜,t :thickness)
t=0.25～6.0

Company Information

NIPPON STEEL CORPORATION
https ://www.nipponsteel.com/en/product/sheet/list/

Registration#	JR-AJ-23014E-A
PCR number	PA-180000-AJ-06
PCR name	Steel products for construction use
Publication date	02/05/2024
Verification date	01/16/2024
Verification method	Product-by-product
Verification#	JV-AJ-24014
Expiration date	01/15/2029

PCR review was conducted by:

Approval date	05/10/2023
PCR review panel chair	Yasunari Matsuno Chiba University

Third party verifier*

Takahiro Atoh

Independent verification of data & declaration in accordance with ISO14025

☐internal ■external

*Auditor's name is stated if system certification has been performed.

EcoLeaf
Type III Environmental Declaration (EPD)
Registration number : JR-AJ-23014E-A

Japan EPD Program by SuMPO
Sustainable Management Promotion Organization
14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan
https ;//ecoleaf-label.jp

1. Results of life cycle impact assessment (LCIA)

Parameter \ Stage	【A1～A3】+【D】	【A1～A3】	Unit
Global warming IPCC2013 GWP100a	1600	2700	kg-CO_2eq
Acidification	0.55	2.3	kg-SO_2eq
Eutrophication	0.025	0.046	kg-PO_4^{3-}eq

Table Legend
【A1】: Raw mterial supply
【A2】: Transport to factory
【A3】: Manufacturing
【D】: Recycling potential
【A1～A3】: sum of 【A1】, 【A2】 and 【A3】 (cradle to gate)
【A1～A3】+【D】: sum of 【A1】, 【A2】, 【A3】 and 【D】 (cradle to gate with allocation for scrap recycling)

Parameter \ stage	Unit	【A1～A3】	【A1】	【A2】	【A3】		【D】
Global warming IPCC2013 GWP100a	kg-CO_2eq	2.7E+03	5.2E+02	1.5E+02	2.1E+03		-1.1E+03
Ozone layer destruction	kg-CFC-11eq	2.7E-04	2.3E-04	9.8E-10	3.8E-05		-2.1E-07
Acidification	kg-SO_2eq	2.3E+00	5.3E-01	4.0E-01	1.4E+00		-1.8E+00
Photochemical ozone	kg-C_2H_4eq	2.4E-02	5.0E-03	7.9E-03	1.1E-02		-2.5E-01
Eutrophication	kg-PO_4^{3-}eq	4.6E-02	1.2E-03	8.8E-13	4.5E-02		-2.1E-02

2. Life cycle inventory analysis (LCI)

Parameter		Unit
Non-renewable material resources	6.8E+02	kg
Renewable material resources	9.6E+02	kg
Non-renewable energy resources	3.0E+04	MJ
Renewable primary energy	-6.3E+02	MJ
Consumption of freshwater	2.4E-01	m^3

3. Material composition

Material		Unit
Fe	≧84.0	%
C	≦1.10	%
Si	≦3.00	%
Mn	≦3.00	%
P	≦0.050	%
S	≦0.050	%
Zn	≦14.00	%
Al	≦1.00	%
Mg	≦0.50	%

4. Waste to disposal

Parameter		Unit
Hazardous waste	0.0E+00	kg
Non-hazardous waste.	1.7E+00	kg

*Data derived from LCA and not assigned to the impact categories of LCIA

5. Additional explanation

1. Each LCI includes allocation for scrap recycling as an optional supplementary information(3) at table.1 . Recycling rate (RR) used in this calculation is 93.0% (calculated based on ISO 20915/JIS Q20915 and using Japan data in 2018 from Japan Iron and SteelFederation and Japan Steel Can Recycling Association).
2. Scenarios of transport to site follow the PCR.
3. Each item (expect iron) in table 3 is the maximum value of all product standards covered by this EPD.However, the iron content in each product is never less than 84%, and the contents of other components are adjusted.
4. Primary data collected in 2018. The source of the unit power consumption is the average of 10 electric power suppliers of Japan in 2014.
5. For the transport of metallurgical coal, the amount is double counted due to the characteristics of the inventory database on which this estimation is based.

6-1. Supplementary environmental information

Setouchi Works has ISO 14001 certificate.

6-2. Regulated hazardous substances

Substance	CAS No.	Reference to standards or regulations
Manganese [Mn]	7439-96-5	Industrial Safety and Health Act

7. Assumptions of secondary data used

The IDEA2.1.3 data and steel scrap data(JP-AJ-0001) from the Japan Iron and Steel Federation are used.

8. Remarks

NIPPON STEEL Grade
General use（e.g.MSMCC-DZBK、MSMHC-DZBK）、Deep drawing（e.g.MSMCD-DZBK、MSMHD-DZBK）、
Structures（e.g.MSMCK370-DZBK、MSMHK370-DZBK）
Constractions (e.g.MSMCK400K-DZBK、MSMHK400K-DZBK）etc.

*January 2024; Modification about allocation method of by-product gases

- For data quantification, please refer to PCR and Rules on quantification and declaration.
- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied.
  （Reference URL：https ://ecoleaf-label.jp/regulation/）