

Ecoleaf Environmental Labeling Program

Sustainable Management Promotion Organization 2-1, Kaji-cho 2 chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/



Yamato Steel Co., Ltd.

High-Spec H-Beams



Functional unit

1t

System boundary

 \square final products \blacksquare intermediate products

Production Stage and optional supplementary infomation

Main specifications of the product

Production sites: Head office (Himeji)

Main standards :

YHS-SS400,YHS-SN400B,YHS-SM490A,YHS-SN490B

Main sizes(unit:mm,t:thickness)

 $H150(t7) \times B150(t10) \sim H912(t18) \times B302(t34)$

Company Information

Yamato Steel Co., Ltd.

http://www.yamatokogyo.co.jp/steel/

Registration#	JR-AJ-20005E	
PCR number	PA-180000-AJ-03	
PCR name	Steel products for construction	
Publication date	8/23/2020	
Verification date	7/31/2020	
Verification method	Product-by-product	
Verification#	JV-AJ-20005	
Expiration date	7/30/2025	
PCR review was conducted by:		
Approval date	10/1/2019	
PCR review	Yasunari Matsuno	
panel chair	(Chiba University)	
Third newly verifies!		

Third party verifier*

Tomoko Fuchigami

Independent verification of data & declaration in accordance with ISO14025 and ISO21930

□internal ■external

Registration number: JR-AJ-20005E

 $[\]hbox{*-} \hbox{Auditor's name is stated if system certification has been performed.}$

EcoLeaf

Type III Environmental Declaration (EPD)


Registration number: JR-AJ-20005E

Ecoleaf Environmental Labeling Program

Sustainable Management Promotion Organization 2-1, Kaji-cho 2 chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

1. Results of life cycle impact assessment (LCIA) 0%

Global warming IPCC2013 GWP100a	660	kg-CO2eq
Acidification	0.38	kg-SO2eq
Resources consumption	0.036	kg-Sbeq



■ [A1]Raw material acquisition ■ [A2] Distribution ■ [A3] Production

stage Parameter	Unit	Total	[A1]Raw material	[A2] Distributio	[A3]	scrup recycling effect for
	kg-CO2eg	6.6E+02	1.9E+02	2.5E+01	4.4E+02	2.5E+02
Global warming IPCC2013 GWP100a	kg-COZeq	0.00+02	1.96+02	2.35+01	4.46+02	2.36+02
Ozone layer destruction	kg-CFC-11eq	8.1E-08	1.7E-08	2.0E-10	6.4E-08	4.5E-08
Acidification	kg-SO2eq	3.8E-01	1.6E-01	7.7E-02	1.5E-01	3.9E-01
Urban area air pollution	kg-SO2eq	1.9E-01	1.0E-01	3.0E-02	5.5E-02	2.8E-01
photochemical oxidants	kg-C2H4eq	3.4E-02	1.9E-03	1.4E-04	3.2E-02	-3.3E-03
Toxic chemicals(cancer)	kg-C6H6eq	3.7E+01	3.6E-04	8.1E-09	3.7E+01	-2.3E+00
Toxic chemicals(chronic disease)	kg-C6H6eq	3.4E-04	5.3E-05	1.2E-09	2.9E-04	-2.5E-04
Aquatic ecotoxicity	kg-C6H6eq	5.2E-01	8.0E-02	1.8E-06	4.4E-01	-6.0E+00
Covance	kg-C6H6eq	1.3E+01	1.9E+00	4.4E-05	1.1E+01	7.2E+00
Eutrophication	kg-PO43-eq	4.1E-05	1.5E-07	1.7E-13	4.1E-05	4.6E-03
Land use(no-change)	m2/year	3.9E+00	1.6E-01	3.1E+00	7.0E-01	0.0E+00
Land transformation(change)	m2	7.8E-02	3.2E-03	6.1E-02	1.4E-02	0.0E+00
Resources consumption	kg-Sbeq	3.6E-02	3.4E-02	1.0E-04	2.1E-03	-5.8E-01

Life cycle inventory analysis (LCI) **Parameter** Unit Non-renewable material resources 1.4E-01 kg kg Non-renewable energy resources 2.5E+02 Non-renewable energy resources 1.1E+04 MJ Renewable material resources 1.9E+02 kg Renewable primary energy 2.4E+02 MJ m³ Consumption of freshwater 8.5E-02 Emissions,C02,fdssil 6.5E+02 kg resource,air,unspecified Resources,crude oil,44.7MJ/kg,ground,Non-3.8E+01 kg renewable energy resources□ Emissions,Volatile Organic 6.1E-10 kg Compounds,air,unspecified□ Emissions,P total water,water,unspecified 1.2E-05 kg

3. Material composition		
Material		Unit
Iron [Fe]	≦99.0	%
Carbon [C]	≦1	%
Manganese [Mn]	≦5	%
Nickel [Ni]	≦1	%
Chromium [Cr]	≦1	%
Molybdenum [Mo]	≦0.5	%

4. Waste to disposal			
Parameter		Unit	
Hazardous waste	1.56E+01	kg	
Non-hazardous waste.	7.2E+00	kg	
Non-Industrial for landfill	0.0E+00	kg	
industrial waste for landfill	7.2E+00	kg	

5. Additional explanation

①Each LCI figure includes allocation for scrap recycling as a optional supplementary infomation[D]. The recycling effect is calculated with the following totals. One is load accompanied with the scrap injection to the product production site. It is the credit accompanied with the scrap collection of the used steel product one more. Recycling rate(RR) of this EPD is 93.1% (the average of Japan in 2014).

- $\ensuremath{@\mathsf{Transport}}$ to site scienario is based on PCR.
- 3The first data was acquired from 2019.
- The source of the unit power consumption is the average of 10 electric power suppliers of Japan in 2014.
- ⑤A component about the material and a substance mentioned the number quoted from our safe data seat (SDS)

^{*}Data derived from LCA and not assigned to the impact categories of LCIA



Type III Environmental Declaration (EPD)

Registration number: JR-AJ-20005E

Ecoleaf Environmental Labeling Program

Sustainable Management Promotion Organization 2-1, Kaji-cho 2 chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-lahel.in/

6-1. Supplementary environmental information

Manufactured at ISO 14001 certified factories.

Manufactured at medical waste disposal certified factories.

6-2. Regulated hazardous substances		
Substance	CAS No.	Reference to standards or regulations
Manganese [Mn]	7439-96-5	Industrial Safety and Health Act
Molybdenum [Mo]	7439-98-7	Industrial Safety and Health Act
Chrome [Cr]	7440-47-3	Industrial Safety and Health Act
Nickel [Ni]	7440-02-0	Industrial Safety and Health Act

7. Assumptions of secondary data used

We use the IDEA2.1.3 data and scrup iron data from the Japan Iron and Steel Federation(J.I.S.F).

8. Remarks

-

- For data quantification, please refer to PCR and Rules on quantification and declaration.
- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied. (Reference URL : https://ecoleaf-label.jp/regulation/)

Registration number: JR-AJ-20005E