Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

Canon Inkjet All-In-One TS3720

Canon Inc.



Functional unit

Per unit product

System boundary

■ final products □intermediate products

Raw Material acquisition, Production, Distribution,

Use & maintenance, and End-of-Life stage

Main specifications of the product

Model name: Canon Inkjet All-In-One TS3720 Specifications

- Printers and multifunction machines (Inkjet method)
- · Maximum paper size: Legal.

Company Information

Canon Inc. 30-2, Shimomaruko 3-chome, Ohta-ku, Tokyo 146-8501, Japan +81-3-3758-2111

registration#	JI AI ZTIJJE A				
PCR number	PA-590000-AI-08				
PCR name	Imaging input and/or output equipment				
Publication date	4/26/2024				
Verification date	4/19/2024				
Verification method	System certificaion				
Verification#	JV-AI-24155				
Expiration date	4/18/2029				
PCR review was conducted by:					
Approval date	9/1/2023				
PCR review	Masayuki Kanzaki				
panel chair	Sustainable Management Promotion Organization				
Third party verifier*					

JR-AI-24155E-A

Third party verifier*

Registration#

Hiroyuki Uchida

Independent verification of data & declaration in accordance with ISO14025

□internal ■ external

Registration number: JR-AI-24155E-A

 $[\]hbox{*-} \hbox{Auditor's name is stated if system certification has been performed.} \\$



Japan EPD Program by SuMPO


Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

1. Results of life cycle impact assessment (LCIA)

Global warming IPCC2013 GWP100a 100. 0 kg-CO2eq

Acidification 0. 061 kg-SO2eq

Resources consumption 0. 011 kg-Sbeq



stage			Raw material			Use &	
Parameter	Unit	Total	acquisition	Production	Distribution	maintenance	End-of-Life
Global warming IPCC2013 GWP100a	kg-CO₂eq	1.0E+02	3.4E+01	1.8E+00	3.1E+00	5.3E+01	9.4E+00
Ozone layer destruction	kg-CFC-11eq	1.2E-05	7.7E-06	3.5E-11	8.3E-11	4.1E-06	7.1E-08
Acidification	kg-SO₂eq	6.1E-02	2.5E-02	1.8E-04	4.2E-03	2.8E-02	3.4E-03
Resources consumption	kg-Sbeq	1.1E-02	1.0E-02	6.2E-06	1.3E-05	9.6E-04	2.2E-06

2. Life cycle inventory analysis (LCI)					
Parameter		Unit			
Non-renewable energy resources	1.5E+03	MJ			
Renewable primary energy	3.0E+01	MJ			

3. Material composition					
Material		Unit			
Common Steel	11	%			
Stainless Steel	0.043	%			
Aluminium	0.0025	%			
Other Metal	2.2	%			
Plastic	45	%			
Rubber	0.75	%			
Glass	11	%			
Paper/Wood	20	%			
Circuit Board	1.7	%			
Others	8.5	%			

5. Additional explanation

Calculated in the following conditions;

- · Printing paper is not considered.
- Expected use period is 3 years.
- The standard scenario for Multifunction Device (IJ type).
- · US market.
- Print volume: 7,200 sheets.
- The applied Energy Star program version is 3.0.

We evaluated the Ecoleaf with Canon's own data of raw materials weight and the general basic unit for the parts because it is difficult to collect the data for a couple of thousands of parts. Accordingly, the results may be different from the specific product specification. As such, please be advised that this result would be a rough estimate.



Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.ip/

6-1. Supplementary environmental information

Complies with the EU RoHS Directive (2011/65/EU) and its amendments including 2015/863/EU. Manufactured at ISO 14001 certified factories.

7. Assumptions of secondary data used

IDEA v2.1.3, and registered data v1.13 of Japan EPD Program by SuMPO are used.

8. Remarks

11/20/2024 Changes to values of Material composition.

- For data quantification, please refer to PCR and Rules on quantification and declaration.
- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied. (Reference URL : https://ecoleaf-label.jp/regulation/)

Registration number: JR-AI-24155E-A