



EcoLeaf

Type III Environmental Declaration (EPD)

Registration number : JR-AI-24215E

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization

14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan

<https://ecoleaf-label.jp/>

Canon Inc.

imageRUNNER ADVANCE DX 6980i(For EU)



Functional unit

Per unit product

System boundary

final products intermediate products

Raw Material acquisition, Production, Distribution, Use & maintenance, and End-of-Life stage

Main specifications of the product

Model name

imageRUNNER ADVANCE DX 6980i(For EU)

Specifications

- Multi Functional Printer (Electrophotography)
- BW
- Print Speed : Up to 80 ipm (A4)
- Max paper size : A3
- Print/copy/scan/Duplex printing/ADF
- Weight: approx.210kg(Toner bottle not included)

Company Information

Canon Inc.

30-2, Shimomaruko 3-chome, Ohta-ku,

Tokyo 146-8501, Japan +81-3-3758-2111

Registration#	JR-AI-24215E
PCR number	PA-590000-AI-08
PCR name	Imaging input and/or output equipment
Publication date	5/22/2024
Verification date	5/17/2024
Verification method	Product-by-product
Verification#	JV-AI-24215
Expiration date	5/16/2029
PCR review was conducted by:	
Approval date	9/1/2023
PCR review panel chair	Masayuki Kanzaki Sustainable Management Promotion Organization

Third party verifier*

Kazuo Naito

Independent verification of data & declaration in accordance with ISO14025

internal


external

*Auditor's name is stated if system certification has been performed.

Registration number : JR-AI-24215E



1. Results of life cycle impact assessment (LCIA)



Parameter	stage	Unit	Total	Raw material acquisition	Production	Distribution	Use & maintenance	End-of-Life
Global warming IPCC2013 GWP100a		kg-CO ₂ eq	2.5E+03	1.4E+03	1.8E+02	1.9E+02	5.0E+02	2.3E+02
Ozone layer destruction		kg-CFC-11eq	1.7E-04	1.4E-04	5.0E-06	1.3E-09	2.2E-05	3.6E-06
Acidification		kg-SO ₂ eq	1.7E+00	1.1E+00	4.4E-02	1.9E-01	2.7E-01	8.4E-02
Resources consumption		kg-Sbeq	2.5E-01	2.4E-01	4.9E-04	8.1E-04	6.0E-03	2.1E-04

2. Life cycle inventory analysis (LCI)

Parameter	Value	Unit
Non-renewable energy resources	3.9E+04	MJ
Renewable primary energy	6.9E+02	MJ

3. Material composition

Material	Value	Unit
Common Steel	51	%
Stainless Steel	2.8	%
Aluminium	0.60	%
Other Metal	2.4	%
Plastic	19	%
Rubber	0.13	%
Glass	1.0	%
Paper/Wood	13	%
Circuit Board	3.9	%
Others	6.1	%



EcoLeaf

Type III Environmental Declaration (EPD)

Registration number : JR-AI-24215E

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization

14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan

<https://ecoleaf-label.jp/>

5. Additional explanation

Calculated in the following conditions;

- Printing paper is not considered.
- Expected use period is 5 years.
- The standard scenario for Multifunction Device (EP type).
- UK / France / Germany / Italy / Spain / Portugal / Belgium / Netherland / Austria / Switzerland / Denmark / Sweden / Norway / Finland market.
- Print volume: 960,000 sheets.
- The applied Energy Star program version is 3.0.

6-1. Supplementary environmental information

Complies with the EU RoHS Directive (2011/65/EU) and its amendments including 2015/863/EU.

Manufactured at ISO 14001 certified factories.

7. Assumptions of secondary data used

IDEA v2.1.3, and registered data v1.13 of Japan EPD Program by SuMPO are used.

8. Remarks

- For data quantification, please refer to PCR and Rules on quantification and declaration.
- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied.
(Reference URL : <https://ecoleaf-label.jp/resource/gpi/>)

Registration number : JR-AI-24215E