Japan EPD Program by SuMPO Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

at your side



BROTHER INDUSTRIES, LTD.



Functional unit

Per unit of product

System boundary

- final products □ intermediate products
 Raw material acquisition Production Distribution
 - Use & maintenance End-of-Life

Main specifications of the product

Model name: HL-L2460DW

- Printer (EP method)
- Monochrome
- Printing speed: 36ppm (Letter)
- Maximum document size: A4, Letter
- Print/Automatic duplex printing
- Product weight: 7.1kg, Packaging etc.: 1.0kg
- Wired/Wireless LAN
- * This product is for North America.

Company Information

Brother Industries, Ltd. inml-ecoleaf-jimukyoku@brother.co.jp https://global.brother/en

A-590000-AI-08 naging input and/or output equipment					
naging input and/or output equipment					
/31/2024					
/9/2024					
ystem certificaion					
/-AI-23348E					
/8/2029					
PCR review was conducted by:					
/1/2023					
asayuki Kanzaki					
stainable Management Promotion Organization					
Third party verifier*					
asuo Koseki					

Independent verification of data & declaration in accordance with ISO14025

□internal

external

*Auditor's name is stated if system certification has been performed.

Registration number : JR-AI-23348E



EcoLeaf

Registration number : JR-AI-23348E

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

1. Results of life cycle	impact as	ssessmer	nt (LCIA)				
			0%	20%	40% 6	0% 80	% 100%
Global warming IPCC2013 GWP100a	430	kg-CO2eq	1% 14%		80%	6	<mark>3%</mark>
Acidification	0.27	kg-SO2eq	0% 17%	63%		3%	2 <mark>%</mark>
Resources consumption	0.019	kg-Sbeq	32	0% 0 ⁴	%	68%	0%
		<u> </u>		material acqu ibution of-Life	isition	Production Use & maint	enance
Stage Parameter	Unit	Total	Raw material acquisition	Productio	n Distribution	Use & maintenance	End-of-Life
Global warming IPCC2013 GWP100a	kg-CO ₂ eq	4.3E+02	6.1E+01	3.5E+00) 5.9E+00	3.5E+02	1.4E+01
Acidification	kg-SO ₂ eq	2.7E-01	4.8E-02	2.6E-04	7.2E-03	2.1E-01	6.2E-03
Resources consumption	kg-Sbeq	1.9E-02	6.2E-03	9.5E-06	2.5E-05	1.3E-02	3.4E-06

2. Life cycle inventory analysis (LCI)						
Parameter		Unit				
Non-renewable material resources	1.5E+01	kg				
Non-renewable energy resources	6.3E+03	MJ				
Renewable material resources	4.1E+01	kg				
Renewable primary energy	1.6E+02	MJ				
Consumption of freshwater	5.5E-01	m³				

3. Material composition					
Material		Unit			
Steel	1.7E+00	kg			
SUS	4.6E-02	kg			
Aluminium	7.6E-02	kg			
Other metal	0.0E+00	kg			
Plastic	4.2E+00	kg			
Rubber	1.4E-01	kg			
Glass	3.3E-02	kg			
Paper and Wood	8.9E-01	kg			
Circuit board	3.2E-01	kg			
Othres	6.1E-01	kg			

5. Additional explanation

Calculation method for usage stage (scenario) : Printer (EP method), Expected use period: 5 years, Assumed usage: 192,000 sheets, Print measuring method (pattern): ISO/IEC 19798, Printing paper is not included in the environmental impact, The applied Energy Star program version is 3.0, This product is for North America.

6-1. Supplementary environmental information

This product and main compornents are produced in ISO 14001 certified factories.

7. Assumptions of secondary data used

Inventory Database: IDEA v2.1.3, and registered data of Japan EPD Program by SuMPO, JLCA data v1.10 are used.

8. Remarks

- For data quantification, please refer to PCR and Rules on quantification and declaration.

- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied. (Reference URL : https://ecoleaf-label.jp/regulation/)

Registration number : JR-AI-23348E