Japan EPD Program by SuMPO Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

brother at your side

Monochrome Laser Printer HL-L2865DW for Europe

BROTHER INDUSTRIES, LTD.



Functional unit	Dogistration#			
	Registration#	JR-AI-24163E		
Per unit of product	PCR number	PA-590000-AI-08		
System boundary	PCR name	Imaging input and/or output equipment		
■ final products □intermediate products	Publication date	7/5/2024		
Raw material acquisition - Production - Distribution	Verification date	6/24/2024		
- Use & maintenance - End-of-Life	Verification method	System certificaion		
Main specifications of the product	Verification#	JV-AI-24163E		
Model name: HL-L2865DW	Expiration date	6/23/2029		
- Printer (EP method)	PCR review was conducted by:			
- Monochrome	Approval date	9/1/2023		
- Printing Speed: 34ppm (A4)	PCR review	Masayuki Kanzaki		
- Maximum document size: A4	panel chair	Sustainable Management Promotion Organization		
- Print/Automatic duplex printing	Third party verifier*			
- Product weight: 6.9kg Packaging etc.: 2.0kg	y Yasuo Koseki			
- Wired/Wireless LAN	Independent verification of data & declaration in			
* This product is for Europe.	accordance with ISO14025			
Company Information	□internal ■external			
Brother Industries, Ltd.	*Auditor's name is stated if system certification has been performed.			
<u>inml-ecoleaf-jimukyoku@brother.co.jp</u>				
https://global.brother/en				

Registration number : JR-AI-24163E



EcoLeaf

Japan EPD Program by SuMPO

Registration number : JR-AI-24163E

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

1. Results of life cycle impact assessment (LCIA)								
			0%	20%	4(0% 60	% 80	% 100%
Global warming IPCC2013 GWP100a	380	kg-CO2eq	17%	% 1%		77%		<mark>4%</mark>
Acidification	0.24	kg-SO2eq	21%	0% 2%		75	%	<mark>3%</mark>
Resources consumption	0.018	kg-Sbeq		34%	0%0%		66%	0%
Raw material acquisition Production Distribution Use & maintenance End-of-Life Image: Control of the second								
stage Parameter	Unit	Total	Raw materi acquisition		duction	Distribution	Use & maintenance	End-of-Life
Global warming IPCC2013 GWP100a	kg-CO ₂ eq	3.8E+02	6.2E+01	3.6	6E+00	5.2E+00	2.9E+02	1.4E+01
Acidification	kg-SO ₂ eq	2.4E-01	4.9E-02	2.7	7E-04	4.6E-03	1.8E-01	6.3E-03
Resources consumption	kg-Sbeq	1.8E-02	6.1E-03	1.0	DE-05	2.2E-05	1.2E-02	3.7E-06

2. Life cycle inventory analysis (LCI)					
Parameter		Unit			
Non-renewable material resources	1.4E+01	kg			
Non-renewable energy resources	5.4E+03	MJ			
Renewable material resources	3.8E+01	kg			
Renewable primary energy	1.0E+02	MJ			
Consumption of freshwater	5.1E-01	m ³			

3. Material composition				
Material		Unit		
Steel	1.7E+00	kg		
SUS	4.5E-02	kg		
Aluminium	7.5E-02	kg		
Other metal	0.0E+00	kg		
Plastic	4.2E+00	kg		
Rubber	1.8E-01	kg		
Glass	3.1E-02	kg		
Paper and Wood	1.8E+00	kg		
Circuit board	3.0E-01	kg		
Othres	6.1E-01	kg		

5. Additional explanation

Calculation method for usage stage (scenario) : Printer (EP method), Expected use period: 5 years, Assumed usage: 172,800 sheets, Print measuring method (pattern): ISO/IEC 19798, Printing paper is not included in the environmental impact, The applied Energy Star program version is 3.0, This product is for Europe.

6-1. Supplementary environmental information

This product and main compornents are produced in ISO 14001 certified factories.

7. Assumptions of secondary data used

Inventory Database: IDEA v2.1.3, and registered data of Japan EPD Program by SuMPO, JLCA data v1.10 are used.

8. Remarks

- For data quantification, please refer to PCR and Rules on quantification and declaration.

- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied. (Reference URL : https://ecoleaf-label.jp/regulation/)