



EcoLeaf

Type III Environmental Declaration (EPD)

Registration number : JR-AI-24223E

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization  
14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan  
<https://ecoleaf-label.jp/>

Canon Inc.

imageRUNNER ADVANCE DX C568iFZ(For US)



### Functional unit

Per unit product

### System boundary

final products       intermediate products

Raw Material acquisition, Production, Distribution,  
Use & maintenance, and End-of-Life stage

### Main specifications of the product

Model name

imageRUNNER ADVANCE DX C568iFZ(For US)

Specifications

- Multi Functional Printer (Electrophotography)
- CL
- Print Speed : Up to 60 ipm (LTR)
- Max paper size : LGL
- Print/copy/scan/FAX/Duplex printing/ADF
- Weight: approx.52kg(CRG not included)

### Company Information

Canon Inc.

30-2, Shimomaruko 3-chome, Ohta-ku,  
Tokyo 146-8501, Japan +81-3-3758-2111

Registration#	JR-AI-24223E
PCR number	PA-590000-AI-08
PCR name	Imaging input and/or output equipment
Publication date	7/12/2024
Verification date	7/5/2024
Verification method	System certificaion
Verification#	JV-AI-24223
Expiration date	7/4/2029
PCR review was conducted by:	
Approval date	9/1/2023
PCR review panel chair	Masayuki Kanzaki Sustainable Management Promotion Organizati

### Third party verifier\*

Hiroyuki Uchida

Independent verification of data & declaration in accordance  
with ISO14025


internal       external

\*Auditor's name is stated if system certification has been performed.

Registration number : JR-AI-24223E



1. Results of life cycle impact assessment (LCIA)



Parameter	stage	Unit	Total	Raw material acquisition	Production	Distribution	Use & maintenance	End-of-Life
Global warming IPCC2013 GWP100a		kg-CO <sub>2</sub> eq	1.3E+03	6.5E+02	2.1E+01	3.8E+01	5.6E+02	7.2E+01
Ozone layer destruction		kg-CFC-11eq	1.8E-04	6.6E-05	3.4E-08	2.7E-10	1.1E-04	7.7E-07
Acidification		kg-SO <sub>2</sub> eq	1.1E+00	5.1E-01	7.3E-03	5.8E-02	5.1E-01	2.9E-02
Resources consumption		kg-Sbeq	1.2E-01	5.6E-02	9.5E-05	1.6E-04	6.0E-02	5.1E-05

2. Life cycle inventory analysis (LCI)

Parameter	Unit
Non-renewable energy resources	2.1E+04 MJ
Renewable primary energy	3.7E+02 MJ

3. Material composition

Material	Unit
Common Steel	29 %
Stainless Steel	0.44 %
Aluminium	0.63 %
Other Metal	2.9 %
Plastic	29 %
Rubber	0.28 %
Glass	1.3 %
Paper/Wood	28 %
Circuit Board	4.6 %
Others	4.4 %

5. Additional explanation

Calculated in the following conditions;

- Printing paper is not considered.
- Expected use period is 5 years.
- The standard scenario for Multifunction Device (EP type).
- US market.
- Print volume: 537,600 sheets.
- The applied Energy Star program version is 3.0.
- We evaluated the Ecoleaf with Canon's own data of raw materials weight and the general basic unit for the parts because it is difficult to collect the data for a couple of thousands of parts. Accordingly, the results may be different from the specific product specification. As such, please be advised that this result would be a rough estimate.



EcoLeaf

Type III Environmental Declaration (EPD)

Registration number : JR-AI-24223E

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization

14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan

<https://ecoleaf-label.jp/>

#### 6-1. Supplementary environmental information

Complies with the EU RoHS Directive (2011/65/EU) and its amendments including 2015/863/EU.

Manufactured at ISO 14001 certified factories.

#### 7. Assumptions of secondary data used

IDEA v2.1.3, and registered data v1.13 of Japan EPD Program by SuMPO are used.

#### 8. Remarks

- For data quantification, please refer to PCR and Rules on quantification and declaration.
- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied.  
(Reference URL : <https://ecoleaf-label.jp/regulation/>)

Registration number : JR-AI-24223E