Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

Canon Inc.

Canon Large Format Printer TZ-32000



Functional unit

Per unit product

System boundary

■ final products □intermediate products

Raw Material acquisition, Production, Distribution,

Use & maintenance, and End-of-Life stage

Main specifications of the product

Model name: Canon Large Format Printer TZ-32000 Specifications

- · Large Format Printer (Inkjet method)
- · Maximum paper size: 36 in.

Company Information

Canon Inc. 30-2, Shimomaruko 3-chome, Ohta-ku, Tokyo 146-8501, Japan +81-3-3758-2111

maging input and/or output equipment				
PCR review was conducted by:				
rganization				

Third party verifier*


Hiroyuki Uchida

Independent verification of data & declaration in accordance with ISO14025

□internal ■external

Registration number: JR-AI-24276E

 $[\]hbox{*-} \hbox{Auditor's name is stated if system certification has been performed.}$




Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

1. Results of life cycle impact assessment (LCIA)

Global warming IPCC2013 GWP100a	1600.0	kg-CO2eq
Acidification	0.96	kg-SO2eq
Resources consumption	0. 150	kg-Sbeq



stage Parameter	Unit	Total	Raw material acquisition	Production	Distribution	Use & maintenance	End-of-Life
Global warming IPCC2013 GWP100a	kg-CO ₂ eq	1.6E+03	9.6E+02	4.0E+01	1.7E+02	7.1E+01	3.4E+02
Ozone layer destruction	kg-CFC-11eq	1.2E-04	1.2E-04	2.4E-09	1.2E-09	1.6E-06	5.5E-06
Acidification	kg-SO₂eq	9.6E-01	6.2E-01	1.7E-03	2.1E-01	4.8E-02	8.3E-02
Resources consumption	kg-Sbeq	1.5E-01	1.5E-01	1.6E-04	7.0E-04	3.9E-04	1.1E-04

2. Life cycle inventory analysis (LCI)				
Parameter		Unit		
Non-renewable energy resources	2.1E+04	MJ		
Renewable primary energy	2.3E+02	MJ		


3. Material composition			
Material		Unit	
Common Steel	53	%	
Stainless Steel	0.85	%	
Aluminium	0.59	%	
Other Metal	1.8	%	
Plastic	18	%	
Rubber	0.042	%	
Glass	0.00	%	
Paper/Wood	24	%	
Circuit Board	0.54	%	
Others	2.1	%	

5. Additional explanation

Calculated in the following conditions;

- · Printing paper is not considered.
- Expected use period is 3 years.
- \cdot The standard scenario for Large Format Printer (IJ type).
- · US market.
- Print volume: 3,600 sheets.
- The applied Energy Star program version is 3.0.

We evaluated the Ecoleaf with Canon's own data of raw materials weight and the general basic unit for the parts because it is difficult to collect the data for a couple of thousands of parts. Accordingly, the results may be different from the specific product specification. As such, please be advised that this result would be a rough estimate.



Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.ip/

6-1. Supplementary environmental information

Complies with the EU RoHS Directive (2011/65/EU) and its amendments including 2015/863/EU. Manufactured at ISO 14001 certified factories.

7. Assumptions of secondary data used

IDEA v2.1.3, and registered data v1.13 of Japan EPD Program by SuMPO are used.

8. Remarks			
_			

- For data quantification, please refer to PCR and Rules on quantification and declaration.
- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied. (Reference URL : https://ecoleaf-label.jp/regulation/)

Registration number: JR-AI-24276E