



EcoLeaf

Type III Environmental Declaration (EPD)

Registration number : JR-AI-24338E

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization

14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan

<https://ecoleaf-label.jp/>

KONICAMINOLTA ,INC.

bizhub C451i



(Photo : Mounted option-unit(PC-216) is not included in the calculation.)

Functional unit

Per unit of product

System boundary

- final products
- intermediate products

Raw material acquisition, Production, Distribution, Use & maintenance, End-of-Life

Main specifications of the product

Model name : bizhub C451i

- Marking technologies : Electrophotographic Printer (EP)
- Printing speed(A4) : Monochrome 45 ppm
Color 45 ppm

- Printing paper : Maximum A3
- Duplex function : Standard

Company Information

Please direct any inquiries or comments to e-mail: eco-support@konicaminolta.com

Registration#	JR-AI-24338E
PCR number	PA-590000-AI-08
PCR name	Imaging input and/or output equipment
Publication date	10/7/2024
Verification date	9/27/2024
Verification method	System certificaion
Verification#	JV-AI-24338
Expiration date	9/26/2029
PCR review was conducted by:	
Approval date	9/1/2023
PCR review panel chair	Masayuki Kanzaki (Sustainable Management Promotion Organization)

Third party verifier*

Kazuo Naitou

Independent verification of data & declaration in accordance with ISO14025


internal external

*Auditor's name is stated if system certification has been performed.

Registration number : JR-AI-24338E



1. Results of life cycle impact assessment (LCIA)



Parameter	stage	Unit	Total	Raw material acquisition	Production	Distribution	Use & maintenance	End-of-Life
Global warming IPCC2013 GWP100a		kg-CO ₂ eq	1.3E+03	7.7E+02	3.7E+01	8.2E+01	2.5E+02	1.3E+02
Acidification		kg-SO ₂ eq	9.3E-01	5.8E-01	2.3E-03	9.4E-02	1.9E-01	5.9E-02
Resources consumption		kg-Sbeq	1.8E-01	9.4E-02	1.1E-04	3.3E-04	8.7E-02	1.0E-04

2. Life cycle inventory analysis (LCI)

Parameter	Unit	Unit
Non-renewable material resources	7.7E+01	kg
Renewable material resources	1.6E+02	kg

3. Material composition

Material	Unit	Unit
Steel	4.7E+01	kg
SUS	7.0E-01	kg
Al	8.2E-01	kg
Other metals	2.5E+00	kg
Glass	2.2E+00	kg
Thermoplastics resin	3.7E+01	kg
Wood	5.5E+00	kg
Paper	8.3E+00	kg
Rubber	5.6E-01	kg
Assembled circuit board	4.3E+00	kg
Medium-sized motor	5.2E+00	kg



EcoLeaf

Type III Environmental Declaration (EPD)

Registration number : JR-AI-24338E

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization

14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan

<https://ecoleaf-label.jp/>

5. Additional explanation

- Production destination : EU
- Calculation method of use stage (Caluclated by the standard scenario for MFP (EP type))
- Expected usage period : five years
- Estimated number of sheets used : 297,600
- The impact of printing paper is not included
- The impact of expendables and Maintenance parts are included in the stage of Use&maintenance.

※ Conformed to the International ENERGY STAR® Ver3.0 Program

6-1. Supplementary environmental information

7. Assumptions of secondary data used

IDEA v2.1.3 and Ecoleaf Enviromental Labeling Program Registry data v1.10

8. Remarks

- For data quantification, please refer to PCR and Rules on quantification and declaration.
- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied.
(Reference URL : <https://ecoleaf-label.jp/regulation/>)

Registration number : JR-AI-24338E