Sumpo S EPD T

SuMPO EPD

Type III Environmental Declaration (EPD)

Registration number: JR-AI-24473E

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/



EPSON

A4 inkjet printer

EP-C800 (North America)

Seiko Epson Corporation

Functional unit

Per product

System boundary

■ final products □intermediate products

Raw material acquisition, Production, Distribution, Use & maintenance, End-of-Life

Main specifications of the product

Model name: EP-C800
Main Specifications
■ Printer(Inkjet)

■ Color

■ Print speed: 25ppm (single-sided A4 sheets)

■ Maximum paper size (standard cassette): A4

■ Automatic duplex printing

%This product is destined for North America

Company Information

Seiko Epson Corporation http://www.epson.com/ http://www.epson.jp/contact/ (Japanese) 3-3-5 Owa, Suwa-shi, Nagano-ken, Japan TEL 81-266-52-5353 (Japan)

Registration#	JR-AI-24473E			
PCR number	PA-590000-AI-08			
PCR name	Imaging input and/or output equipment			
Publication date	12/10/2024			
Verification date	12/2/2024			
Verification method	Product-by-product			
Verification#	JV-AI-24473			
Expiration date	12/1/2029			
PCR review was conducted by:				
Approval date	9/1/2023			
PCR review	Masayuki Kanzaki			
panel chair	(SuMPO)			

Third party verifier*

Yasuo Koseki

Independent verification of data & declaration in accordance with ISO14025

□internal ■external

Registration number: JR-AI-24473E

^{*}Auditor's name is stated if system certification has been performed.

Registration number: JR-AI-24473E

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

5.5E-03

1.7E-05

1. Results of life cycle impact assessment (LCIA) 20% 100% 40% 60% 80% Global warming IPCC2013 GWP100a 220 kg-CO2eq 4% Acidification 0.17 kg-SO2eq 1% -0.030 Urban area air pollution kg-SO2eq 0.1% 0.1% - 0.1% ■ Raw material acquisition ■ Production Distribution ■ Use & maintenance ■ End-of-Life stage Raw material Use & **Parameter** Unit Total acquisition Production Distribution End-of-Life maintenance Global warming IPCC2013 GWP100a kg-CO₂eq 2.2E+02 1.3E+02 1.1E+01 8.8E+00 4.9E+01 1.9E+01 kg-SO₂eq 1.7E-01 9.1E-02 9.5E-04 1.5E-02 2.6E-02 3.2E-02

2.5E-02

2. Life cycle inventory analysis (LCI)				
Parameter		Unit		
Non-renewable material resources	1.1E+01	kg		
Renewable material resources	4.8E+01	kg		

kg-Sbeq

3.0E-02

3. Waste to disposal		
Parameter		Unit
Steel	5.2E+00	kg
SUS	2.4E-01	kg
Aluminum	3.0E-02	kg
Other metal	4.5E-01	kg
Plastic	1.2E+01	kg
Rubber	1.9E-01	kg
Glass	0.0E+00	kg
Paper and wood	3.2E+00	kg
Circuit Board	5.3E-01	kg
Other	1.1E+00	kg

5. Additional explanation

2.8E-05

- Product destination: North America
- Calculation method of use stage (scenario)
 - Expected usage period: 5 years
 - Estimated number of use: 90,000 sheets*
 - Print measuring method (pattern): ISO/IEC 19752

3.7E-05

- Inventory of the print paper is not included
- Products selected in the scenario used for inventory calculation
 - Printer(Inkjet)
- * In accordance with the ENERGY STAR® Ver.3.1 90,000sheets = (25 pages x 12 jobs/day x 5 days) / 4 x 4 weeks x 12 months x 5 years

6-1. Supplementary environmental information

- This product and main compornents are produced in our ISO 14001 certified factories.
- Compliant with the International Energy Star Program Ver.3.1. It also complies with the European RoHS Directive.

7. Assumptions of secondary data used

We used IDEA v2.1.3 and SuMPO Environmental Label Program registration intensity v1.13.

8. Remarks

Acidification

Resources consumption

- For data quantification, please refer to PCR and Rules on quantification and declaration.
- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied. (Reference URL : https://ecoleaf-label.jp/regulation/)

Registration number: JR-AI-24473E