

### Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

Canon Inc.

Canon Inkjet Printer PRO-200S



#### **Functional unit**

Per unit product

### **System boundary**

■ final products □intermediate products

Raw Material acquisition, Production, Distribution,

Use & maintenance, and End-of-Life stage

### Main specifications of the product

Model name: Canon Inkjet Printer PRO-200S "Specifications

- Printers and multifunction machines (Inkjet method)
- Maximum paper size: A3+"

### **Company Information**

Canon Inc. 30-2, Shimomaruko 3-chome, Ohta-ku, Tokyo 146-8501, Japan +81-3-3758-2111

Registration#	JR-AI-24445E			
PCR number	PA-590000-AI-08			
PCR name	maging input and/or output equipment			
<b>Publication date</b>	1/31/2025			
<b>Verification date</b>	.2/9/2024			
Verification method	System certificaion			
Verification#	JV-AI-24445			
<b>Expiration date</b>	12/8/2029			
PCR review was conducted by:				
Approval date	9/1/2023			
PCR review	Masayuki Kanzaki			
panel chair	Sustainable Management Promotion Organization			
Third construction	<b>.</b>			


# Third party verifier\*

Independent verification of data & declaration in accordance with ISO14025

□internal	■ external
	■ exterriar

Registration number: JR-AI-24445E


<sup>\*</sup>Auditor's name is stated if system certification has been performed.




### Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

# 1. Results of life cycle impact assessment (LCIA)





stage Parameter	Unit	Total	Raw material acquisition	Production	Distribution	Use & maintenance	End-of-Life
Global warming IPCC2013 GWP100a	kg-CO₂eq	1.9E+02	1.1E+02	6.8E+00	1.3E+01	2.9E+01	3.4E+01
Ozone layer destruction	kg-CFC-11eq	2.8E-05	2.7E-05	2.6E-10	3.7E-10	3.1E-07	2.2E-07
Acidification	kg-SO₂eq	1.1E-01	7.1E-02	5.0E-04	1.7E-02	1.4E-02	1.3E-02
Resources consumption	kg-Sbeq	3.0E-02	2.9E-02	2.6E-05	5.3E-05	1.5E-04	7.6E-06

2. Life cycle inventory analysis (LCI)				
Parameter		Unit		
Non-renewable energy resources	2.7E+03	MJ		
Renewable primary energy	3.8E+01	MJ		


3. Matı Masayuki Kanzaki				
Material		Unit		
Common Steel	20.0	%		
Stainless Steel	0.35	%		
Aluminium	0.14	%		
Other Metal	1.2	%		
Plastic	43.9	%		
Rubber	0.42	%		
Glass	0.00	%		
Paper/Wood	26.4	%		
Circuit Board	2.6	%		
Others	4.9	%		

### 5. Additional explanation

Calculated in the following conditions;

- Printing paper is not considered.
- Expected use period is 3 years.
- The standard scenario for Multifunction Device (IJ type).
- · US market.
- Print volume: 7,200 sheets.
- The applied Energy Star program version is 3.0.

We evaluated the Ecoleaf with Canon's own data of raw materials weight and the general basic unit for the parts because it is difficult to collect the data for a couple of thousands of parts. Accordingly, the results may be different from the specific product specification. As such, please be advised that this result would be a rough estimate.



# Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.ip/

# 6-1. Supplementary environmental information

Complies with the EU RoHS Directive (2011/65/EU) and its amendments including 2015/863/EU. Manufactured at ISO 14001 certified factories.

# 7. Assumptions of secondary data used

IDEA v2.1.3, and registered data v1.13 of Japan EPD Program by SuMPO are used.

8. Remarks			
_			

- For data quantification, please refer to PCR and Rules on quantification and declaration.
- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied. (Reference URL : https://ecoleaf-label.jp/regulation/)

Registration number: JR-AI-24445E