

# **RICOH COMPANY, LTD**

Color MFP (Electrophotography)



# RICOH IM C3010SD



### JR-AI-24476E **Registration#** Per product **PCR number** PA-590000-AI-08 PCR name Imaging input and/or output equipment System boundary Publication date 2/4/2025 Verification date 12/20/2024 ■ final products □intermediate products Verification method System certificaion Verification# JV-AI-24476 Expiration date 12/19/2029 Main specifications of the product PCR review was conducted by: Approval date 9/1/2023 Masayuki Kanzaki PCR review panel chair (SuMPO) Print Speed : Monochrome 30ppm ,Color 30ppm (A4) Third party verifier\* Hiroyuki Uchida Independent verification of data & declaration in accordance with ISO14025 □internal external

\*Auditor's name is stated if system certification has been performed.

Registration number : JR-AI-24476E

### **Functional unit**

Raw material acquisition, Production, Distribution, Use & maintenance, End-of-Life

Product name: RICOH IM C3010SD Main specifications: Color MFP (Electrophotography) Maximum Paper Size : A3 Function: Print /Copy /Scan Included Units in Assessment : Automatic Reversing Document Feeder, Automatic Duplexing Unit

## **Company Information**

RICOH COMPANY, LTD Tel:(03) 3777-8111



### SuMPO EPD

Type III Environmental Declaration (EPD)

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

1. Results of life cycle impact assessment (LCIA)									
			0% 2	20% 4	0% 60	0% 80%	6 100		
Global warming IPCC2013 GWP100a	750	kg-CO2eq		79	9%	49	<mark>65%</mark> 9%2 <mark>%</mark>		
Acidification	0.63	kg-SO2eq		8	0%	1%	11% 6% <mark>2</mark> %		
Resources consumption	0.76	kg-Sbeq			98%		29		
	Raw material acquisition Production   Distribution Use & maintenance   End-of-Life						enance		
Stage Parameter	Unit	Total	Raw material acquisition	Production	Distribution	Use & maintenance	End-of-Life		
Global warming IPCC2013 GWP100a	kg-CO <sub>2</sub> eq	7.5E+02	6.0E+02	3.3E+01	3.5E+01	7.1E+01	1.6E+01		
Acidification	kg-SO <sub>2</sub> eq	6.3E-01	5.0E-01	8.6E-03	6.9E-02	3.7E-02	1.5E-02		
Resources consumption	kg-Sbeq	7.6E-01	7.5E-01	1.5E-04	1.5E-04	1.3E-02	4.0E-05		

2. Life cycle inventory analysis (LCI)						
Parameter		Unit				
Non-renewable material resources	8.6E+01	kg				
Renewable material resources	9.3E+01	kg				

3. Material composition					
Material		Unit			
SUS	2.7E+00	kg			
Aluminum	1.3E+00	kg			
Ordinary steel	4.6E+01	kg			
Other metals	3.3E+00	kg			
Thermoplastic resin	4.4E+01	kg			
Thermosetting resin	8.1E-01	kg			
Glass	2.3E+00	kg			
Rubber	2.5E-01	kg			
Paper	1.7E+01	kg			
Lubricant	7.6E-03	kg			
Mounting circuit board	2.0E+00	kg			
Wood	2.8E-01	kg			



Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

\*Data derived from LCA and not assigned to the impact categories of LCIA

### 5. Additional explanation

Products selected in the scenario used for load calculation

--MFP (EP)

Product destination: DOM

- Expected usage period: 5 years
- Estimated number of sheets:135,000 sheets ※

\*\* Apply the number of sheets according to the actual usage conditions based on the product performance \*\* Compatible with International Energy Star Program Ver.3.0

- The load on the image output medium (printing paper) is not included.

6-1. Supplementary environmental information

Compliant with the International Energy Star Program Ver.3.0. It also complies with the European RoHS Directive.

Assembly production of this product and production of the main parts, photoconductor and toner, are carried out at an ISO14001 certified factory.

Certification number: JQA-E-70001

Certification number: EMS646026

https://jp.ricoh.com/sustainability/environment/management/iso

7. Assumptions of secondary data used

IDEA v2.1.3, and registered data of Japan EPD Program by SuMPO v1.13 are used.

8. Remarks

- For data quantification, please refer to PCR and Rules on quantification and declaration.

- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied. (Reference URL : https://ecoleaf-label.jp/regulation/)

Registration number : JR-AI-24476E