

RICOH COMPANY, LTD

Black and White MFP (Electrophotography)



RICOH IM 430FLT



Functional unit

Per product

System boundary

■ final products □ intermediate products Raw material acquisition,Production,Distribution, Use & maintenance,End-of-Life

Main specifications of the product

Product name: RICOH IM 430FLT Main specifications: Black and White MFP (Electrophotography) Print Speed : 43 prints/minute (A4) Maximum Paper Size : A4 Function: Print /Copy /Scan /FAX Included Units in Assessment : Automatic Reversing Document Feeder, Automatic Duplexing Unit

Registration#	JR-AI-24525E			
PCR number	PA-590000-AI-08			
PCR name	Imaging input and/or output equipment			
Publication date	2/28/2025			
Verification date	2/5/2025			
Verification method	System certificaion			
Verification#	JV-AI-24525			
Expiration date	2/4/2030			
PCR review was conducted by:				
Approval date	9/1/2023			
PCR review	Masayuki Kanzaki			
panel chair	(SuMPO)			
Third party verifier*				
	Hirovuli Uchida			

Hiroyuki Uchida

Independent verification of data & declaration in accordance with ISO14025

*Auditor's name is stated if system certification has been performed.

external

Company Information

RICOH COMPANY,LTD Tel:(03) 3777-8111

Registration number : JR-AI-24525E

□internal



SuMPO EPD

Type III Environmental Declaration (EPD)

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

Japan EPD Program by SuMPO

1. Results of life cycle impact assessment (LCIA)									
			0%	20% 4	0% 60	0% 80%	% 100%		
Global warming IPCC2013 GWP100a	510	kg-CO2eq		56%	69	<mark>63</mark> % 34	1% 1 <mark>%</mark>		
Acidification	0.38	kg-SO2eq		64%		1 <mark>%6%</mark>	29% 1 <mark>%</mark>		
Resources consumption	0.33	kg-Sbeq			93%		7%		
Raw material acquisition Production Distribution Use & maintenance End-of-Life End-of-Life									
Stage Parameter	Unit	Total	Raw material acquisition	Production	Distribution	Use & maintenance	End-of-Life		
Global warming IPCC2013 GWP100a	kg-CO ₂ eq	5.1E+02	2.9E+02	3.3E+01	1.3E+01	1.7E+02	5.0E+00		
Acidification	kg-SO ₂ eq	3.8E-01	2.4E-01	3.4E-03	2.2E-02	1.1E-01	4.2E-03		
Resources consumption	kg-Sbeq	3.3E-01	3.1E-01	6.6E-05	5.5E-05	2.4E-02	1.3E-05		

2. Life cycle inventory analysis (LCI)					
Parameter		Unit			
Non-renewable material resources	2.2E+01	kg			
Renewable material resources	5.8E+01	kg			

3. Material composition					
Material		Unit			
SUS	2.3E-01	kg			
Aluminum	2.7E-01	kg			
Ordinary steel	1.0E+01	kg			
Other metals	8.3E-01	kg			
Thermoplastic resin	1.7E+01	kg			
Thermosetting resin	3.0E-01	kg			
Glass	1.0E+00	kg			
Rubber	1.4E-01	kg			
Paper	4.0E+00	kg			
Lubricant	7.0E-04	kg			
Mounting circuit board	9.8E-01	kg			
Wood	8.9E-05	kg			



Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

*Data derived from LCA and not assigned to the impact categories of LCIA

5. Additional explanation

Products selected in the scenario used for load calculation

--MFP (EP)

Product destination: DOM

• Expected usage period: 5 years

+ Estimated number of sheets:268,800 sheets \times

** Apply the number of sheets according to the actual usage conditions based on the product performance ** Compatible with International Energy Star Program Ver.3.0

- Print rate: Standard data specified in ISO/IEC 19798 (A4).

- The load on the image output medium (printing paper) is not included.

6-1. Supplementary environmental information

Compliant with the International Energy Star Program Ver.3.0. It also complies with the European RoHS Directive.

Assembly production of this product and production of the main parts, photoconductor and toner, are carried out at an ISO14001 certified factory.

Certification number: JQA-E-70001

Certification number: CN18/20330

https://jp.ricoh.com/sustainability/environment/management/iso

7. Assumptions of secondary data used

IDEA v2.1.3, and registered data of Japan EPD Program by SuMPO v1.13 are used.

8. Remarks

- For data quantification, please refer to PCR and Rules on quantification and declaration.

- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied. (Reference URL : https://ecoleaf-label.jp/regulation/)

Registration number : JR-AI-24525E