Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/



3-in-1 Monochrome Laser Printer

DCP-L2660DW for Europe

BROTHER INDUSTRIES, LTD.



Functional unit

Per unit of product

System boundary

■ final products □intermediate products Raw material acquisition - Production - Distribution

- Use & maintenance - End-of-Life

Main specifications of the product

Model name: DCP-L2660DW

- Multifunction device(EP method)
- Monochrome
- Printing Speed: 34ppm (A4)
- Maximum paper size : A4
- Print/Copy/Scan/Automatic duplex printing Automatic document feeding
- -Wired/Wireless LAN
- * This product is for Europe.

Company Information

Brother Industries, Ltd.

inml-ecoleaf-jimukyoku(at)brother.co.jp

https://global.brother/en

Registration#	JR-AI-24415E	
PCR number	PA-590000-AI-08	
PCR name	Imaging input and/or output equipment	
Publication date	3/11/2025	
Verification date	2/27/2025	
Verification method	System certificaion	
Verification#	JV-AI-24415E	
Expiration date	2/26/2030	
PCR review was conducted by:		
Approval date	9/1/2023	
PCR review	Masayuki Kanzaki	

panel chair Third party verifier*

Yasuo Koseki

- Product weight: 11.3kg, Packaging etc.: 3.0kg Independent verification of data & declaration in accordance with ISO14025

□internal

■ external

Sustainable Management Promotion Organization

Registration number: JR-AI-24415E

^{*}Auditor's name is stated if system certification has been performed.

EcoLeaf Type III Environmental Declaration(EPD) Registration number: JR-AI-24415E

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

1. Results of life cycle impact assessment (LCIA) 0% 20% 60% 80% 100% 40% 1% 1% Global warming IPCC2013 GWP100a 590 kg-CO2eq 78% 0%2% Acidification 0.35 kg-SO2eq 0% 0% Resources consumption 0.025 kg-Sbeq Raw material acquisition ■ Production Distribution ■ Use & maintenance ■ End-of-Life stage Raw material Use & **Parameter** Unit **Total** acquisition Production Distribution maintenance End-of-Life kg-CO2eq 5.9E+02 Global warming IPCC2013 GWP100a 9.3E+01 5.3E+00 8.3E+00 4.6E+02 2.3E+01 Acidification kg-SO₂eq 3.5E-01 6.9E-02 3.9E-04 7.3E-03 2.6E-01 1.1E-02 Resources consumption kg-Sbeq 2.5E-02 8.0E-03 1.5E-05 3.5E-05 1.7E-02 5.9E-06

2. Life cycle inventory analysis (LCI)			
Parameter		Unit	
Non-renewable material resources	2.7E+01	kg	
Non-renewable energy resources	8.6E+03	MJ	
Renewable material resources	6.4E+01	kg	
Renewable primary energy	1.7E+02	MJ	
Consumption of freshwater	7.1E-01	m ³	

3. Material composition			
Material		Unit	
Steel	2.4E+00	kg	
SUS	6.4E-02	kg	
Aluminium	7.5E-02	kg	
Other metal	0.0E+00	kg	
Plastic	7.3E+00	kg	
Rubber	1.8E-01	kg	
Glass	6.7E-01	kg	
Paper and Wood	2.5E+00	kg	
Circuit board	4.1E-01	kg	
Othres	7.5E-01	kg	

5. Additional explanation

Calculation method for usage stage (Scenario): Multifunction device(EP method), Expected use period: 5 years, Assumed usage: 172,800 sheets, Print measuring method (Pattern): ISO/IEC 19798, Printing paper is not included in the environmental impact, The applied Energy Star program version is 3.0, This product is for Europe.

6-1. Supplementary environmental information

This product and main compornents are produced in ISO 14001 certified factories.

7. Assumptions of secondary data used

Inventory Database: IDEA v2.1.3, and registered data of Japan EPD Program by SuMPO, JLCA data v1.18 are used.

8. Remarks

| =

- For data quantification, please refer to PCR and Rules on quantification and declaration.
- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied. (Reference URL: https://ecoleaf-label.jp/regulation/)

Registration number: JR-AI-24415E