



EcoLeaf

Type III Environmental Declaration (EPD)

Registration number : JR-AI-24595E

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization

14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan

<https://ecoleaf-label.jp/>



A3 Color Multifunction Printer

Apeos C4571 (Model-CPS) (for AU)

FUJIFILM

Value from Innovation

富士フイルム ビジネス イノベーション株式会社
FUJIFILM Business Innovation Corp.

The image above shows "Apeos C5571", but the actual product is labeled "Apeos C4571".

Apeos, Apeos logo and ApeosPlus are registered trademarks or trademarks of FUJIFILM Business Innovation Corp. in Japan and/or other countries.

Functional unit

Per unit of product

System boundary

- final products intermediate products

Raw material acquisition, Production, Distribution,
Use & Maintenance, End-of-Life

Main specifications of the product

- Model: Apeos C4571(Model-CPS)
- Color Multifunction Printer (EP Type)
- Print Speed (A4 LEF): Color 45ppm, Monochrome 45ppm
- Paper Size (Max.): A3,12x18"(305x457mm),
SRA3(320x450mm)
- Copy / Print / Scan
- Automatic 2 Sided Output,
Automatic Document Feeder

Company Information

FUJIFILM Business Innovation Corp.

6-1 Minatomirai, Nishi-ku, Yokohama-shi, Kanagawa Japan

<https://www.fujifilm.com/fbglobal/eng>

Registration#	JR-AI-24595E
PCR number	PA-590000-AI-08
PCR name	Imaging input and/or output equipment
Publication date	3/10/2025
Verification date	2/28/2025
Verification method	System certificaion
Verification#	2024-FB-EL-071
Expiration date	2/27/2030

PCR review was conducted by:

Approval date	9/1/2023
PCR review panel chair	Masayuki Kanzaki Sustainable Management Promotion Organization

Third party verifier*

Sachiko Hashizume

Independent verification of data & declaration in accordance with ISO14025


internal external

*Auditor's name is stated if system certification has been performed.

Registration number : JR-AI-24595E



1. Results of life cycle impact assessment (LCIA)



Parameter	stage	Unit	Total	Raw material acquisition	Production	Distribution	Use & maintenance	End-of-Life
Global warming IPCC2013 GWP100a		kg-CO ₂ eq	1.4E+03	9.2E+02	3.3E+01	6.8E+01	2.3E+02	1.1E+02
Acidification		kg-SO ₂ eq	1.0E+00	6.8E-01	3.3E-03	9.6E-02	1.1E-01	1.0E-01
Resources consumption		kg-Sbeq	9.8E-01	8.9E-01	1.5E-04	2.9E-04	9.4E-02	1.7E-04
Water resource consumption		m ³	2.0E+00	1.7.E+00	1.3.E-02	4.0.E-03	3.2.E-01	4.4.E-03

2. Life cycle inventory analysis (LCI)

Parameter	Unit
Renewable material resources	2.6E+02 kg
Non-renewable material resources	1.1E+02 kg
Renewable energy resources	4.6E+02 MJ
Non-renewable energy resources	5.2E+02 MJ
Consumption of freshwater	1.9E+00 m ³

3. Material composition

Material	Unit
Steel	61 kg
SUS	0.87 kg
Aluminium	0.72 kg
Other Metals	6.6 kg
Plastic	48 kg
Rubber	0.15 kg
Glass	2.0 kg
Paper, Wood	9.3 kg
Circuit Board	4.4 kg
Conversion Parts	4.8 kg
Others	3.4 kg

5. Additional explanation

- Product destination: Australia
- Calculated based on standard scenario for MFP (EP type).
- Assumed lifespan of the product is five years.
- Printing paper is excluded from Use & maintenance stage.
- The applied International ENERGY STAR® Program Version is 3.0.
- Assumed print volume are 297,600 sheets.
1/4 x 32 (jobs per day) x 31 (sheets per job) x 5 (days) x 4 (weeks) x 12 (months) x 5 (years) = 297,600 (sheets)



EcoLeaf

Type III Environmental Declaration (EPD)

Registration number : JR-AI-24595E

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization
14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan
<https://ecoleaf-label.jp/>

6-1. Supplementary environmental information

7. Assumptions of secondary data used

Inventory Database: LCI Database IDEA v2.1.3, Japan EPD Program by SuMPO registered data v1.18.

8. Remarks

- For data quantification, please refer to PCR and Rules on quantification and declaration.
- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied.
(Reference URL : <https://ecoleaf-label.jp/regulation/>)

Registration number : JR-AI-24595E