EcoLeaf Type III Environmental Declaration (EPD) Registration number : JR-AI-24631E

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/



Color MFD TASKalfa MZ5001ci(US)

KYOCERA Document Solutions Inc.

The impact of following options is not included. ADF Paper Feeder (\times 2)

Functional unit

Per unit of product

System boundary

- final products □intermediate products
- Raw material acquisition-Production-Distribution-

Use & maintenance-End-of-Life

Main specifications of the product

Model name : Color MFD

TASKalfa MZ5001ci(US)

Making Technology : Electrophotographic Printer (EP) Printng Speed:

Monochrome 50 pages per minute in A4 Color 50 pages per minute in A4

Priting paper : Maximum A3 Duplex function: Standard ADF: Option Copy / Print / Scan / FAX (FAX: Option)

Company Information

KYOCERA Document Solutions Inc. Quality Assurance Division Reliability Assurance Section 21 TEL : 06-6764-3764 https://www.kyoceradocumentsolutions.co.jp

Registration#	JR-AI-24631E		
PCR number	PA-590000-AI-08		
PCR name	Imaging input and/or output equimpent		
Publication date	3/31/2025		
Verification date	3/12/2025		
Verification method	System certificaion		
Verification#	JV-AI-24631E		
Expiration date	3/11/2030		
PCR review was conducted by:			
Approval date	9/1/2023		
PCR review	Masayuki Kanzaki		
panel chair	Sustanable Management Promotion Organization		

Third party verifier*

Hiroyuki Uchida

Independent verification of data & declaration in accordance with ISO14025

□internal

external

*Auditor's name is stated if system certification has been performed.

Registration number : JR-AI-24631E



EcoLeaf

Type III Environmental Declaration (EPD)

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

Registration number : JR-AI-24631E

1. Results of life cycle i	mpact as	sessment	(LCIA)				
			0%	20%	40% 6	0% 80	% 100%
Global warming IPCC2013 GWP100a	1200	kg-CO2eq		63%		9% 2 <mark>%</mark>	18% 8%
Acidification	1.20	kg-SO2eq		58%	19	× 20%	11% 10%
Resources consumption	0.092	kg-Sbeq			98%		078%
Raw material acquisition Production Distribution Use & maintenance End-of-Life							
stage			Raw material			Use &	
Parameter	Unit	Total	acquisition	Production	Distribution	maintenance	End-of-Life
Global warming IPCC2013 GWP100a	kg-CO ₂ eq	1.2E+03	7.8E+02	2.1E+01	1.1E+02	2.3E+02	9.5E+01
Acidification	kg-SO₂eq	1.2E+00	6.9E-01	7.3E-03	2.3E-01	1.3E-01	1.2E-01
Resources consumption	kg-Sbeq	9.2E-02	9.0E-02	8.8E-05	4.5E-04	1.5E-03	1.0E-04

2. Life cycle inventory analysis (LCI)						
Parameter		Unit				
Non-renewable material resources	8.8E+01	kg				
Non-renewable energy resources	1.9E+04	MJ				
Renewable material resources	2.3E+02	kg				
Renewable primary energy	3.3E+02	MJ				

3. Material composition		
Material		Unit
Steel	4.4E+01	kg
SUS	2.0E+00	kg
Cu	2.0E+00	kg
Al	1.2E+00	kg
Other metals	3.1E-02	kg
Glass	2.4E+00	kg
Thermoplastics resin	3.9E+01	kg
Thermosetting resin	1.2E+00	kg
Rubber	5.9E-02	kg
Paper	1.2E+01	kg
Wood	1.1E+01	kg
Assembled circuit board	3.5E+00	kg
Medium-sized motor	3.2E+00	kg

5. Additional explanation

- Product destination: North America
- Calculation method of use stage (scenario)

 $\textcircled{1}\mathsf{E}\mathsf{x}\mathsf{pected}$ usage period: five years

②Estimated number of sheets used:Monoclome 187,200 Color 187,200

③The impact of printing paper is not included

 $\boldsymbol{\cdot}$ Products selected in the scenario used

for inventory calculation :

- Copier, Printer and Multifunction device (EP) • Conformed to the International
 - ENERGY STAR® Ver3.2 Program

· Consumables will be shipped directly from the factory to

the country of sale separately from the product body and all of them are accounted for in the use and maintenance



EcoLeafType III Environmental Declaration (EPD)

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

Registration number : JR-AI-24631E

6-1. Supplementary environmental information

 \cdot Conformed to the International ENERGY STAR $\ensuremath{\mathbb{R}}$ Program

Manufactured at ISO14001 certified factories.

 $\boldsymbol{\cdot}$ Halogenated flame retardants are not used in Plastic housing and outer package.

7. Assumptions of secondary data used

IDEA v2.1.3 and Japan EPD Program by SuMPO Registry data v1.17

8. Remarks

-

- For data quantification, please refer to PCR and Rules on quantification and declaration.

- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied.

(Reference URL : https://ecoleaf-label.jp/regulation/)

Registration number : JR-AI-24631E