

SuMPO EPD Type III Environmental Declaration (EPD)

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

Registration number: JR-AI-20116E-B



4-in-1 Colour Laser Printer

MFC-L8690CDW for Europe

BROTHER INDUSTRIES, LTD.



Functional unit

Per unit of product

System boundary

Main specifications of the product

Model name: MFC-L8690CDW

Multifunction device (Colour EP method)

Printing Speed:31ppm (A4) Maximum paper size : A4

Print/Copy/Scan/FAX/Automatic duplex printing/

Automatic document feeding

Wired/Wireless LAN

Product weight: 25.8kg, Packaging etc.: 7.1kg

* This product is for Europe.

Company Information

Brother Industries, Ltd.

inml-ecoleaf-jimukyoku(at)brother.co.jp

https://global.brother/en

| Registration# | JR-AI-20116E-B | | | |
|------------------------------|---|--|--|--|
| PCR number | PA-590000-AI-08 | | | |
| PCR name | Imaging input and/or output equipment | | | |
| Publication date | 10/28/2025 | | | |
| Verification date | 10/15/2025 | | | |
| Verification method | System certificaion | | | |
| Verification# | JV-AI-20116E-B | | | |
| Expiration date | 10/14/2030 | | | |
| PCR review was conducted by: | | | | |
| Approval date | 9/1/2023 | | | |
| PCR review | Masayuki Kanzaki | | | |
| panel chair | Sustainable Management Promotion Organization | | | |

Third party verifier*

Yasuo Koseki

Independent verification of data & declaration in accordance with ISO14025

| □internal | ■external | |
|-----------|-----------|--|
| | | |

Registration number: JR-AI-20116E-B

 $^{{}^{*}}$ Auditor's name is stated if system certification has been performed.



SuMPO EPD Type III Environmental Declaration (EPD)

Japan EPD Program by SuMPO
Sustainable Management Promotion
Organization

14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

| Results of life cycle impact as | sessment (LCI <i>A</i> | 4) | | | | |
|--|------------------------|--------------------------|------------|--------------|-------------------|-------------|
| | | Raw material acquisition | Production | Distribution | Use & maintenance | End-of-Life |
| Global Warming Potential total (GWP-total) | kg-CO₂eq | 2.16E+02 | 1.74E+01 | 1.94E+01 | 5.74E+02 | 5.54E+01 |
| Acidification | kg-SO₂eq | 6.41E-01 | 1.54E-01 | 1.28E-02 | 2.28E+00 | 3.72E-02 |
| ADP elements | ka-Sbea | 1 13F-02 | 3 89F-05 | 3 76F-08 | 8 09F-02 | 7 15F-06 |

| Life cycle inventory analysis (LCI) | | | | | | |
|--------------------------------------|-------------|---------------------------|------------|--------------|-------------|-------------|
| Indicators describing use of primary | / resources | | | | | |
| | | Raw material acquisition | Production | Distribution | Use & | End-of-Life |
| | | Tall Haterial acquisition | Troduction | Distribution | maintenance | End of Enc |
| RPR _E | MJ | 5.43E+02 | 1.33E+02 | 3.66E-02 | 3.47E+03 | 1.58E+01 |
| RPR _M | MJ | 7.14E+00 | 1.52E-01 | 1.67E-04 | 4.66E+01 | 2.96E-03 |
| NRPR _E | MJ | 3.71E+03 | 3.60E+02 | 2.17E+02 | 1.09E+04 | 8.55E+01 |
| NRPR _M | MJ | 7.59E+02 | 7.97E-01 | 4.17E-04 | 1.62E+03 | 5.19E-02 |

RPRE = renewable primary resources used as an energy carrier (fuel)

RPRM = renewable primary resources with energy content used as material

NRPRE = non-renewable primary resources used as an energy carrier (fuel)

NRPRM = non-renewable primary resources with energy content used as material

JR-AI-20116E-B

Additional explanation

Calculation method for usage stage (Scenario): Multifunction device(EP method), Expected use period: 5 years, Assumed usage: 139,500 sheets, Print measuring method (Pattern): ISO/IEC 19798, Printing paper is not included in the environmental impact, The applied Energy Star program version is 3.0, This product is for Europe.

Supplementary environmental information

This product and main compornents are produced in our ISO 14001 certified factories.

| Material composition | | | | |
|----------------------|---------|------|--|--|
| Material | | Unit | | |
| Steel | 7.6E+00 | kg | | |
| SUS | 2.8E-01 | kg | | |
| Aluminium | 4.2E-01 | kg | | |
| Other metal | 4.5E-03 | kg | | |
| Plastic | 1.7E+01 | kg | | |
| Rubber | 1.6E-01 | kg | | |
| Glass | 1.0E+00 | kg | | |
| Paper and Wood | 4.0E+00 | kg | | |
| Circuit board | 1.0E+00 | kg | | |
| Othres | 1.8E+00 | kg | | |

| Assumptions of secondary data used |
|--|
| Inventory Database: IDEA v3.4, and registered data of Japan EPD Program by |
| SuMPO, JLCA data v1.16 are used. |

| Remarks | | |
|--------------------|-----------------|--|
| 15 October 2025: F | Re-verification | |
| | | |
| | | |
| | | |

- For data quantification, please refer to PCR and Rules on quantification and declaration.
- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied. (Reference URL: https://ecoleaf-label.jp/regulation/)
- This is a selfdeclared translation of EPD that can be accessed at https://ecoleaf-label.jp/epd/217 and is published for convenience purposes. Only the original EPD is valid and binding between parties.