Ecolear Environmental Labeling Program
Sustainable Management Promotion Organization
2-1, Kaji-cho 2 chome, Chiyoda-ku, Tokyo Japan
https://ecoleaf-label.jp/
1,,, 51,

Ecoloaf Environmental Labeling Progra

RICOH COMPANY, LTD

RICOH imagine. change.



Black and White MFP (Electrophotography)

IM 7000



Functional	unit
Tunctiona	unit

Per product

System boundary

■ final products □intermediate products Raw material acquisition,Production,Distribution, Use & maintenance,End-of-Life

Main specifications of the product

Product name:IM 7000 Product destination: NA Main specifications: Black and White MFP (Electrophotography) Print Speed : 70 prints/minute (A4) Maximum Paper Size : 11" x 17" Included Units in Assessment : Automatic Reversing Document Feeder, Automatic Duplexing Unit **Company Information** RICOH COMPANY,LTD Tel:(03) 3777-8111

Registration#	JR-AI-21046E-A
PCR number	PA-590000-AI-03
PCR name	Imaging input and/or output equipment
Publication date	3/15/2021
Verification date	11/2/2021
Verification method	System certificaion
Verification#	JV-AI-20121
Expiration date	11/1/2026
PCR review was conducted by:	
Approval date	11/8/2019
PCR review	Masayuki Kanzaki
panel chair	(SuMPO)
Third party verified	er*

Yasuo Koseki

Independent verification of data & declaration in accordance with ISO14025

□internal

external

*Auditor's name is stated if system certification has been performed.

Registration number : JR-AI-21046E-A



EcoLeaf

Ecoleaf Environmental Labeling Program

Registration number : JR-AI-21046E-A

Sustainable Management Promotion Organization 2-1, Kaji-cho 2 chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

1. Results of life cycle i	mpact as	sessment	t (LCIA)				
			0%	20% 4	.0% 60	0% 80%	% 100%
Global warming IPCC2013 GWP100a	1800	kg-CO2eq		59%	2	<mark>%5%</mark> 20%	14%
Acidification	1.5	kg-SO2eq		71%	•	1 <mark>% 9%</mark>	8% 11%
Resources consumption	0. 62	kg-Sbeq	Paw	material acquisit	99%	Production	0%
				ibution	.1011	Use & maint	enance
stage Parameter	Unit	Total	Raw material acquisition	Production	Distribution	Use & maintenance	End-of-Life
Global warming IPCC2013 GWP100a	kg-CO ₂ eq	1.8E+03	1.1E+03	3.8E+01	9.5E+01	3.5E+02	2.6E+02
Acidification	kg-SO ₂ eq	1.5E+00	1.0E+00	1.3E-02	1.3E-01	1.2E-01	1.6E-01
Resources consumption	kg-Sbeq	6.2E-01	6.2E-01	1.7E-04	4.0E-04	5.0E-03	2.5E-04

2. Life cycle inventory analysis (LCI)				
Parameter		Unit		
Non-renewable material resources	1.9E+02	kg		
Renewable material resources	1.9E+02	kg		

3. Material composition				
Material		Unit		
SUS	3.4	kg		
Aluminum	4.5	kg		
Ordinary steel	140.7	kg		
Other metals	6.9	kg		
Thermoplastic resin	44.4	kg		
Thermosetting resin	1.1	kg		
Glass	2.3	kg		
Rubber	0.2	kg		
Paper	18.4	kg		
Lubricant	0.1	kg		
Mounting circuit board	1.7	kg		
Wood	14.2	kg		

*Data derived from LCA and not assigned to the impact categories of LCIA

5. Additional explanation

-Products selected in the scenario used for load calculation --Multifunction device (EP)

Product destination: NA ※

** Transportation scenarios are for China, Thailand, and Ricoh Group.from three production sites in Japan, North America, Europe, on transportation routes to the five poles of China, Oceania and Japan transport load calculate the weighted average of transportation activity per kg of product from the total calculated using

the annual production volume for each pole .

Then, it is used as a transportation unit of calcuration.

• Expected usage period: 5 years

Estimated number of sheets:729600 sheets ※

Compatible with International Energy Star Program Ver.3.0
-The load on the image output medium (printing paper) is not included.



EcoLeaf

Registration number : JR-AI-21046E-A

Ecoleaf Environmental Labeling Program

Sustainable Management Promotion Organization 2-1, Kaji-cho 2 chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

6-1. Supplementary environmental information

Compliant with the International Energy Star Program Ver.3.0. It also complies with the European RoHS Directive.

Assembly production of this product and production of the main parts, photoconductor and toner, are carried out at an ISO14001 certified

7. Assumptions of secondary data used IDEA v2.1.3 is used and registration data and JLCA data v1.07 are used.

8. Remarks

Change date : 12/20/2021 Periodic examination To respond to the points pointed out Change Results of life cycle impact assessment (LCIA)

Global warming IPCC2013 GWP100a detail: End-of-Life 2.1E+02 \rightarrow 2.6E+02 Acidification 1.4 \rightarrow 1.5kg-SO2eq Acidification detail: Use & maintenance 1.3E-01 \rightarrow 1.2E-01 End-of-Life 1.1E-01 \rightarrow 1.6E-01 Resources consumption detail: End-of-Life 1.1E-04 \rightarrow 2.5E-04 Verification date 3/5/2021 \rightarrow 11/2/2021

For data quantification, please refer to PCR and Rules on quantification and declaration.
Comparative assertion is permitted only when Rules on quantification and declaration are satisfied.

(Reference URL : https://ecoleaf-label.jp/regulation/)