

SuMPO EPD Type III Environmental Declaration (EPD)

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.ip/

Registration number: JR-AI-25018E



Inkjet All-in-One Printer

MFC-J4355DW for North America



Functional unit

Per unit of product

System boundary

Main specifications of the product

Model name: MFC-J4355DW

Multifunction device (IJ method)

Product weight: 8.4kg Packaging etc.: 1.7kg

Maximum paper size : A4, Letter

Print/Copy/Scan/FAX/Automatic duplex printing/

Automatic document feeding

Wireless LAN

* This product is for North America.

R	egistration#	JR-AI-25018E			
	PCR number	PA-590000-AI-08			
	PCR name	Imaging input and/or output equipment			
Pu	blication date	8/8/2025			
Ve	rification date	7/18/2025			
Veri	ification method	System certificaion			
V	erification#	JV-AI-25018E			
Ex	piration date	7/17/2030			
PCF	PCR review was conducted by:				
	Approval date	9/1/2023			
	PCR review	Masayuki Kanzaki			
	panel chair	Sustainable Management Promotion Organization			

Third party verifier*

Yasuo Koseki

Independent verification of data & declaration in accordance with ISO14025

□internal **■** external

Company Information

Brother Industries, Ltd. inml-ecoleaf-jimukyoku(at)brother.co.jp https://global.brother/en

 * Auditor's name is stated if system certification has been performed.

Registration number: JR-AI-25018E



SuMPO EPD Type III Environmental Declaration (EPD)

JR-AI-25018E

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

Results of life cycle impact assessment (LCIA)							
		Raw material acquisition	Production	Distribution	Use & maintenance	End-of-Life	
Global Warming Potential total (GWP-total)	kg-CO₂eq	8.21E+01	8.26E+00	8.79E+00	8.12E+00	1.63E+01	
Acidification	kg-SO₂eq	1.94E-01	5.54E-02	1.53E-02	2.73E-02	1.03E-02	
ADP elements	kg-Sbeg	5.89E-03	1.14E-05	4.21E-06	1.74E-04	1.60E-06	

Life cycle inventory analysis (LCI)							
Indicators describing use of primary resources							
	Raw material acquisition	Production	Distribution	Use & maintenance	End-of-Life		
RPR _E	MJ	1.39E+02	6.78E+01	9.62E+00	3.40E+01	3.50E+00	
RPR _M	MJ	9.99E+00	1.87E-02	2.23E-04	2.45E+00	6.83E-04	
NRPR _E	MJ	1.24E+03	1.22E+02	1.23E+02	1.88E+02	2.29E+01	
NRPR _M	MJ	2.33E+02	3.59E-01	1.23E-02	2.28E+01	1.32E-02	

Additional explanation

Calculation method for usage stage (Scenario): Multifunction device(IJ method), Expected use period:3 years, , Assumed usage: 7,200 sheets, Printing paper is not included in the environmental impact, The applied Energy Star program version is 3.0, This product is for North America.

Supplementary environmental information

This product and main compornents are produced in our ISO 14001 certified factories.

Material composition					
Material		Unit			
Steel	1.3E+00	kg			
SUS	5.9E-02	kg			
Aluminium	1.2E-01	kg			
Other metal	4.5E-03	kg			
Plastic	4.8E+00	kg			
Rubber	7.9E-02	kg			
Glass	6.3E-01	kg			
Paper and Wood	1.6E+00	kg			
Circuit board	5.7E-01	kg			
Othres	8.7E-01	kg			

Assumptions of secondary data used
Inventory Database: IDEA v3.4, and registered data of Japan EPD Program by
SuMPO, JLCA data v1.16 are used.

Remarks			
_			

- For data quantification, please refer to PCR and Rules on quantification and declaration.
- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied. (Reference URL: https://ecoleaf-label.jp/regulation/)
- This is a selfdeclared translation of EPD that can be accessed at https://ecoleaf-label.jp/epd/2374 and is published for convenience purposes. Only the original EPD is valid and binding between parties.