

SuMPO EPD Type III Environmental Declaration (EPD)

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

Registration number: JR-AI-25185E





富士フイルム ビジネス イノベーション株式会社 FUJIFILM Business Innovation Corp.

Remanufactured Product A3 Color Multifunction Printer

ApeosPort-VI C3371 R (for AU)

Apeos, Apeos logo, ApeosPro, ApeosPort and ApeosPrint are registered trademarks or trademarks of FUJIFILM Business Innovation Corp. in Japan and/or other countries.

Xerox, the Xerox logo, and the Fuji Xerox logo are registered trademarks or trademarks of Xerox Corporation.

Functional unit

Per unit of product

System boundary

■ final products □intermediate products

Raw material acquisition, Production, Distribution,

Use & Maintenance, End-of-Life

Main specifications of the product

- Model: ApeosPort-VI C3371 R
- Color Multifunction Printer (EP Type)
- Print Speed (A4 LEF): Color 35ppm, Monochrome 35ppm
- Paper Size (Max.): SRA3(320×450 mm)、 12×18"(305×457 mm)、A3
- Copy / Print / Scan
- Automatic 2 Sided Output,

Automatic Document Feeder

	Registration#	JR-AI-25185E	
	PCR number	PA-590000-AI-08	
	PCR name	Imaging input and/or output equipment	
	Publication date	10/7/2025	
	Verification date	9/18/2025	
	Verification method	System certificaion	
	Verification#	2025-FB-EL-040	
	Expiration date	9/17/2030	
	PCR review was conducted by:		
	Approval date	9/1/2023	
	PCR review	Masayuki Kanzaki	
1	panel chair	Sustainable Management Promotion Organization	
1	Verification# Expiration date PCR review was Approval date PCR review	System certificaion 2025-FB-EL-040 9/17/2030 conducted by: 9/1/2023 Masayuki Kanzaki	

Third party verifier*

Sachiko Hashizume

Independent verification of data & declaration in accordance with ISO14025

ternal
ex

Company Information

FUJIFILM Business Innovation Corp.

6-1 Minatomirai, Nishi-ku, Yokohama-shi, Kanagawa Japan https://www.fujifilm.com/fbglobal/eng

Registration number: JR-AI-25185E

^{*}Auditor's name is stated if system certification has been performed.





SuMPO EPD Type III Environmental Declaration (EPD)

JR-AI-25185E

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

Results of life cycle impact assessment (LCIA)						
		Raw material acquisition	Production	Distribution	Use & maintenance	End-of-Life
Global Warming Potential total	kg-CO₂eq	3.47E+02	2.79E+01	7.06E+01	1.44E+02	1.54E+02
(GWP-total)	kg-CO ₂ eq	3.47E+02	2.79E+01	7.00E+01	1.446+02	1.54E+02
Ozone layer destruction	kg-CFC-11eq	4.78E-05	4.51E-08	2.64E-08	4.49E-06	3.33E-08
Eutrophication	kg-PO₄³-eq	1.16E-02	1.18E-03	1.87E-04	6.21E-03	1.83E-04
Acidification	kg-SO₂eq	1.11E+00	1.80E-01	6.83E-02	6.29E-01	1.65E-01
Photochemical ozone	kg-C₂H₄eq	1.00E-02	4.46E-05	4.56E-04	1.21E-03	1.29E-03
ADP elements	kg-Sbeg	4.86E-01	9.91E-05	1.35E-05	4.97E-02	3.20E-05

Life cycle inventory analysis (LCI)							
ndicators describing use of primary resources							
		Raw material acquisition	Production	Distribution	Use & maintenance	End-of-Life	
RPR _E	MJ	8.60E+02	2.27E+02	9.76E+00	6.83E+02	7.22E+01	
RPR _M	MJ	1.48E+01	3.82E-03	2.52E+02	6.51E+02	1.36E-02	
NRPR _E	MJ	5.82E+03	9.39E+02	8.10E+02	3.34E+03	8.40E+02	
NRPR _M	MJ	1.21E+03	2.89E-01	2.83E+00	2.91E+02	1.77E-01	
Consumption of freshwater	m³	2.97E+00	2.47E-02	2.65E+01	6.88E+01	1.29E-02	

Additional explanation

- · Product destination: Australia
- · Calculated based on standard scenario for MFP (EP type).
- · Assumed lifespan of the product is five years.
- · Printing paper is excluded from Use & maintenance stage.
- ${}^{\textstyle \bullet}$ The applied International ENERGY STAR ${}^{\textstyle \circledR}$ Program Version is 3.2.
- · Assumed print volume are 182,400 sheets.
 - $1/4 \times 32$ (jobs per day) x 19 (sheets per job) x 5 (days) x 4 (weeks) x 12 (months) x 5 (years) = 182,400 (sheets)
- This product has reused parts collected from used products. It is reflected as a reduction at the raw material acquisition stage in the life cycle assessment result.

Supplementary environmental information

Material composition					
Material		Unit			
Steel	61	kg			
SUS	1.1	kg			
Alminium	1.4	kg			
Other Metals	10	kg			
Plastic	44	kg			
Rubber	0.30	kg			
Glass	1.8	kg			
Paper, Wood	9.6	kg			
Circuit Board	4.2	kg			
Conversion Parts	6.4	kg			
Others	5.1	kg			

Regulated hazardous substances					
Substance	ubstance CAS No. Reference to standards				
-	_	_			
-	_	-			
_	-	_			

Assumptions of secondary data used
Inventory Database: LCI Database IDEA v3.4,
Japan EPD Program by SuMPO registered data v1.16.

Remarks			
_			

- For data quantification, please refer to PCR and Rules on quantification and declaration.
- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied. (Reference URL: https://ecoleaf-label.jp/regulation/)
- This is a selfdeclared translation of EPD that can be accessed at [https://ecoleaf-label.jp/epd/2490] and is published for convenience purposes. Only the original EPD is valid and binding between parties.