



SuMPO EPD
Type III Environmental Declaration (EPD)

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization
14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan
<https://ecoleaf-label.jp/>

Registration number : JR-AI-25101E



FUJIFILM

Value from Innovation

富士フイルム ビジネス イノベーション株式会社
FUJIFILM Business Innovation Corp.

A3 Monochrome Multifunction Printer
ApeosPort 3060 (Model-CPS)
(for KR)

Apeos, Apeos logo, ApeosPro, ApeosPort and ApeosPrint are registered trademarks or trademarks of FUJIFILM Business Innovation Corp. in Japan and/or other countries.

Xerox, the Xerox logo, and the Fuji Xerox logo are registered trademarks or trademarks of Xerox Corporation.

Functional unit

Per unit of product

System boundary

■ final products ☐ intermediate products

Raw material acquisition, Production, Distribution,
Use & Maintenance, End-of-Life

Main specifications of the product

- Model: ApeosPort 3060 (Model-CPS)
- Monochrome Multifunction Printer (EP Type)
- Print Speed (A4 LEF): Monochrome 30ppm
- Paper Size (Max.): A3, 11x17"
- Copy / Print / Scan
- Automatic 2 Sided Output, Automatic Document Feeder

Company Information

FUJIFILM Business Innovation Corp.

6-1 Minatomirai, Nishi-ku, Yokohama-shi, Kanagawa Japan

<https://www.fujifilm.com/fbglobal/eng>

Registration#	JR-AI-25101E
PCR number	PA-590000-AI-08
PCR name	Imaging input and/or output equipment
Publication date	11/7/2025
Verification date	9/24/2025
Verification method	System certification
Verification#	2025-FB-EL-036
Expiration date	9/23/2030
PCR review was conducted by:	
Approval date	9/1/2023
PCR review	Masayuki Kanzaki
panel chair	(Sustainable Management Promotion Organization)

Third party verifier*

Sachiko Hashizume

Independent verification of data & declaration in accordance
with ISO14025

☐ internal

☒ external

*Auditor's name is stated if system certification has been performed.

Registration number : JR-AI-25101E

Results of life cycle impact assessment (LCIA)

		Raw material acquisition	Production	Distribution	Use & maintenance	End-of-Life
Global Warming Potential total (GWP-total)	kg-CO ₂ eq	5.06E+02	1.37E+01	3.01E+01	1.19E+02	9.58E+01
Ozone layer destruction	kg-CFC-11eq	3.96E-05	2.23E-08	2.61E-08	3.90E-06	2.03E-08
Eutrophication	kg-PO ₄ ³⁻ -eq	1.31E-02	1.94E-04	1.86E-04	4.09E-03	1.10E-04
Acidification	kg-SO ₂ eq	1.35E+00	9.78E-02	4.93E-02	5.51E-01	1.01E-01
Photochemical ozone	kg-C ₂ H ₄ eq	1.02E-02	1.26E-05	3.34E-04	1.23E-03	7.80E-04
ADP elements	kg-Sbeq	6.35E-01	5.43E-05	1.34E-05	1.26E-02	1.95E-05

Life cycle inventory analysis (LCI)

Indicators describing use of primary resources

		Raw material acquisition	Production	Distribution	Use & maintenance	End-of-Life
RPR _E	MJ	1.02E+03	1.25E+02	9.63E+00	5.97E+02	4.38E+01
RPR _M	MJ	1.66E+01	2.04E-03	2.51E+02	6.49E+02	8.28E-03
NRPR _E	MJ	8.29E+03	4.94E+02	3.56E+02	2.86E+03	5.10E+02
NRPR _M	MJ	1.18E+03	1.57E-01	2.83E+00	1.88E+02	1.08E-01
Consumption of freshwater	m ³	3.50E+00	8.56E-03	2.63E+01	6.85E+01	7.85E-03

Additional explanation

- Product destination: South Korea
- Calculated based on standard scenario for MFP (EP type).
- Assumed lifespan of the product is five years.
- Printing paper is excluded from Use & maintenance stage.
- The electricity consumption on use stage of this product is calculated based on TEC value measured according to ENERGY STAR® Program Version 3.2.
- Assumed print volume are 135,000 sheets.
1/4 x 30 (jobs per day) x 15 (sheets per job) x 5 (days) x 4 (weeks) x 12 (months) x 5 (years) = 135,000(sheets)

Supplementary environmental information

-

Material composition

Material		Unit
Steel	39	kg
SUS	0.41	kg
Aluminium	0.12	kg
Other Metals	3.7	kg
Plastic	29	kg
Rubber	0.29	kg
Glass	1.8	kg
Paper, Wood	11	kg
Circuit Board	2.1	kg
Conversion Parts	3.3	kg
Others	2.5	kg

Regulated hazardous substances

Substance	CAS No.	Reference to standards or regulations
-	-	-
-	-	-
-	-	-

Assumptions of secondary data used

Inventory Database: LCI Database IDEA v3.4,
Japan EPD Program by SuMPO registered data v1.16.

Remarks

-

- For data quantification, please refer to PCR and Rules on quantification and declaration.
- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied.
(Reference URL : <https://ecoleaf-label.jp/regulation/>)
- This is a selfdeclared translation of EPD that can be accessed at <https://ecoleaf-label.jp/epd/2546> and is published for convenience purposes. Only the original EPD is valid and binding between parties.