

Ecoleaf Environmental Labeling Program

Sustainable Management Promotion Organization 2-1, Kaji-cho 2 chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

Color MFP (Electrophotography)

RICOH COMPANY, LTD

RICOH

imagine. change.



PRO C7200SL



Functional unit

Per product

System boundary

■ final products □intermediate products

Raw material acquisition, Production, Distribution,

Use & maintenance, End-of-Life

Main specifications of the product

Product name: PRO C7200SL Product destination: NA

Main specifications:

Color MFP (Electrophotography)

Print Speed: 85 prints/minute (A4)
Maximum Paper Size: 11" x 17"

Included Units in Assessment : Automatic Reversing

Document Feeder, Automatic Duplexing Unit

Company Information

RICOH COMPANY,LTD Tel:(03) 3777-8111

F	Registration#	JR-AI-21068E				
	PCR number	PA-590000-AI-03				
	PCR name	Imaging input and/or output equipment				
Pı	ublication date	5/28/2021				
Ve	erification date	5/17/2021				
Ve	rification method	System certificaion				
	Verification#	JV-AI-20121				
E	xpiration date	5/16/2026				
PC	PCR review was conducted by:					
	Approval date	11/8/2019				
	PCR review	Masayuki Kanzaki				
	panel chair	(SuMPO)				

Third party verifier*

Yasuo Koseki

Independent verification of data & declaration in accordance with ISO14025

□internal **■** external

Registration number: JR-AI-21068E

 $[\]hbox{*Auditor's name is stated if system certification has been performed.}\\$


EcoLeaf

Ecoleaf Environmental Labeling Program

Sustainable Management Promotion Organization 2-1, Kaji-cho 2 chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

Type III Environmental Declaration (EPD)
Registration number: JR-AI-21068E

1. Results of life cycle impact assessment (LCIA)						
	09	%				
Global warming IPCC2013 GWP100a	11000	kg-CO2eq		26%		
Acidification	7.7	kg-SO2eq				
Resources consumption	1.6	kg-Sbeq				



			Raw				
stage			material			Use &	
Parameter	Unit	Total	acquisition	Production	Distribution	maintenance	End-of-Life
Global warming IPCC2013 GWP100a	kg-CO ₂ eq	1.1E+04	2.8E+03	2.5E+02	3.6E+02	7.1E+03	5.1E+02
Acidification	kg-SO₂eq	7.7E+00	3.5E+00	8.9E-02	5.0E-01	3.5E+00	1.6E-01
Resources consumption	kg-Sbeq	1.6E+00	1.2E+00	1.1E-03	1.5E-03	3.5E-01	2.6E-04

2. Life cycle inventory	analysis	(LCI)
Parameter		Unit
Non-renewable material resources	6.9E+02	kg
Renewable material resources	1.1E+03	kg

3. Material composition					
Material		Unit			
SUS	16.4	kg			
Aluminum	21.6	kg			
Ordinary steel	429.1	kg			
Other metals	19.3	kg			
Thermoplastic resin	69.3	kg			
Thermosetting resin	7.7	kg			
Glass	6.2	kg			
Rubber	3.5	kg			
Paper	25.3	kg			
Lubricant	0.1	kg			
Mounting circuit board	5.5	kg			
Wood	1.7	kg			

5. Additional explanation

-Products selected in the scenario used for load calculation -MFP (EP)

Product destination: NA ※

**Transportation scenarios are for China, Thailand, and Ricoh Group.from three production sites in Japan, North America, Europe, on transportation routes to the five poles of China, Oceania and Japan transport load calculate the weighted average of transportation activity per kg of product from the total calculated using the annual production volume for each pole .

Then, it is used as a transportation unit of calcuration.

- Expected usage period: 5 years
- Estimated number of sheets:4,300,800 sheets \times
- *Compatible with International Energy Star Program Ver.2.0
- -The load on the image output medium (printing paper) is not included.

^{*}Data derived from LCA and not assigned to the impact categories of LCIA



Ecoleaf Environmental Labeling Program

Sustainable Management Promotion Organization 2-1, Kaji-cho 2 chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

Type III Environmental Declaration (EPD)
Registration number: JR-AI-21068E

6-1. Supplementary environmental information

Compliant with the International Energy Star Program Ver.2.0. It also complies with the European RoHS Directive.

Assembly production of this product and production of the main parts, photoconductor and toner, are carried out at an ISO14001 certified

7. Assumptions of secondary data used

IDEA v2.1.3 is used and registration data and JLCA data v1.10 are used.

8. Remarks

- For data quantification, please refer to PCR and Rules on quantification and declaration.
- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied. (Reference URL : https://ecoleaf-label.jp/regulation/)

Registration number: JR-AI-21068E