



RICOH COMPANY,LTD

Black and White Printer (Electrophotography)

P 501TL (for NA)

EDP 423973



Functional unit

Per product

System boundary

final products intermediate products
Raw material acquisition,Production,Distribution,
Use & maintenance,End-of-Life

Main specifications of the product

Product name: P 501TL for NA EDP 423973

Main specifications:

Printer (Electrophotography)

Print Speed : Monochrome 43ppm (A4)

Maximum Paper Size : A4

Function: Print

Included Units in Assessment : Automatic Reversing

Registration#	JR-AI-25117E
PCR number	PA-590000-AI-08
PCR name	Imaging input and/or output equipment
Publication date	14 Nov 2025
Verification date	22 Oct 2025
Verification method	System certificaion
Verification#	JV-AI-25117
Expiration date	21 Oct 2030

PCR review was conducted by:

Approval date	1 Sep 2023
PCR review panel chair	Masayuki Kanzaki (SuMPO)

Third party verifier*

Hiroyuki Uchida

Independent verification of data & declaration in accordance with ISO14025

internal external


*Auditor's name is stated if system certification has been performed.

Company Information

RICOH COMPANY,LTD

<https://www.rioh.co.jp/>

1. Results of life cycle impact assessment (LCIA)



Parameter	stage		Raw material acquisition	Production	Distribution	Use & maintenance	End-of-Life
	Unit	Total					
Global warming IPCC2013 GWP100a	kg-CO ₂ eq	4.3E+02	1.4E+02	1.3E+01	1.7E+01	2.3E+02	2.7E+01
Acidification	kg-SO ₂ eq	8.9E-01	1.5E-01	6.8E-02	2.1E-02	6.4E-01	1.3E-02
Resources consumption	kg-Sbeq	2.2E-01	1.4E-01	5.4E-05	7.1E-05	7.5E-02	1.2E-05

2. Life cycle inventory analysis (LCI)

Parameter	Value	Unit
Non-renewable material resources	1.9E+01	kg
Renewable material resources	4.9E+01	kg

3. Material composition

Material	Value	Unit
SUS	2.9E-01	kg
Aluminum	1.8E-01	kg
Ordinary steel	6.3E+00	kg
Other metals	1.8E+00	kg
Thermoplastic resin	9.6E+00	kg
Thermosetting resin	7.8E-01	kg
Glass	3.8E-02	kg
Rubber	8.5E-02	kg
Paper	2.9E+00	kg
Lubricant	5.4E-04	kg
Mounting circuit board	3.4E-01	kg
Wood	5.5E-01	kg
Other	0.0E+00	kg



5. Additional explanation

Products selected in the scenario used for load calculation

--Printer (Electrophotography)

- Product destination: NA
- Expected usage period: 5 years
- Estimated number of sheets:268,800 sheets ※

※Compatible with International Energy Star Program Ver.3.0

-The load on the image output medium (printing paper) is not included.

6-1. Supplementary environmental information

Compliant with the International Energy Star Program Ver.3.0. It also complies with the European RoHS Directive.

Assembly production of this product and production of the main parts, photoconductor and toner, are carried out at an ISO14001 certified factory.

Certification number: CN18/20330.01, EMS765926, JQA-E-70001

<https://jp.ricoh.com/sustainability/environment/management/iso>

7. Assumptions of secondary data used

IDEA v3.1.0, and registered data of Japan EPD Program by SuMPO v1.15 are used.

8. Remarks

- For data quantification, please refer to PCR and Rules on quantification and declaration.
- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied.
(Reference URL : <https://ecoleaf-label.jp/regulation/>)