

SuMPO EPD Type III Environmental Declaration (EPD)

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

Registration number: JR-AI-25088E-A





富士フイルム ビジネス イノベーション株式会社 FUJIFILM Business Innovation Corp.

A3 Color Multifunction Printer

ApeosPort C2570 (Model-PFS)

(for JP)

The image above shows "ApeosPort C3570", but the actual product is labeled "ApeosPort C2570".

Apeos, Apeos logo, ApeosPro, ApeosPort and ApeosPrint are registered trademarks or trademarks of FUJIFILM Business Innovation Corp. in Japan and/or other countries.

Xerox, the Xerox logo, and the Fuji Xerox logo are registered trademarks or trademarks of Xerox Corporation.

Functional unit

Per unit of product

System boundary

■ final products □intermediate products

Raw material acquisition, Production, Distribution,

Use & Maintenance, End-of-Life

Main specifications of the product

- Model: ApeosPort C2570 (Model-PFS)
- Color Multifunction Printer (EP Type)
- Print Speed (A4 LEF): Color 25ppm, Monochrome 25ppm
- Paper Size (Max.): A3,12x18"(305mmx457mm), SRA3(320mmx450mm)
- Copy / Print / Scan / Fax
- Automatic 2 Sided Output,

A Level's Been well Frede	
Automatic Document Feeder	

Registration#	JR-AI-25088E-A
PCR number	PA-590000-AI-08
PCR name	Imaging input and/or output equipment
Publication date	21 November 2025
Verification date	16 September 2025
Verification method	System certificaion
Verification#	2025-FB-EL-023
Expiration date	15 September 2030
PCR review was	conducted by:
Approval date	01 September 2023
PCR review	Masayuki Kanzaki
panel chair	Sustainable Management Promotion Organization

Third party verifier*

Sachiko Hashizume

Independent verification of data & declaration in accordance with ISO14025

□internal	■external	

Company Information

FUJIFILM Business Innovation Corp.

6-1 Minatomirai, Nishi-ku, Yokohama-shi, Kanagawa Japan

https://www.fujifilm.com/fbglobal/eng

Registration number: JR-AI-25088E-A

^{*}Auditor's name is stated if system certification has been performed.



SuMPO EPD Type III Environmental Declaration (EPD)

JR-AI-25088E-A

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

Results of life cycle impact assessment (LCIA)						
		Raw material acquisition	Production	Distribution	Use & maintenance	End-of-Life
Global Warming Potential total	ka CO aa	0.075 . 02	2.755.01	5.27E+01	7.39E+01	1.515.03
(GWP-total)	kg-CO₂eq	8.87E+02	2.75E+01	5.276+01	7.39E+01	1.51E+02
Ozone layer destruction	kg-CFC-11eq	6.09E-05	4.63E-08	2.63E-08	1.21E-06	3.32E-08
Eutrophication	kg-PO₄³-eq	1.48E-02	1.23E-03	1.87E-04	1.96E-03	1.83E-04
Acidification	kg-SO₂eq	2.30E+00	1.84E-01	6.55E-02	3.51E-01	1.64E-01
Photochemical ozone	kg-C₂H₄eq	1.70E-02	4.20E-05	4.40E-04	6.26E-04	1.29E-03
ADP elements	kg-Sbeg	8.64E-01	1.02E-04	1.35E-05	9.43E-03	3.20E-05

Life cycle inventory analysis (LCI)						
		Raw material acquisition	Production	Distribution	Use & maintenance	End-of-Life
RPR _E	MJ	1.73E+03	2.33E+02	9.74E+00	3.83E+02	7.20E+01
RPR _M	MJ	1.42E+01	3.91E-03	2.52E+02	6.50E+02	1.35E-02
NRPR _E	MJ	1.44E+04	9.47E+02	6.09E+02	1.84E+03	8.40E+02
NRPR _M	MJ	1.74E+03	2.96E-01	2.83E+00	7.28E+01	1.76E-01
Consumption of freshwater	m³	4.29E+00	2.55E-02	2.65E+01	6.84E+01	1.29E-02

Additional explanation

- Product destination: Japan
- · Calculated based on standard scenario for MFP (EP type).
- · Assumed lifespan of the product is five years.
- · Printing paper is excluded from Use & maintenance stage.
- The electricity consumption on use stage of this product is calculated based on TEC value measured according to ENERGY STAR® Program Version 3.2.
- · Assumed print volume are 90,000 sheets.

1/4 x 25 (jobs per day) x 12 (sheets per job) x 5 (days) x 4 (weeks) x 12 (months) x 5 (years) = 90,000 (sheets)

Supplementary environmental information

ENERGY STAR® Ver.3.2 qualified.

Material composition		
Material		Unit
Steel	63	kg
SUS	1.2	kg
Alminium	0.85	kg
Other Metals	9.9	kg
Plastic	42	kg
Rubber	0.20	kg
Glass	1.8	kg
Paper, Wood	7.8	kg
Circuit Board	4.1	kg
Conversion Parts	6.3	kg
Others	5.9	kg

Regulated hazardous substances				
Substance	CAS No.	Reference to standards or regulations		
_	_	-		
_	_	-		
_	_	-		

Assumptions of secondary data used
Inventory Database: LCI Database IDEA v3.4,
Japan EPD Program by SuMPO registered data v1.16.

Remarks	
Revised on 25 November, 2025:	
Provided detailed information about electricity consumption of the product.	

- For data quantification, please refer to PCR and Rules on quantification and declaration.
- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied. (Reference URL: https://ecoleaf-label.jp/regulation/)
- This is a selfdeclared translation of EPD that can be accessed at https://ecoleaf-label.jp/epd/2592 and is published for convenience purposes. Only the original EPD is valid and binding between parties.