

SuMPO EPD Type III Environmental Declaration (EPD)

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

Registration number: JR-AI-25212E-A





富士フイルム ビジネス イノベーション株式会社 FUJIFILM Business Innovation Corp.

A3 Color Multifunction Printer

ApeosPort C6570 (Model-PFS) (for JP)

The image above shows "ApeosPort C7070", but the actual product is labeled "ApeosPort C6570".

Apeos, Apeos logo, ApeosPro, ApeosPort and ApeosPrint are registered trademarks or trademarks of FUJIFILM Business Innovation Corp. in Japan and/or other countries.

Xerox, the Xerox logo, and the Fuji Xerox logo are registered trademarks or trademarks of Xerox Corporation.

Functional unit

Per unit of product

System boundary

■ final products □intermediate products Raw material acquisition, Production, Distribution, Use & Maintenance, End-of-Life

Main specifications of the product

- Model: ApeosPort C6570 (Model-PFS)
- Color Multifunction Printer (EP Type)
- Print Speed (A4 LEF): Color 65ppm, Monochrome 65ppm
- Paper Size (Max.): SRA3(320×450 mm), 12×18"(305×457 mm), A3

- Copy / Print / Scan / FAX
- Automatic 2 Sided Output, Automatic Document Feeder with ISO14025

	Registration#	JR-AI-25212E-A				
	PCR number	PA-590000-AI-08				
	PCR name	Imaging input and/or output equipment				
	Publication date	21 November 2025				
	Verification date	21 October 2025				
	Verification method	System certificaion				
	Verification#	2025-FB-EL-067				
	Expiration date	20 October 2030				
	PCR review was conducted by:					
	Approval date	01 September 2023				
	PCR review	Masayuki Kanzaki				
1	panel chair	(Sustainable Management Promotion Organization)				

Third party verifier*

Sachiko Hashizume

Independent verification of data & declaration in accordance

□internal ■ external

Company Information

FUJIFILM Business Innovation Corp.

6-1 Minatomirai, Nishi-ku, Yokohama-shi, Kanagawa Japan https://www.fujifilm.com/fbglobal/eng

*Auditor's name is stated if system certification has been performed.

Registration number: JR-AI-25212E-A



SuMPO EPD Type III Environmental Declaration (EPD)

JR-AI-25212E-A

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku,

Tokyo Japan https://ecoleaf-label.jp/

Results of life cycle impact assessment (LCIA)								
		Raw material acquisition	Production	Distribution	Use & maintenance	End-of-Life		
Global Warming Potential total	ka CO oa	1.03E+03	2.75E+01	5.92E+01	4.32E+02	1.055.00		
(GWP-total)	kg-CO₂eq					1.65E+02		
Ozone layer destruction	kg-CFC-11eq	6.51E-05	4.63E-08	2.64E-08	1.90E-05	3.80E-08		
Eutrophication	kg-PO₄³-eq	1.58E-02	1.23E-03	1.87E-04	2.54E-02	2.15E-04		
Acidification	kg-SO₂eq	2.58E+00	1.84E-01	7.21E-02	1.92E+00	1.85E-01		
Photochemical ozone	kg-C₂H₄eq	1.90E-02	4.20E-05	4.84E-04	4.14E-03	1.49E-03		
ADP elements	ka-Sbea	8.68E-01	1.02E-04	1.35E-05	2.29E-01	3.68E-05		

Life cycle inventory analysis (LCI)							
Indicators describing use of primary resources							
	Raw material acquisition	Production	Distribution	Use & maintenance	End-of-Life	JR	
RPR _E	MJ	1.93E+03	2.33E+02	9.77E+00	2.07E+03	8.30E+01]
RPR _M	MJ	1.50E+01	3.91E-03	2.52E+02	7.83E+02	1.55E-02	1
NRPR _E	MJ	1.66E+04	9.47E+02	6.80E+02	9.82E+03	9.71E+02	1
NRPR _M	MJ	1.77E+03	2.96E-01	2.83E+00	1.28E+03	1.99E-01	1
Consumption of freshwater	m³	4.69E+00	2.55E-02	2.65E+01	8.39E+01	1.48E-02	

Additional explanation

- · Product destination: Japan
- · Calculated based on standard scenario for MFP (EP type).
- · Assumed lifespan of the product is five years.
- $\boldsymbol{\cdot}$ Printing paper is excluded from Use & maintenance stage.
- The electricity consumption on use stage of this product is calculated based on TEC value measured according to ENERGY STAR® Program Version 3.2.
- · Assumed print volume are 633,600 sheets.

 $1/4 \times 32$ (jobs per day) x 66 (sheets per job) x 5 (days) x 4 (weeks) x 12 (months) x 5 (years) = 633,600 (sheets)

Supplementary environmental information

ENERGY STAR® Ver.3.2 qualified.

Material composition					
Material		Unit			
Steel	77	kg			
SUS	1.3	kg			
Alminium	0.86	kg			
Other Metals	12	kg			
Plastic	42	kg			
Rubber	0.25	kg			
Glass	2.2	kg			
Paper, Wood	8.0	kg			
Circuit Board	5.0	kg			
Conversion Parts	8.2	kg			
Others	6.5	kg			

Regulated hazardous substances					
Substance	ce CAS No. Reference to standards or regulation				
-	_	_			
-	_	_			
-	_	_			

Assumptions of secondary data used

Inventory Database:

LCI Database IDEA v3.4, Japan EPD Program by SuMPO registered data v1.16.

D.	Δ	100	6	м	172	7
III 6/3	-		0	18	M	6

Revised on 25 November, 2025:

Provided an explanation regarding lifespan of the product.

- For data quantification, please refer to PCR and Rules on quantification and declaration.
- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied. (Reference URL: https://ecoleaf-label.jp/regulation/)
- This is a selfdeclared translation of EPD that can be accessed at https://ecoleaf-label.jp/epd/2602 and is published for convenience purposes. Only the original EPD is valid and binding between parties.