

# Hitachi, Ltd. Hitachi Virtual Storage Platform 5200



## Functional unit

Per sales unit (per unit)

## System boundary

 ■ final products  intermediate products

## Main specifications of the product

All-Flash Array

- Controller chassis

H/A-65AG-CBXAAN\* up to 1pair

\* "H/A-" means "H-" or "A-"

- Drive box

H/A-F65AG-B1NSBX (Up to 96 SAS SSD)

Up to 8 units

H/A-F65AG-B1NNBX (Up to 96 NVMe SSD)

Up to 1 units

\*The maximum installed drives represents

the case of connecting only a single type of drive box.

The mix of the SAS/NVMe drive is excluded

- Assumed operating years : 5years

\* The specifications listed are subject to change without notice due to product improvements

## Company Information

Hitachi, Ltd.

+81-3-5471-2745

|                     |                    |
|---------------------|--------------------|
| Registration#       | JR-BF-25002E       |
| PCR number          | PA-520000-BF-04    |
| PCR name            | IT equipments      |
| Publication date    | 12/5/2025          |
| Verification date   | 11/18/2025         |
| Verification method | Product-by-product |
| Verification#       | JV-BF-25002        |
| Expiration date     | 11/17/2030         |

## PCR review was conducted by:

|                        |  |
|------------------------|--|
| Approval date          | 8/15/2023  |
| PCR review panel chair | Ken Yamagishi<br>(Sustainable Management Promotion Organization) |

## Third party verifier\*

Yasuo Naito


Independent verification of data &amp; declaration in accordance with ISO14025

 internal

 external

\*Auditor's name is stated if system certification has been performed.

## 1. Results of life cycle impact assessment (LCIA)



| Parameter                        | stage | Unit                                | Total   | Raw material acquisition | Production | Distribution | Use & maintenance | End-of-Life |
|----------------------------------|-------|-------------------------------------|---------|--------------------------|------------|--------------|-------------------|-------------|
| Global warming IPCC2013 GWP100a  |       | kg-CO <sub>2</sub> eq               | 4.3E+05 | 1.3E+04                  | 4.9E+03    | 2.0E+02      | 4.1E+05           | 3.5E+02     |
| Ozone layer destruction          |       | kg-CFC-11eq                         | 1.0E-01 | 1.4E-03                  | 1.2E-03    | 2.7E-09      | 9.9E-02           | 9.8E-06     |
| Acidification                    |       | kg-SO <sub>2</sub> eq               | 4.2E+02 | 1.5E+01                  | 4.8E+00    | 6.6E-01      | 4.0E+02           | 1.6E-01     |
| Urban area air pollution         |       | kg-SO <sub>2</sub> eq               | 3.2E+02 | 1.2E+01                  | 3.7E+00    | 2.5E-01      | 3.1E+02           | 9.7E-02     |
| Photochemical ozone              |       | kg-C <sub>2</sub> H <sub>4</sub> eq | 8.3E+00 | 2.8E-01                  | 9.5E-02    | 1.4E-03      | 7.9E+00           | 1.3E-03     |
| Toxic chemicals(cancer)          |       | kg-C <sub>6</sub> H <sub>6</sub> eq | 2.2E+01 | 1.2E+01                  | 1.1E-01    | 9.9E-04      | 9.6E+00           | 1.0E-02     |
| Toxic chemicals(chronic disease) |       | kg-C <sub>6</sub> H <sub>6</sub> eq | 1.4E+00 | 1.4E-01                  | 1.5E-02    | 6.4E-04      | 1.2E+00           | 3.6E-04     |
| Aquatic toxicity                 |       | kg-C <sub>6</sub> H <sub>6</sub> eq | 8.6E+02 | 4.6E+01                  | 9.6E+00    | 3.2E-05      | 8.0E+02           | 8.6E-02     |
| Biological toxicity              |       | kg-C <sub>6</sub> H <sub>6</sub> eq | 2.1E+04 | 1.0E+03                  | 2.3E+02    | 5.2E-04      | 1.9E+04           | 1.9E+00     |
| Eutrophication                   |       | kg-PO <sub>4</sub> <sup>3-</sup> eq | 1.2E-01 | 9.8E-02                  | 3.0E-04    | 2.0E-09      | 2.5E-02           | 1.3E-03     |
| Land use(Occupation)             |       | m <sup>2</sup> /year                | 2.2E+03 | 1.3E+02                  | 2.4E+01    | 1.7E+01      | 2.0E+03           | 1.9E+00     |
| Land use(Transformation)         |       | m <sup>2</sup>                      | 5.9E+01 | 2.0E+00                  | 6.7E-01    | 3.3E-01      | 5.6E+01           | 4.0E-02     |
| Resources consumption            |       | kg-Sbeq                             | 3.9E+00 | 1.1E+00                  | 3.3E-02    | 8.3E-04      | 2.8E+00           | 5.6E-04     |

## 2. Life cycle inventory analysis (LCI)

| Parameter                        | Unit                   |
|----------------------------------|------------------------|
| Non-renewable material resources | 7.1E+03 kg             |
| Non-renewable energy resources   | 1.6E+05 kg             |
| Non-renewable energy resources   | 6.7E+06 MJ             |
| Renewable material resources     | 1.6E+03 kg             |
| Renewable primary energy         | 2.7E+06 MJ             |
| Consumption of freshwater        | 1.2E+02 m <sup>3</sup> |

## 3. Material composition

| Material                | Unit |
|-------------------------|------|
| All Flash array Steel   | %    |
| Other metals            | %    |
| Plastics                | %    |
| PCB                     | %    |
| Copper-clad wire,Motors | %    |
| Batteries               | %    |
| PSU                     | %    |
| SSD                     | %    |
| Total                   | %    |

## 4. Waste to disposal

| Parameter                             | Unit       |
|---------------------------------------|------------|
| Hazardous waste                       | 0.0E+00 kg |
| Non-hazardous waste.                  | 1.7E+03 kg |
| Treated MSW for landfill              | 6.1E-07 kg |
| Treated industrial waste for landfill | 1.7E+03 kg |

\*Data derived from LCA and not assigned to the impact categories of LCIA



## 5. Additional explanation

### <Products>

- Product Name : Hitachi Virtual Storage Platform 5200
- Conditions for calculating :  
Calculated using 1 controller chassis (H/A-65AG-CBXAAN) and 8 drive boxes (H/A-F65AG-B1NSBX) , with the maximum installed of SAS SSDs(768 units).
- Product type name of the scenario used :  
Disk array (Solid State Drive(SSD) installed)

### <Product main specifications>

Physical storage capacity<sup>\*1</sup> : 23,113TB

Operating years<sup>\*2</sup> : 5 years

Drive type : Solid State Drive (SAS SSD)

Drive interface : SAS

Installed drives : 768 units

### • Measurement conditions :

-Power during use is measured by the measurement method specified by certified PCR (PA-520000-BF-04).

\*<sup>1</sup> The capacity is calculated as 1TB = 1,000,000,000,000 bytes

\*<sup>2</sup> The operating years were assumed to be the statutory useful life(5 years for computer/others)

- The largest amount of greenhouse gas emissions occurs during the use and maintenance stages, accounting for approximately 96% of the entire lifecycle. The energy consumption during use has a significant impact, so energy-saving performance during use is a very important factor. Note that the use and maintenance stages were evaluated under general conditions, so they may not be the same as the conditions under which the customer uses the product.
- In calculating EPD, we use our own data for the amount of raw materials used, but because it is difficult to collect data on the manufacture of the thousands of parts used, we use data from the manufacture of general raw materials. As a result, the product's unique characteristics may not be reflected.



### 6-1. Supplementary environmental information

- This product is manufactured and assembled at a factory that has obtained ISO14001:2015 certification.
- This product complies with the European RoHS Directive.
- We have established environmentally friendly green procurement guidelines and are working on green procurement with our procurement partners.

### 7. Assumptions of secondary data used

Primary used IDEA V3.1.0 , complemented by CO2 Emissions Intensity v1.15.

### 8. Remarks

-

- For data quantification, please refer to PCR and Rules on quantification and declaration.
- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied.  
(Reference URL : <https://ecoleaf-label.jp/regulation/>)
- This is a selfdeclared translation of EPD that can be accessed at <https://ecoleaf-label.jp/epd/2622> and is published for convenience purposes. Only the original EPD is valid and binding between parties.

Registration number : JR-BF-25002E