

KONICAMINOLTA, INC.

AccurioPress C5070



Functional unit

Per unit of product

System boundary

final products intermediate products

Raw material acquisition, Production, Distribution,
Use & maintenance, End-of-Life

Main specifications of the product

Model name : AccurioPress C5070

■ Marking technologies : Electrophotographic Printer (EP)

■ Printing speed(A4) : Monochrome 81 ppm

Color 71 ppm

■ Printing paper : Maximum A3

■ Duplex function : Standard

Company Information

Please direct any inquiries or comments
to e-mail: eco-support@konicaminolta.com

Registration#	JR-AI-25376E
PCR number	PA-590000-AI-08
PCR name	Imaging input and/or output equipment
Publication date	9 January 2026
Verification date	24 December 2025
Verification method	System certification
Verification#	JV-AI-25376
Expiration date	23 December 2030
PCR review was conducted by:	

Approval date	01 September 2023
PCR review panel chair	Masayuki Kanzaki (Sustainable Management Promotion Organization)

Third party verifier*

Kazuo Naitou

Independent verification of data & declaration in accordance
with ISO14025

internal

external

*Auditor's name is stated if system certification has been performed.

Registration number : JR-AI-25376E



SuMPO EPD
Type III Environmental Declaration (EPD)

JR-AI-25376E

Japan EPD Program by SuMPO

Sustainable Management Promotion

Organization

14-8, Uchikanda 1-chome, Chiyoda-ku,

Tokyo Japan

<https://ecoleaf-label.jp/>

Results of life cycle impact assessment (LCIA)

		Raw material acquisition	Production	Distribution	Use & maintenance	End-of-Life
Global Warming Potential total (GWP-total)	kg-CO ₂ eq	1.23E+03	1.09E+02	7.24E+01	5.04E+03	2.27E+02
Ozone layer destruction	kg-CFC-11eq	1.28E-04	4.17E-07	1.40E-07	5.21E-04	1.42E-06
Eutrophication	kg-PO ₄ ³⁻ eq	3.67E-02	1.78E-02	2.98E-05	8.05E-02	2.84E-04
Acidification	kg-SO ₂ eq	1.49E+00	1.03E+00	5.51E-02	5.41E+00	1.54E-01
Photochemical ozone	kg-C ₂ H ₆ eq	2.72E-02	6.03E-05	5.16E-04	1.04E-01	1.94E-03
ADP elements	kg-Sbeq	2.86E-01	2.40E-04	1.24E-05	7.24E-01	1.10E-04

Life cycle inventory analysis (LCI)

Indicators describing use of primary resources

		Raw material acquisition	Production	Distribution	Use & maintenance	End-of-Life
RPR _E	MJ	3.19E+03	8.66E+02	2.06E+01	3.50E+04	2.08E+02
RPR _M	MJ	4.95E+02	2.24E-02	2.57E-03	4.61E+01	3.15E-02
NRPR _E	MJ	1.97E+04	2.23E+03	7.97E+02	1.20E+05	1.35E+03
NRPR _M	MJ	2.25E+03	1.67E+00	9.93E-02	1.04E+04	8.14E-01

Additional explanation

- Production destination : Japan
- Calculation method of use stage (Calculated by the standard scenario for MFP (EP type))
- Expected usage period : five years
- Estimated number of sheets used : 2,995,200※
- The impact of printing paper is not included
- The impact of expendables and Maintenance parts are included in the stage of Use&maintenance.

※ Conformed to the International ENERGY STAR® Ver3.2 Program

- The results of the environmental impact assessment are presented as relative figures only. These figures should not be interpreted as definitive indicators of environmental impact based solely on their magnitude.
- Additionally, the calculated figures do not directly reflect the specific extent of environmental impact, environmental safety (e.g., whether thresholds are exceeded), or risk assessment (e.g., the degree of impact on the environment or human health).

Supplementary environmental information

- ENERGY STAR® Ver.3.0 qualified
- The assembly of this product and the production of its main components are carried out at an ISO14001 certified factory.

Material composition

Material		Unit
Steel	2.1E+02	kg
SUS	1.1E+01	kg
Al	8.5E+00	kg
Other metals	1.9E+01	kg
Glass	2.7E+00	kg
Thermoplastics resin	3.9E+01	kg
Wood	2.0E+01	kg
Paper	1.3E+01	kg
Rubber	3.6E+00	kg
Assembled circuit board	7.1E+00	kg
Medium-sized motor	1.4E+01	kg

Regulated hazardous substances

Substance	CAS No.	Reference to standards or regulation

Assumptions of secondary data used

IDEA v3.4, registered data v2.13 of Japan EPD Program by SuMPO are used.

Remarks

-

- For data quantification, please refer to PCR and Rules on quantification and declaration.
- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied.
(Reference URL : <https://ecoleaf-label.jp/regulation/>)
- This is a selfdeclared translation of EPD that can be accessed at <https://ecoleaf-label.jp/epd/2696> and is published for convenience purposes. Only the original EPD is valid and binding between parties.