



SuMPO EPD

## Type III Environmental Declaration (EPD)

Registration number : JR-AI-25274E

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization  
14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan  
<https://ecoleaf-label.jp/>



# FUJIFILM

Value from Innovation

富士フイルム ビジネス イノベーション株式会社  
FUJIFILM Business Innovation Corp.

A3 Color Multifunction Printer

## ApeosPort-VI C6671

(for JP)

The image above shows "ApeosPort-VI C7771" and the actual product is labeled "ApeosPort-VI C6671".

Apeos, Apeos logo, ApeosPro, ApeosPort and ApeosPrint are registered trademarks or trademarks of FUJIFILM Business Innovation Corp. in Japan and/or other countries.

Xerox, the Xerox logo, and the Fuji Xerox logo are registered trademarks or trademarks of Xerox Corporation.

### Functional unit

Per unit of product

### System boundary

- final products    □ intermediate products

Raw material acquisition, Production, Distribution,  
Use & Maintenance, End-of-Life

### Main specifications of the product

- Model: ApeosPort-VI C6671
- Color Multifunction Printer (EP Type)
- Print Speed (A4 LEF): Color 65ppm, Monochrome 65ppm
- Paper Size (Max.): SRA3(320×450 mm),  
12×18"(305×457 mm)、A3
- Copy / Print / Scan / FAX
- Automatic 2 Sided Output, Automatic Document Feeder

### Company Information

**FUJIFILM Business Innovation Corp.**

6-1 Minatomirai, Nishi-ku, Yokohama-shi, Kanagawa Japan

<https://www.fujifilm.com/fbglobal/eng>

Registration#	JR-AI-25274E
PCR number	PA-590000-AI-08
PCR name	Imaging input and/or output equipment
Publication date	23 January 2026
Verification date	25 November 2025
Verification method	System certification
Verification#	2025-FB-EL-075
Expiration date	24 November 2030

### PCR review was conducted by:

Approval date	01 September 2023
PCR review panel chair	Masayuki Kanzaki (Sustainable Management Promotion Organization)

### Third party verifier\*

Sachiko Hashizume

Independent verification of data & declaration in accordance  
with ISO14025

☐ internal    ☒ external

\*Auditor's name is stated if system certification has been performed.

Registration number : JR-AI-25274E

Results of life cycle impact assessment (LCIA)						
		Raw material acquisition	Production	Distribution	Use & maintenance	End-of-Life
Global Warming Potential total (GWP-total)	kg-CO <sub>2</sub> eq	1.06E+03	2.20E+01	6.05E+01	4.48E+02	1.68E+02
Ozone layer destruction	kg-CFC-11eq	6.79E-05	2.81E-08	1.92E-08	2.07E-05	3.85E-08
Eutrophication	kg-PO <sub>4</sub> <sup>3-</sup> -eq	1.59E-02	1.63E-06	2.04E-04	1.27E-02	2.18E-04
Acidification	kg-SO <sub>2</sub> eq	2.61E+00	1.32E-01	7.42E-02	1.95E+00	1.88E-01
Photochemical ozone	kg-C <sub>2</sub> H <sub>4</sub> eq	1.98E-02	3.98E-05	4.95E-04	4.35E-03	1.51E-03
ADP elements	kg-Sbeq	8.68E-01	7.19E-05	1.35E-05	2.49E-01	3.73E-05

Life cycle inventory analysis (LCI)						
Indicators describing use of primary resources						
		Raw material acquisition	Production	Distribution	Use & maintenance	End-of-Life
RPR <sub>E</sub>	MJ	1.95E+03	1.65E+02	1.05E+01	2.09E+03	8.42E+01
RPR <sub>M</sub>	MJ	1.55E+01	2.72E-03	2.76E+02	7.96E+02	1.57E-02
NRPR <sub>E</sub>	MJ	1.70E+04	7.01E+02	6.97E+02	1.00E+04	9.84E+02
NRPR <sub>M</sub>	MJ	1.79E+03	2.07E-01	3.42E-01	1.40E+03	2.02E-01
Consumption of freshwater	m <sup>3</sup>	4.79E+00	8.62E-03	2.90E+01	8.53E+01	1.51E-02

Additional explanation	
<ul style="list-style-type: none"> <li>Product destination: Japan</li> <li>Calculated based on standard scenario for MFP (EP type).</li> <li>Assumed lifespan of the product is five years.</li> <li>Printing paper is excluded from Use &amp; maintenance stage.</li> <li>The electricity consumption on use stage of this product is calculated based on TEC value measured according to ENERGY STAR® Program Version 3.2.</li> <li>Assumed print volume are 633,600 sheets.  <math>1/4 \times 32 \text{ (jobs per day)} \times 66 \text{ (sheets per job)} \times 5 \text{ (days)} \times 4 \text{ (weeks)} \times 12 \text{ (months)} \times 5 \text{ (years)} = 633,600 \text{ (sheets)}</math></li> </ul>	

Supplementary environmental information
ENERGY STAR® Ver.3.2 qualified.

Material composition		
Material		Unit
Steel	77	kg
SUS	1.3	kg
Aluminium	0.85	kg
Other Metals	13	kg
Plastic	43	kg
Rubber	0.30	kg
Glass	2.2	kg
Paper, Wood	8.3	kg
Circuit Board	5.3	kg
Conversion Parts	8.6	kg
Others	6.4	kg

Regulated hazardous substances		
Substance	CAS No.	Reference to standards or regulations
—	—	—
—	—	—
—	—	—

Assumptions of secondary data used
Inventory Database: LCI Database IDEA v3.4, Japan EPD Program by SuMPO registered data v1.16.

Remarks
—

- For data quantification, please refer to PCR and Rules on quantification and declaration.
- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied.  
 (Reference URL : <https://ecoleaf-label.jp/regulation/>)
- This is a selfdeclared translation of EPD that can be accessed at <https://ecoleaf-label.jp/epd/2777> and is published for convenience purposes. Only the original EPD is valid and binding between parties.