



**FUJIFILM**  
Value from Innovation

富士フイルム ビジネス イノベーション株式会社  
FUJIFILM Business Innovation Corp.

Remanufactured Product

A3 Color Multifunction Printer

ApeosPort C3570 R (for TW)

Apeos, Apeos logo, ApeosPro, ApeosPort and ApeosPrint are registered trademarks or trademarks of FUJIFILM Business Innovation Corp. in Japan and/or other countries.

Xerox, the Xerox logo, and the Fuji Xerox logo are registered trademarks or trademarks of Xerox Corporation.

#### Functional unit

Per unit of product

#### System boundary

final products  intermediate products

Raw material acquisition, Production, Distribution,

Use & Maintenance, End-of-Life

#### Main specifications of the product

- Model: ApeosPort C3570 R
- Color Multifunction Printer (EP Type)
- Print Speed (A4 LEF): Color 35ppm, Monochrome 35ppm
- Paper Size (Max.): A3,12x18"(305mmx457mm),  
SRA3(320mmx450mm)

- Copy / Print / Scan
- Automatic 2 Sided Output,
- Automatic Document Feeder

Registration#	JR-AI-25194E
PCR number	PA-590000-AI-08
PCR name	Imaging input and/or output equipment
Publication date	30 January 2026
Verification date	11 November 2025
Verification method	System certificaion
Verification#	2025-FB-EL-049
Expiration date	10 November 2030

#### PCR review was conducted by:

Approval date	01 September 2023
PCR review panel chair	Masayuki Kanzaki Sustainable Management Promotion Organization

#### Third party verifier\*

Sachiko Hashizume

Independent verification of data & declaration in accordance with ISO14025

internal

external

\*Auditor's name is stated if system certification has been performed.

#### Company Information

##### FUJIFILM Business Innovation Corp.

6-1 Minatomirai, Nishi-ku, Yokohama-shi, Kanagawa Japan

<https://www.fujifilm.com/fbglobal/eng>

**Results of life cycle impact assessment (LCIA)**

		Raw material acquisition	Production	Distribution	Use & maintenance	End-of-Life
Global Warming Potential total (GWP-total)	kg-CO <sub>2</sub> eq	3.66E+02	2.87E+01	4.52E+01	1.26E+02	1.54E+02
Ozone layer destruction	kg-CFC-11eq	4.44E-05	4.53E-08	3.51E-08	3.91E-06	3.35E-08
Eutrophication	kg-PO <sub>4</sub> <sup>3-</sup> eq	1.16E-02	1.18E-03	1.88E-04	5.45E-03	1.84E-04
Acidification	kg-SO <sub>2</sub> eq	1.00E+00	1.82E-01	6.46E-02	5.91E-01	1.66E-01
Photochemical ozone	kg-C <sub>2</sub> H <sub>4</sub> eq	1.01E-02	6.25E-05	4.39E-04	1.11E-03	1.30E-03
ADP elements	kg-Sbeq	4.31E-01	9.96E-05	1.46E-05	4.50E-02	3.23E-05

**Life cycle inventory analysis (LCI)**

Indicators describing use of primary resources

		Raw material acquisition	Production	Distribution	Use & maintenance	End-of-Life
RPR <sub>E</sub>	MJ	7.41E+02	2.28E+02	9.91E+00	6.45E+02	7.26E+01
RPR <sub>M</sub>	MJ	1.56E+01	3.84E-03	2.52E+02	6.50E+02	1.37E-02
NRPR <sub>E</sub>	MJ	5.79E+03	9.50E+02	5.23E+02	3.06E+03	8.47E+02
NRPR <sub>M</sub>	MJ	1.04E+03	2.90E-01	5.36E+00	2.55E+02	1.78E-01
Consumption of freshwater	m <sup>3</sup>	2.93E+00	2.48E-02	2.65E+01	6.86E+01	1.30E-02

**Additional explanation**

- Product destination: Taiwan
- Calculated based on standard scenario for MFP (EP type).
- Assumed lifespan of the product is five years.
- Printing paper is excluded from Use & maintenance stage.
- The electricity consumption on use stage of this product is calculated based on TEC value measured according to ENERGY STAR® Program Version 3.2.
- Assumed print volume are 182,400 sheets.  
1/4 x 32 (jobs per day) x 19 (sheets per job) x 5 (days) x 4 (weeks) x 12 (months) x 5 (years) = 182,400 (sheets)
- This product uses reused parts to reduce the environmental impact. It is not included at the raw material acquisition stage in the LCA

**Supplementary environmental information**

–

**Material composition**

Material		Unit
Steel	63	kg
SUS	1.2	kg
Alminium	0.85	kg
Other Metals	10	kg
Plastic	43	kg
Rubber	0.20	kg
Glass	1.8	kg
Paper, Wood	10	kg
Circuit Board	4.1	kg
Conversion Parts	6.4	kg
Others	5.8	kg

**Regulated hazardous substances**

Substance	CAS No.	Reference to standards or regulations
–	–	–
–	–	–
–	–	–

**Assumptions of secondary data used**

Inventory Database: LCI Database IDEA v3.4,  
Japan EPD Program by SuMPO registered data v1.16.

**Remarks**

–

- For data quantification, please refer to PCR and Rules on quantification and declaration.

- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied.

(Reference URL : <https://ecoleaf-label.jp/regulation/>)

- This is a selfdeclared translation of EPD that can be accessed at <https://ecoleaf-label.jp/epd/2790>

and is published for convenience purposes. Only the original EPD is valid and binding between parties.