



FUJIFILM
Value from Innovation

富士フイルム ビジネス イノベーション株式会社
FUJIFILM Business Innovation Corp.

Remanufactured Product
A3 Color Multifunction Printer
ApeosPort C5570 R (for AU)

Apeos, Apeos logo, ApeosPro, ApeosPort and ApeosPrint are registered trademarks or trademarks of FUJIFILM Business Innovation Corp. in Japan and/or other countries. Xerox, the Xerox logo, and the Fuji Xerox logo are registered trademarks or trademarks of Xerox Corporation.

Functional unit

Per unit of product

System boundary

final products intermediate products
Raw material acquisition, Production, Distribution,
Use & Maintenance, End-of-Life

Main specifications of the product

- Model: ApeosPort C5570 R
- Color Multifunction Printer (EP Type)
- Print Speed (A4 LEF): Color 55ppm, Monochrome 55ppm
- Paper Size (Max.): A3,12x18"(305x457mm),
SRA3(320x450mm)
- Copy / Print / Scan
- Automatic 2 Sided Output,
Automatic Document Feeder

Registration#	JR-AI-25360E
PCR number	PA-590000-AI-08
PCR name	Imaging input and/or output equipment
Publication date	30 January 2026
Verification date	13 January 2026
Verification method	System certificaion
Verification#	2025-FB-EL-081
Expiration date	12 January 2031

PCR review was conducted by:

Approval date	01 September 2023
PCR review	Masayuki Kanzaki
panel chair	Sustainable Management Promotion Organization

Third party verifier*

Sachiko Hashizume

Independent verification of data & declaration in accordance
with ISO14025

internal

external

*Auditor's name is stated if system certification has been performed.

Company Information

FUJIFILM Business Innovation Corp.

6-1 Minatomirai, Nishi-ku, Yokohama-shi, Kanagawa Japan

<https://www.fujifilm.com/fbglobal/eng>

Registration number : JR-AI-25360E



Registration number :

SuMPO EPD

Type III Environmental Declaration (EPD)

JR-AI-25360E

Japan EPD Program by SuMPO

Sustainable Management Promotion

Organization

14-8, Uchikanda 1-chome, Chiyoda-ku,

Tokyo Japan

<https://ecoleaf-label.jp/>

Results of life cycle impact assessment (LCIA)		Raw material acquisition	Production	Distribution	Use & maintenance	End-of-Life
Global Warming Potential total (GWP-total)	kg-CO ₂ eq	3.90E+02	2.87E+01	7.10E+01	3.06E+02	1.55E+02
Ozone layer destruction	kg-CFC-11eq	4.52E-05	4.53E-08	2.64E-08	1.21E-05	3.35E-08
Eutrophication	kg-PO ₄ ³⁻ eq	1.14E-02	1.18E-03	1.87E-04	1.70E-02	1.84E-04
Acidification	kg-SO ₂ eq	1.01E+00	1.82E-01	6.86E-02	1.31E+00	1.67E-01
Photochemical ozone	kg-C ₂ H ₄ eq	1.06E-02	6.25E-05	4.58E-04	2.70E-03	1.30E-03
ADP elements	kg-Sbeq	4.26E-01	9.96E-05	1.35E-05	1.52E-01	3.23E-05

Life cycle inventory analysis (LCI)							
Indicators describing use of primary resources							
		Raw material acquisition	Production	Distribution	Use & maintenance	End-of-Life	
RPR _E		MJ	7.51E+02	2.28E+02	9.76E+00	1.41E+03	7.27E+01
RPR _M		MJ	1.56E+01	3.84E-03	2.52E+02	6.54E+02	1.37E-02
NRPR _E		MJ	6.08E+03	9.50E+02	8.15E+02	6.88E+03	8.47E+02
NRPR _M		MJ	1.05E+03	2.90E-01	2.83E+00	8.32E+02	1.79E-01
Consumption of freshwater		m ³	2.95E+00	2.48E-02	2.65E+01	6.98E+01	1.30E-02

Additional explanation					
<ul style="list-style-type: none"> Product destination: Australia Calculated based on standard scenario for MFP (EP type). Assumed lifespan of the product is five years. Printing paper is excluded from Use & maintenance stage. The electricity consumption on use stage of this product is calculated based on TEC value measured according to ENERGY STAR® Program Version 3.2. Assumed print volume are 451,200 sheets. 1/4 x 32 (jobs per day) x 47 (sheets per job) x 5 (days) x 4 (weeks) x 12 (months) x 5 (years) = 451,200 (sheets) This product uses reused parts to reduce the environmental impact. It is not included at the raw material acquisition stage in the LCA 					

Supplementary environmental information					
-					

Material composition			Regulated hazardous substances		
Material		Unit	Substance	CAS No.	Reference to standards or regulations
Steel	62	kg	–	–	–
SUS	1.1	kg	–	–	–
Alminium	0.86	kg	–	–	–
Other Metals	10	kg			
Plastic	44	kg			
Rubber	0.29	kg			
Glass	1.8	kg			
Paper, Wood	10	kg			
Circuit Board	4.0	kg			
Conversion Parts	6.4	kg			
Others	5.4	kg			

Assumptions of secondary data used		
Inventory Database: LCI Database IDEA v3.4, Japan EPD Program by SuMPO registered data v1.16.		

Remarks		
–		

- For data quantification, please refer to PCR and Rules on quantification and declaration.
- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied.
(Reference URL : <https://ecoleaf-label.jp/regulation/>)
- This is a selfdeclared translation of EPD that can be accessed at <https://ecoleaf-label.jp/epd/2792> and is published for convenience purposes. Only the original EPD is valid and binding between parties.