



FUJIFILM

Value from Innovation

富士フイルム ビジネス イノベーション株式会社
FUJIFILM Business Innovation Corp.

A3 Monochrome Multifunction Printer
Apeos 3560 (Model-CPS-B)
(for US)

Apeos, Apeos logo, ApeosPro, ApeosPort and ApeosPrint are registered trademarks or trademarks of FUJIFILM Business Innovation Corp. in Japan and/or other countries.

The image above shows "Apeos 3060 " and the actual product is labeled "Apeos 3560 ".

Functional unit

Per unit of product

System boundary

- final products intermediate products

Raw material acquisition, Production, Distribution,
Use & Maintenance, End-of-Life

Main specifications of the product

- Model: Apeos 3560 (Model-CPS-B)
- Monochrome Multifunction Printer (EP Type)
- Print Speed (A4 LEF): Monochrome 35ppm
- Paper Size (Max.): A3, 11 x 17"
- Copy / Print / Scan
- Automatic 2 Sided Output,
Automatic Document Feeder

Registration#	JR-AI-25433E
PCR number	PA-590000-AI-08
PCR name	Imaging input and/or output equipment
Publication date	13 March 2026
Verification date	24 February 2026
Verification method	System certificaion
Verification#	2025-FB-EL-101
Expiration date	23 February 2031
PCR review was conducted by:	
Approval date	01 September 2023
PCR review panel chair	Masayuki Kanzaki Sustainable Management Promotion Organization

Third party verifier*

Sachiko Hashizume

Independent verification of data & declaration in accordance
with ISO14025

internal external

*Auditor's name is stated if system certification has been performed.

Company Information

FUJIFILM Business Innovation Corp.

6-1 Minatomirai, Nishi-ku, Yokohama-shi, Kanagawa Japan

<https://www.fujifilm.com/fbglobal/eng>

Results of life cycle impact assessment (LCIA)						
		Raw material acquisition	Production	Distribution	Use & maintenance	End-of-Life
Global Warming Potential total (GWP-total)	kg-CO ₂ eq	4.10E+02	1.61E+01	8.87E+01	1.81E+02	6.49E+01
Ozone layer destruction	kg-CFC-11eq	3.78E-05	2.59E-08	1.71E-08	5.49E-06	8.14E-09
Eutrophication	kg-PO ₄ ³⁻ eq	8.76E-03	1.87E-04	8.21E-05	5.68E-03	7.68E-05
Acidification	kg-SO ₂ eq	1.09E+00	1.15E-01	1.06E-01	6.90E-01	6.50E-02
Photochemical ozone	kg-C ₂ H ₄ eq	9.10E-03	1.13E-05	7.05E-04	1.78E-03	5.50E-04

Life cycle inventory analysis (LCI)						
Indicators describing use of primary resources						
		Raw material acquisition	Production	Distribution	Use & maintenance	End-of-Life
RPR _E	MJ	7.94E+02	1.46E+02	4.63E+00	6.96E+02	2.49E+01
RPR _M	MJ	9.69E+00	2.39E-03	1.09E+02	6.63E+02	5.44E-03
NRPR _E	MJ	6.62E+03	5.81E+02	9.91E+02	3.78E+03	3.36E+02
NRPR _M	MJ	8.15E+02	1.84E-01	2.66E+00	2.63E+02	5.18E-02
Consumption of freshwater	m ³	2.36E+00	9.59E-03	1.15E+01	7.00E+01	4.79E-03

Additional explanation	
<ul style="list-style-type: none"> Product destination: North America Calculated based on standard scenario for MFP (EP type). Assumed lifespan of the product is five years. Printing paper is excluded from Use & maintenance stage. The electricity consumption on use stage of this product is calculated based on TEC value measured according to ENERGY STAR® Program Version 3.2. Assumed print volume are 182,400 sheets. 1/4 x 32 (jobs per day) x 19 (sheets per job) x 5 (days) x 4 (weeks) x 12 (months) x 5 (years) = 182,400 (sheets) 	

Supplementary environmental information	
<ul style="list-style-type: none"> ENERGY STAR® Ver.3.2 qualified. 	

Material composition		
Material		Unit
Steel	25	kg
SUS	0.18	kg
Aluminium	0.12	kg
Other Metals	3.0	kg
Plastic	21	kg
Rubber	0.39	kg
Glass	1.9	kg
Paper, Wood	5.9	kg
Circuit Board	1.9	kg
Conversion Parts	2.5	kg
Others	2.1	kg

Regulated hazardous substances		
Substance	CAS No.	Reference to standards or regulations
-	-	-
-	-	-
-	-	-

Assumptions of secondary data used	
Inventory Database: LCI Database IDEA v3.4, Japan EPD Program by SuMPO registered data v1.16.	
Remarks	
-	

- For data quantification, please refer to PCR and Rules on quantification and declaration.
- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied.
(Reference URL : <https://ecoleaf-label.jp/regulation/>)
- This is a selfdeclared translation of EPD that can be accessed at <https://ecoleaf-label.jp/epd/2861> and is published for convenience purposes. Only the original EPD is valid and binding between parties.