

RICOH
imagine. change.

RICOH COMPANY,LTD.

Color MFP (Electrophotography)

RICOH IM C5511



※The ADF and the inner 1-bin tray shown in the image are not included in the LCA calculation scope of the relevant EPD.

Functional unit

Per product

System boundary

■ final products □ intermediate products
Raw material acquisition, Production, Distribution,
Use & maintenance, End-of-Life

Main specifications of the product

Product name: RICOH IM C5511
Main specifications:
MFP (Electrophotography)
Print Speed : Monochrome 55ppm, Color 55ppm (A4)
Maximum Paper Size : A3
Function: Print /Copy /Scan
Included Units in Assessment :
Automatic Duplexing Unit

Company Information

RICOH COMPANY,LTD
<https://www.ricoh.co.jp/>

Registration#	JR-AI-26098E
PCR number	PA-590000-AI-08
PCR name	Imaging input and/or output equipment
Publication date	18 Aug 2026
Verification date	1 Jul 2026
Verification method	Product-by-product
Verification#	JV-AI-26098
Expiration date	30 Jun 2031
PCR review was conducted by:	
Approval date	1 Sep 2023
PCR review panel chair	Masayuki Kanzaki (SuMPO)

Third party verifier*


Hiroyuki Uchida

Independent verification of data & declaration in
accordance with ISO14025

☐ internal ☒ external

*Auditor's name is stated if system certification has been performed.

1. Results of life cycle impact assessment (LCIA)



2. Life cycle inventory analysis (LCI)

Parameter	Unit
Non-renewable material resources	7.9E+01 kg
Renewable material resources	1.0E+02 kg

3. Material composition

Material	Unit
SUS	3.0E+00 kg
Aluminum	1.2E+00 kg
Ordinary steel	4.0E+01 kg
Other metals	2.7E+00 kg
Thermoplastic resin	3.6E+01 kg
Thermosetting resin	4.7E-01 kg
Glass	2.1E+00 kg
Rubber	4.8E-01 kg
Paper	1.3E+01 kg
Lubricant	4.4E-03 kg
Mounting circuit board	1.6E+00 kg
Wood	4.4E-04 kg
Other	1.5E-01 kg



5. Additional explanation

Products selected in the scenario used for load calculation

--MFP (Electrophotography)

- Product destination: JP
- Expected usage period: 5 years
- Estimated number of sheets: 451,200 sheets ※

※Compatible with International Energy Star Program Ver.3.0

-The load on the image output medium (printing paper) is not included.

6-1. Supplementary environmental information

Compliant with the International Energy Star Program Ver.3.0. It also complies with the European RoHS Directive.

Assembly production of this product and production of the main parts, photoconductor and toner, are carried out at an ISO14001 certified factory.

Certification number: JQA-E-70001, SSCC-061-23-E1-0080-R1-L

<https://jp.ricoh.com/sustainability/environment/management/iso>

7. Assumptions of secondary data used

IDEA v3.1.0, and registered data of Japan EPD Program by SuMPO v1.16 are used.

8. Remarks

- For data quantification, please refer to PCR and Rules on quantification and declaration.
- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied.
(Reference URL : <https://ecoleaf-label.jp/regulation/>)