

Environmental Product Declaration

In conformance with
ISO14025 | ISO14040 | ISO14044



RISO KAGAKU CORPORATION

RISO SJ9490U



Paper: Not subject
to calculation

Registration number	Verification date	Publication date	Expiration date	EPD type
SuMPO-EPD-2608-234-1	2026/8/24	2026/10/1	2031/8/23	Single Product EPD

* First publication date

Additional standards in conformance
None

EPD can be updated or withdrawn during the validity period. To confirm the validity of this EPD, check the following website:
<https://ecoleaf-label.jp/epd/search>

● General Information

> Programme

Programme name	SuMPO EPD Japan
Programme operator	Sustainable Management Promotion Organization (SuMPO)
Address	KANDA SQUARE GATE 4F, 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo, 101-0047, Japan
Website	https://ecoleaf-label.jp

> GPI and PCR

GPI	SuMPO EPD Japan General Program Instructions v.2.1.1
PCR name	Imaging input and/or output equipment
PCR registration number	SuMPO-PCR-02001-9-0-0
PCR publication date	2025/10/17
PCR review panel chair	Ken Yamagishi (LCA expert center Co., Ltd.)
PCR valid until	2030/10/16
PCR issuer	Sustainable Management Promotion Organization (SuMPO)

> Verification

Verification Type	Third-party verification in conformance with ISO14025		
	☐ Internal	☒ External	
	☒ Third-party verification by individual verifier	☐ Third-party verification by verification body	☐ Third-party verification by system certification
Verifier	Kengo Minamiyama (K's Business Factory)		

> Standards

Standards in conformance with;	☒ ISO14040:2006	☒ ISO14044:2006	☐ ISO14067:2018
	☒ ISO14025:2006	☐ ISO21930:2007	☐ ISO21930:2017
	☐ EN15804+A2	☐ EN50693:2019	☐ ISO/IEC63366:2025

EPD owner is responsible for the information contained in the EPD and for environmental claims related to the information. For any inquiries or requests regarding the content of the EPD, please contact the EPD owner.

EPDs are comparable only if they comply with this document, use the same sub-PCR where applicable, include all relevant information and are based on equivalent scenarios. Comparability of EPDs is limited to those applying a functional unit.

The LCIA results are relative expressions and do not predict impacts on category endpoints, the exceedance of thresholds, safety margins or risks.

When using weighted averages for calculation, the life cycle impact assessment results, life cycle inventory analysis-related information, waste-related information, and environmental information on output flows do not correspond to information about a specific product.

● EPD Owner's Information

Name of company and dept.	RISO KAGAKU CORPORATION
Address	Riso Research and Design Center, 2-8-1 Gakuen-minami, Tsukuba-shi, Ibaraki 305-0818, Japan
Contact	+81-29-850-5314
LCA practitioner	Kazuki Nomura (Product Environment Section)
Company description	Business Operations: Development, manufacturing, and sales of high-speed inkjet printer "ORPHIS," digital duplicator "RISOGRAPH," along with related hardware, equipment, and consumables.

●Product Information

Product name		RISO SJ9490U	
Product /model number		SJ9490U	
Product specification	Function	133kg	Conversion factor —
	Mass	High-speed digital printer	
	Applications	Print office documents like meeting materials at high speed and low cost.	
	TS*	Method: Digital Printing	
RSL (Reference Service Life)	Service life	5 years	
	In-use conditions	In accordance with the Ministry of the Environment's Basic Policy on Promoting Green Procurement (Digital Printers).	
	reference	Based on the estimated period of use for digital printer as defined in the PCR for Imaging Equipment.	
Manufacturing site(s)		RISO (Thailand) LTD.	
Product description		Product Type: High-speed digital printer Printing Speed: 200 ppm Maximum paper size: 320 mm × 432 mm Target Function for Verification (ADF, Sorter, etc.): — Printing Method: digital printer Product destination: North America	
Website		https://www.riso.co.jp/index.html	

* TS: technical specifications,

●Product Content

Product components	Proportion (%)	Mass (unit)
SUS	4.4	4.96 kg
Aluminium	1.6	1.87 kg
Rubber	0.1	0.12 kg
Others	0.3	0.37 kg
Other Metals	2.4	2.70 kg
Plastic	15.6	17.83 kg
Paper, Wood	0.5	0.59 kg
Circuit Board	2.8	3.18 kg
Copper	5.6	6.34 kg
Steel	66.7	76.04 kg
Packaging materials	Proportion (%)	Mass (unit)
Others	0.3	0.05 kg
Plastic	10.8	2.05 kg
Paper, Wood	52.2	9.91 kg
Cardboard	36.7	6.98 kg
		kg
		kg

●Biogenic Carbon Content

Item	Content (kg-C)	Content (kg-CO ₂ eq)
Biogenic carbon content per product	—	—
Biogenic carbon content in packaging	—	—

● LCA-related Information

> EPD Type Information

EPD type	Product type	☒ Single product EPD	☐ Multiple products EPD	☐ Industry-wide EPD
	Site type	☒ Single site	☐ Multiple sites	
	Value	☒ Specific	☐ Average	☐ Representative ☐ Worst case
Geographical coverage		North America		
Description of representativeness for multiple-products/sites EPD		—		
Description of variation for multiple-products/sites EPD		—		
Description of products covered in the multiple products EPD		—		

> LCA Information

Declared unit	1unit		
Mass per declared unit (Conversion factor to mass)	133kg		
Reference flow (number of products required to fulfil the function)	—		
System boundary	☐ Cradle-to Gate	☐ Cradle-to-Gate with options	☒ Cradle-to-Grave
LCA software	MiLCA Ver.3.1		
LCI database	AIST-IDEAv3.1		
Characterization model	LIME2, IPCC 2013 GWP 100a		
Use of other background data	—		
Secondary data quality	Calculations were conducted using data that meet the secondary data quality requirements specified in the GPI.		
Primary data collection sites	RISO (Thailand) LTD., Ube Works		
Primary data collection period	April 1, 2024 – March 31, 2025		
Biogenic carbon	☒ 0/0 approach	☐ -1/+1 approach	
Information about electricity	Use	☒ Average consumption mix	☐ Others
	Type		
	Purchase date		
	Issuing body		

> Life Cycle Stages

Raw materials acquisition stage	Production stage	Distribution stage	Use stage	End of life stage
☒	☒	☒	☒	☒

■ : declared stage — : stage not declared

> Allocation

In this calculation, process subdivision and allocation were examined following the procedures outlined in the GPI. In the manufacturing processes for the main unit, other digital printer products are generated as co-products. Since avoiding allocation through process subdivision was difficult, and the economic value of the product in this application is equivalent to that of the other digital printers from the same process, physical allocation was applied.

> Cut-off rules

Impacts related to packaging and transport materials used for sourcing input materials.

Impacts related to auxiliary materials.

Transport-related impacts for components, materials, packaging, and accessories.

Impacts related to product storage, warehouse management during transport, sales, and installation processes.

Impacts related to the proper treatment of waste in the raw material procurement and manufacturing stages.

Impacts related to component assembly.

> System Boundary

【Target Life Cycle Stages】

The assessment covers all mandatory life cycle stages: Raw Material Acquisition, Manufacturing, Distribution, Use and Maintenance, and End-of-Life (Final Treatment).

【Temporal System Boundary】

The temporal boundary for the system is set at 100 years, beginning from the year of primary data collection.

> Scenario

【Distribution Stage】

Transportation Mode & Loading Rate: PCR scenarios applied.

Transportation Distance: Both PCR and internal company scenarios applied.

【Use and Maintenance Stage】

Load Calculation During Operation: PCR scenarios applied.

Transportation Mode & Loading Rate: PCR scenarios applied.

Transportation Distance: Both PCR and internal company scenarios applied.

【End-of-Life Stage】


Transportation Mode, Loading Rate, & Distance: PCR scenarios applied.

> Electricity Modelling

All stages: Calculated using the latest available average grid electricity data for each manufacturing and user country.

Environmental Product Declaration for **RISO SJ9490U**

> Life Cycle System Diagram



● LCA Result

> LCIA Indicators

		Total	Raw materials acquisition stage	Production stage	Distribution stage	Use stage	End of life stage
GWP	kg-CO ₂ eq	2.06E+03	7.03E+02	1.25E+01	7.40E+01	1.19E+03	7.66E+01
Ozone layer depletion	kg-CFC-11eq	2.27E-04	1.24E-04	2.03E-09	5.59E-07	1.02E-04	6.67E-07
Acidification	kg-SO ₂ eq	3.31E+00	7.25E-01	7.22E-02	1.59E-01	2.27E+00	8.23E-02
Urban air pollution	kg-SO ₂ eq	2.25E+00	5.38E-01	5.80E-02	7.25E-02	1.54E+00	4.66E-02
Photochemical oxidants	kg-C ₂ H ₄ eq	4.84E-02	2.19E-02	1.11E-05	3.64E-04	2.59E-02	2.76E-04
Hazardous chem. - carcinogenic	kg-C ₆ H ₆ eq	1.70E+00	1.36E+00	3.55E-05	1.08E-02	3.15E-01	1.04E-02
Hazardous chem. - chronic	kg-C ₆ H ₆ eq	2.75E-02	1.77E-02	2.66E-05	2.20E-04	9.42E-03	1.03E-04
Aquatic ecotoxicity	kg-C ₆ H ₆ eq	1.20E+01	4.37E+00	2.04E-05	4.51E-03	7.61E+00	5.41E-03
Terrestrial ecotoxicity	kg-C ₆ H ₆ eq	4.76E+02	7.55E+01	4.05E-04	1.07E-01	4.00E+02	1.27E-01
Eutrophication	kg-PO ₄ ³⁻ eq	8.23E+00	5.24E-02	3.84E-08	1.86E-06	8.18E+00	2.07E-06
Land use - maintenance	m ² /year	4.79E+02	6.33E+01	2.74E-02	5.50E+00	4.09E+02	7.97E-01
Land use - modification	m ²	7.58E+00	2.22E-01	8.09E-04	1.10E-01	7.23E+00	1.60E-02
Resource consumption	kg-Sbeq	9.14E-02	7.51E-02	5.33E-05	2.89E-04	1.58E-02	1.38E-04

> LCI

		Raw materials acquisition stage	Production stage	Distribution stage	Use stage	End of life stage
Use of non-renewable resources	kg	1.54E+02	8.01E-02	1.26E+00	3.99E+01	1.24E+00
Use of non-renewable energy	kg	2.85E+02	5.82E+00	2.10E+01	3.96E+02	9.87E+00
Use of non-renewable energy	MJ	1.11E+04	2.28E+02	9.36E+02	1.65E+04	4.38E+02
Use of renewable resources	kg	1.59E+02	4.93E-03	1.06E-02	1.21E+02	1.15E-02
Use of renewable energy	MJ	1.48E+03	1.45E+01	1.43E+01	1.78E+03	1.70E+01
Consumption of freshwater resources	m ³	5.32E+01	1.11E-03	4.03E-03	2.34E+02	4.10E-03

> Waste Indicators

		Raw materials acquisition stage	Production stage	Distribution stage	Use stage	End of life stage
hazardous waste disposed	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
non-hazardous waste disposed	kg	3.53E+01	4.91E-05	8.36E-02	2.06E+01	9.57E+01
Municipal waste, landfill	kg	7.22E-05	7.19E-14	9.87E-13	1.14E-06	1.39E-12
Industrial waste, landfill	kg	3.53E+01	4.91E-05	8.36E-02	2.06E+01	9.57E+01

*It indicates the amount of waste generated throughout the lifecycle.

> Output Flow Indicators

		Raw materials acquisition stage	Production stage	Distribution stage	Use stage	End of life stage
Components for reuse	kg	—	—	—	—	—
Materials for recycling	kg	—	—	—	—	—
Material for energy recovery	kg	—	—	—	—	—
Exported energy from waste (energy recovery efficiency ≥ 60%)	MJ	—	—	—	—	—
Incineration of waste (energy recovery efficiency < 60%)	Waste disposed	kg	—	—	—	—
	Recovered energy	MJ	—	—	—	—
Waste disposed in landfill and energy recoved from landfill gas	Waste disposed	kg	—	—	—	—
	Recovered energy	MJ	—	—	—	—

> Description of LCA Results

Since generic values (emission factors) are used, the specific characteristics of the materials used in this product may not be fully reflected. Therefore, please use these results as an approximation.

- Product destination: North America
- Calculation method for use and maintenance stage: Based on PCR scenarios
- Assumed product lifespan: 5 years
- Total lifetime print volume: 3,840,000 sheets
- Environmental impact of printing paper during the use and maintenance stage is not included.
- Product selected for the impact calculation scenario: digital printer

● Additional Environmental Information

> Additional Environmental Information not related to LCA

The assembly and production of this product, as well as the manufacturing of its ink and masters, are conducted at ISO 14001 registered factories.

This product is in compliance with the EU RoHS Directive.

> Information on Hazardous Substances

Hazardous materials name	CAS No.	Standards or regulations
—	—	—
—	—	—
—	—	—

● Definitions of Terms

—

● References

- ISO14025:2006 Environmental labels and declarations — Type III environmental declarations — Principles and procedures
- ISO14040:2006 Environmental management - Life Cycle Assessment - Principles and framework
- ISO14044:2006 Environmental management - Life Cycle Assessment - Requirements and guidelines

● Version History

—