

NIPPON STEEL | NIPPON STEEL CORPORATION



Wire Rod



Functional unit

1 t

System boundary

final products intermediate products

Production Stage and optional supplementary information

Main specifications of the product

Production sites : Muroran ,East Nippon and Kyushu Works

Main standards : S45C,SCR,SMN,SCM,SUP,SUJ,SUM

SGD,SWRY,SWRM,SWRH,SWRS,SWRCH,ASBO

ASMN,ASCM

※Please refer to the pamphlet for details

[SteelLinC\(Bar and rod materials\)](#) | [NIPPON STEEL](#)

STEELType : Wirerod(Coil)

Main sizes

Wire Rod : φ3.6 ~ φ22.0

Company Information

NIPPON STEEL CORPORATION

<https://www.nipponsteel.com/en/product/sheet/list/>

Registration#	JR-AW-21005E-B
PCR number	PA-180000-AW-05
PCR name	Steel products except for construction
Publication date	1/21/2022
Verification date	01/16/2024
Verification method	Product-by-product
Verification#	JV-AW-24011
Expiration date	1/15/2029
PCR review was conducted by:	
Approval date	05/10/2023
PCR review panel chair	Yasunari Matsuno (Chiba University)

Third party verifier*

Shinichi Inoue

Independent verification of data & declaration in accordance with ISO14025

internal external

*Auditor's name is stated if system certification has been performed.

Registration number : JR-AW-21005E-B

1. Results of life cycle impact assessment (LCIA)

Parameter	Stage	(1)+(2)+(3)	(1)+(2)	Unit
Global warming IPCC2013 GWP100a		1300	2600	kg-CO ₂ eq
Acidification		1.0	2.9	kg-SO ₂ eq
Eutrophication		0.024	0.047	kg-PO ₄ ³⁻ eq

Be sure to refer to "6-1. Supplementary environmental information" for Scope 3 and carbon footprint calculations.

Table Legend

(1)Raw material supply

(2)Production

(3)Recycling potential

(1)+(2):sum of (1)and(2) (cradle to gate)

(1)+(2)+(3): sum of (1),(2)and(3) (cradle to

Parameter	stage	Unit	(1)+(2)	(1)	(2)	(3)
Global warming IPCC2013 GWP100a		kg-CO ₂ eq	2.6E+03	6.4E+02	1.9E+03	-1.3E+03
Ozone layer destruction		kg-CFC-11eq	6.5E-08	1.6E-07	-1.0E-07	-2.3E-07
Acidification		kg-SO ₂ eq	2.9E+00	5.8E-01	2.4E+00	-1.9E+00
Photochemical ozone		kg-C ₂ H ₄ eq	1.5E-02	6.1E-03	8.5E-03	-2.7E-01
Eutrophication		kg-PO ₄ ³⁻ eq	4.7E-02	1.5E-03	4.5E-02	-2.3E-02

2. Life cycle inventory analysis (LCI)

Parameter	Unit	Unit
Non-renewable material resources	8.1E+02	kg
Non-renewable energy resources	2.7E+04	MJ
Renewable material resources	1.1E+03	kg
Renewable primary energy	-2.6E+02	MJ
Consumption of freshwater	6.9E+00	m ³

3. Material composition

Material	Unit	Unit
iron [Fe]	≥95.0	%
carbon [C]	≤1.10	%
silicon [Si]	≤3.00	%
manganese [Mn]	≤3.00	%
phosphorus [P]	≤0.05	%
sulfur [S]	≤0.05	%

4. Waste to disposal

Parameter	Unit	Unit
Hazardous waste	0.00E+00	kg
Non-hazardous waste.	4.70E+00	kg
Landfill of general waste	0.00E+00	kg
Landfill of industrial waste	1.00E+01	kg

*Data derived from LCA and not assigned to the impact categories of LCIA

5. Additional explanation

① As an indirect effect, the recycling effect of steel materials based on JIS Q 20915 was evaluated, and in this declaration, the value is described in the indirect effect column of the life cycle impact evaluation result breakdown table.

The indirect effect is added to the total value in Tables A1 and A2 above.

The recycling rate used in the calculation is 93.0% (calculation is based on JISQ20915, domestic data for FY2018 (Source: Japan Iron and Steel Federation, Iron Source Association, Steel Can Recycling Association))

② The transport scenario followed PCR.

③ Regarding the constituents of materials and substances, except for iron, the maximum of each upper limit of the target steel material standard is shown.

④ For the primary data, the actual values for FY2018 were used. For the electric power intensity, "Electricity, average of 10 general electric power companies, FY2014" was used.

6-1. Supplementary environmental information

1. Muroran, East Nippon and Kyushu Works are certified to ISO 14001.

2. We provide environment-friendly steel materials such as lead-free and steel materials that make it possible to reduce the weight of automobiles and omit manufacturing processes.

As a typical eco-products (environmentally friendly products), there is an OA shaft using lead-free free-cutting steel.

Reference: Nippon Steel Catalog Steel Bar/ Wire P7

https://www.nipponsteel.com/product/catalog_download/pdf/B001en.pdf

Note on Global warming IPCC2013 GWP100a: When purchasers of this product calculate GHG emissions under GHG Protocol Scope 3, Category 1 for their organization, or when calculating the carbon footprint of products manufactured using this product, they must check the following URL:

<https://www.nipponsteel.com/en/product/cfp/certificate.html>

(The content of the above URL is not subject to EPD verification.)

6-2. Regulated hazardous substances

Substance	CAS No.	Reference to standards or regulations
Manganese [Mn]	7439-96-5	Industrial Safety and Health Act

7. Assumptions of secondary data used

We use the IDEA2.1.3 data and steel scrap data from the Japan Iron and Steel Federation (JISF).

8. Remarks

January 2024; Modification about allocation method of by-product gases

April 2026; Additional explanatory notes added to "6-1. Supplementary environmental information".

- For data quantification, please refer to PCR and Rules on quantification and declaration.
- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied.
(Reference URL : <https://ecoleaf-label.jp/regulation/>)