

Japan EPD Program by SuMPO Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/



Heavy Wide Flange H-Shapes



Functional unit

1 metric ton

System boundary

□ final products ■intermediate products

Production stage (Raw material supply, Transport to factory, Manufacturing)

and Recycling potential

Main specifications of the product

Production Site:

West Japan Works (Kurashiki, Fukuyama) Representative Standards:

Listed on Page 3 (8. Remarks) Shape:

Wide Flange Shapes Representative Section and Thickness:

Listed on Page 3 (8. Remarks)

Registration#	JR-AJ-23017E-B	
PCR number PA-180000-AJ-06		
PCR name	Steel products for construction	
Publication date	1 August 2022	
Verification date	14 February 2025	
Verification method	Product-by-product	
Verification#	JV-AJ-24055	
Expiration date	19 July 2028	
PCR review was	conducted by:	
Approval date	10 May 2023	
PCR review	Yasunari Matsuno	
panel chair	(Chiba University)	
Third party verified	er*	
	Takahiro Atoh	

Independent verification of data & declaration in accordance with ISO14025 and ISO21930

□internal ■external

*Auditor's name is stated if system certification has been performed.

Company Information

JFE Steel Corporation Planning&Marketing Dept., Construction Materials & Services Business Division https://www.jfe-steel.co.jp/en/index.html

Registration number : JR-AJ-23017E-B

Sumpo EPD

Type III Environmental Declaration (EPD)

Registration number : JR-AJ-23017E-B

SuMPC

Japan EPD	Program	by SuMPO
-----------	---------	----------

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

1. Results of life of	ycle impact asse	ssment (LCIA)	
		-	

Production stage and Recycling potential [A1],[A2],[A3] and [D]	Production stage (cradle to gate) [A1],[A2] and [A3]	Unit
2.1E+03	3.1E+03	kg-CO₂eq
-4.3E-01	1.1E+00	kg-SO₂eq
2.5E-02	4.4E-02	kg-PO₄ ³⁻ eq
	Production stage and Recycling potential [A1],[A2],[A3] and [D] 2.1E+03 -4.3E-01 2.5E-02	Production stage and Recycling potential [A1],[A2],[A3] and [D]Production stage (cradle to gate) [A1],[A2] and [A3]2.1E+033.1E+03-4.3E-011.1E+002.5E-024.4E-02

Stage Parameter	Unit	Total	[A1] Raw material supply	[A2] Transport to factory	[A3] Manufacturing	[D] Recycling potential
Global warming IPCC2013 GWP100a	kg-CO ₂ eq	3.1E+03	8.6E+02	2.3E+01	2.2E+03	-1.0E+03
Ozone layer destruction	kg-CFC-11eq	2.1E-07	1.1E-07	1.5E-10	1.0E-07	-1.8E-07
Acidification	kg-SO ₂ eq	1.1E+00	3.8E-01	3.6E-02	7.2E-01	-1.6E+00
Photochemical ozone	kg-C ₂ H ₄ eq	8.8E-03	6.4E-03	6.9E-04	1.6E-03	-2.2E-01
Eutrophication	kg-PO ₄ ³⁻ eq	4.4E-02	1.1E-05	1.3E-13	4.4E-02	-1.9E-02

2. Life cycle inventory analysis (LCI)			
Parameter		Unit	
Non-renewable material resources	1.3E+03	kg	
Non-renewable energy resources	3.6E+04	MJ	
Renewable material resources	1.2E+03	kg	
Renewable primary energy	1.2E+02	MJ	
Consumption of freshwater	2.6E+00	m³	

4. Waste to disposal		
Parameter		Unit
Hazardous waste	0.0E+00	kg
Non-hazardous waste.	1.8E+00	kg

r - 100	Matorial	composition

Material		Unit	
iron [Fe]	≧96.1	wt%	
carbon [C]	≦0.30	wt%	
silicon [Si]	≦0.65	wt%	
manganese [Mn]	≦1.65	wt%	
phosphorus [P]	≦0.05	wt%	
sulfur [S]	≦0.05	wt%	
copper [Cu]	≦0.60	wt%	
nickel [Ni]	≦0.50	wt%	
vanadium [V]	≦0.11	wt%	

*Data derived from LCA and not assigned to the impact categories of LCIA

5. Additional explanation

- This EPD shows the results calculated without applying system extensions.
- Scrap recycling potential is calculated based on ISO 20915/JIS Q 20915 and shown as [D] in table 1. Recycling ratio used in this calculation is 93.0%. (Using data is 2018FY from The Japan Iron and Steel Federation, The Japan ferrous raw materials association and The Japan Steel Can recycling Association).
- The environmental impact of self-generated electricity was calculated as primary data of fuel and the basic unit data of grid power consumption is the average of 10 electric power suppliers of Japan in 2014FY.
- Each item (except iron) in table 3 is the maximum value of all product standards covered by this EPD.

• Primary data in 2018 is used.



Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

6-1. Suppl	lementary	environmental	informatio

The production site is certified to ISO 14001.

6-2. Regulated hazardous substances				
Substance	CAS No.	Reference to standards or regulations		
manganese [Mn]	7349-96-5	 Industrial Safety and Health Act 		
copper [Cu]	7440-50-8	 Industrial Safety and Health Act 		
nickel [Ni]	7440-02-0	 Industrial Safety and Health Act 		
chromium [Cr]	7440-47-3	 Industrial Safety and Health Act 		
molybdenum [Mo]	7439-98-7	 Industrial Safety and Health Act 		
cobalt [Co]	7440-48-4	 Industrial Safety and Health Act 		

7. Assumptions of secondary data used

IDEA v2.1.3 database is used. Steel scrap data (JP-AJ-0001) from the Japan Iron and Steel Federation are used.

8. Remarks

Representative standards: SN400A, SN400B, SN400C, SN490B, SN490C, SM400A, SM400B, SM400C, SM490A, SM490B, SM490C, SS400, SS490, SS540, SM490YA, SM490YB, SM520B, SM520C, HBL[®]-JH325B, HBL[®]-JH325C, HBL[®]-JH355B, HBL[®]-JH355C, SS275, SM275A, SM275B, SM355A, SM355B, SHN355 and others Representative section and thickness (unit mm, t=thickness): H418(t15)×402(t30) - 498(t45)×432(t70) H492(t15)×465(t20) - 572(t45)×510(t60) H670(t25)×475(t30) - 770(t70)×520(t80)

• July, 2023; Correction of double counting on upstream and modification of allocation method of by-product gases

 $\cdot\,$ February, 2025; Modification about system boundary and allocation of by-product gases.

- For data quantification, please refer to PCR and Rules on quantification and declaration.

- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied. (Reference URL : https://ecoleaf-label.jp/regulation/)

Registration number : JR-AJ-23017E-B