

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/



Monochrome Printer ECOSYS PA4500x

KYOCERA Document Solutions Inc.

Functional unit

Per unit of product

System boundary

■ final products □ intermediate products Raw material acquisition-Production-Distribution-Use & maintenance-End-of-Life

Main specifications of the product

Model name : Monochrome Printer ECOSYS PA4500x Making Technology :Electrophotographic Printer (EP) Printng Speed: Monochrome 45 Pages per minute in A4 Priting paper :Maximum Folio (Legal) Duplex function: Standard

Company Information

KYOCERA Document Solutions Inc. Quality Assurance Division Reliability Assurance Section 11 TEL : 06-6764-3764 http://www.kyoceradocumentsolutions.co.jp/

Registration#	JR-AI-23040E	
PCR number	PA-590000-AI-05	
PCR name	Imaging input and/or output equimpent	
Publication date	2/14/2023	
Verification date	2/3/2023	
Verification method	System certificaion	
Verification#	JV-AI-23040E	
Expiration date	2/2/2028	
PCR review was conducted by:		
Approval date	1/6/2023	
PCR review	Masayuki Kanzaki	
panel chair	Sustanable Management Promotion Organization	
Third party verifier*		

Wataru Kawamura

Independent verification of data & declaration in accordance with ISO14025

□internal

■ external

*Auditor's name is stated if system certification has been performed.

Registration number : JR-AI-23040E



EcoLeaf

Type III Environmental Declaration (EPD)

Registration number : JR-AI-23040E

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

1. Results of life cycle impact assessment (LCIA) 0% 20% 40% 60% 80% 100% Global warming IPCC2013 GWP100a 330 kg-CO2eq Acidification 0.24 kg-SO2eq 52% 14% 35% 0.039 0% Resources consumption kg-Sbeq Raw material acquisition Production Distribution Use & maintenance stage Raw material Use & Production End-of-Life Parameter Unit Total Distribution acquisition maintenance kg-CO₂eq 3.3E+02 1.5E+02 5.9E+00 4.7E+00 1.6E+02 1.5E+01 Global warming IPCC2013 GWP100a Acidification kg-SO₂eq 2.4E-01 1.3E-01 1.9E-03 1.0E-02 8.6E-02 1.8E-02 Resources consumption kg-Sbeq 3.9E-02 2.6E-02 2.5E-05 2.0E-05 1.2E-02 1.3E-05

2. Life cycle inventory analysis (LCI)				
Parameter		Unit		
Non-renewable material resources	1.5E+01	kg		
Non-renewable energy resources	5.7E+03	MJ		
Renewable material resources	9.7E+01	kg		
Renewable primary energy	1.2E+02	MJ		

3. Material composition			
Material		Unit	
Steel	4.3E+00	kg	
SUS	1.5E-01	kg	
Cu	8.5E-01	kg	
Al	2.6E-01	kg	
Glass	6.8E-02	kg	
Thermoplastics resin	8.2E+00	kg	
Thermosetting resin	1.1E-01	kg	
Rubber	1.8E-02	kg	
Paper	4.0E+00	kg	
Assembled circuit board	1.0E+00	kg	
Medium-sized motor	5.0E-01	kg	

5. Additional explanation

- Product destination: Japan
- · Calculation method of use stage (scenario)
- $\textcircled{1}\xspace$ Usage period: five years
- ②Estimated number of sheets used:
- Monoclome 297,600 ③The impact of printing paper is not included
- Products selected in the scenario used
 - for inventory calculation : Multifunction device (EP)
- Conformed to the International ENERGY STAR® Ver3.0 Program
- · Consumables will be shipped directly from the factory to

the country of sale separately from the product body and all of them are accounted for in the use and maintenance



Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan

https://ecoleaf-label.jp/

6-1. Supplementary environmental information

 \cdot Conformed to the International ENERGY STAR $\ensuremath{\mathbb{R}}$ Ver3.0 Program

Manufactured at ISO14001 certified factories.

Registration number : JR-AI-23040E

• Halogenated flame retardants are not used in Plastic housing and outer package.

7. Assumptions of secondary data used

IDEA v2.1.3 and Japan EPD Program by SuMPO Registry data v1.13

8. Remarks

-

- For data quantification, please refer to PCR and Rules on quantification and declaration.

- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied. (Reference URL : https://ecoleaf-label.jp/regulation/)

Registration number : JR-AI-23040E