Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

KONICAMINOLTA, INC.

bizhub 950i



Functional unit

Per unit of product

System boundary

■ final products □intermediate products

Raw material acquision, Production, Distribution,

Use & maintenance, End-of-Life

Main specifications of the product

Model name: bizhub 950i

■ Marking technologies : Electrophotographic Printer (EP)

■ Printing speed(8.5"×11"): Monochrome 95 prints-per

-minute

■ Printing paper : Maximum 11"×17"

■ Duplex function: Standard

Company Information

Please direct any inquiries or comments to e-mail: eco-support@konicaminolta.com

Registration#	JR-A1-2221/E			
PCR number	PA-590000-AI-06			
PCR name	Imaging input and/or output equipment			
Publication date	05/10/2023			
Verification date	04/27/2023			
Verification method	System certificaion			
Verification#	JV-AI-22217			
Expiration date	04/26/2028			
PCR review was conducted by:				
Approval date	03/29/2023			

panel chair (Sus Third party verifier*

PCR review

Kazuo Naitou

Masayuki Kanzaki

Independent verification of data & declaration in accordance with ISO14025

□internal ■ external

(Sustainable Management Promotion Organization)

Registration number: JR-AI-22217E

^{*}Auditor's name is stated if system certification has been performed.




Resources consumption

Japan EPD program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

Type III Environmental Declaration (EPD) Registration number: JR-AI-22217E

6. 2E-01 kg-Sbeq



stage			material			maintenanc	
Parameter	Unit	Total	acquisition	Production	Distribution	е	End-of-Life
Global warming IPCC2013 GWP100a	kg-CO₂eq	2.8E+03	1.2E+03	1.6E+02	1.4E+02	9.3E+02	3.0E+02
Acidification	kg-SO₂eq	2.0E+00	8.5E-01	3.4E-02	4.0E-01	5.2E-01	2.2E-01
Resources consumption	kg-Sbeq	6.2E-01	2.0E-01	4.5E-04	5.5E-04	4.1E-01	5.1E-04

2. Life cycle inventory analysis (LCI)					
Parameter		Unit			
Non-renewable material resources	2.0E+02	kg			
Renewable material resources	3.0E+02	kg			

3. Material composition					
Material		Unit			
Steel	1.3E+02	kg			
SUS	3.7E+00	kg			
Al	1.3E+00	kg			
Other metals	3.0E+00	kg			
Glass	2.2E+00	kg			
Thermoplastics resin	4.3E+01	kg			
Wood	1.1E+01	kg			
Paper	1.3E+01	kg			
Rubber	1.1E+00	kg			
Assembled circuit board	4.9E+00	kg			
Medium-sized motor	1.1E+01	kg			

5. Additional explanation

- · Production destination: North America
- Calculation method of use stage (Caluclated by the standard scenario for MFP (EP type))
 - Expected usage period : five years
 - Estimated number of sheets used: 1,353,600
 - The impact of printing paper is not included
 - The impact of expendables and Maintenance parts are included in the stage of Use&maintenance.
- ※ Conformed to the International ENERGY STAR® Ver3.0 Program



Japan EPD program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

6-1. Supplementary environmental information

· ENERGY STAR® qualified

7. Assumptions of secondary data used

IDEA v2.1.3 and Ecoleaf Enviromental Labeling Program Registry data v1.10

8. Remarks

- For data quantification, please refer to PCR and Rules on quantification and declaration.
- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied. (Reference URL : https://ecoleaf-label.jp/regulation/)

Registration number: JR-AI-22217E