
## NIPPON STEEL | NIPPON STEEL CORPORATION

# Welded Pipes for Mechanical Use



## Application examples of steel pipes for mechanical use



#### Functional unit

#### 1 t

#### System boundary

final products	intermediate	products
initial producto	mitormoulato	producto

Production Stage and optional supplementary infomation

### Main specifications of the product

Production sites : East Nippon Works/Kimitsu Area, Nagoya Works,Kansai Works ,Kansai Works/Wakayama Area(Wakayama) ,Kyushu Works/Oita Area(Hikari)

Main standards : STKM11A~20A, S10C~50C,

SCM415/420/440,

SAE1536/1541/4130, 26MnB5, 34MnB5, STAM290 ~780

Main sizes

Outer diameter: 12.7~216.3mm, Thickness: 0.8~15.0mm

#### **Company Information**

#### NIPPON STEEL CORPORATION

https://www.nipponsteel.com/en/product/pipe/

Registration#	JR-AW-23018E
PCR number	PA-180000-AW-05
PCR name	Steel products except for construction use
Publication date	02/05/2024
Verification date	11/01/2023
Verification method	Product-by-product
Verification#	JV-AW-23018
Expiration date	10/31/2028
PCR review was	conducted by:
Approval date	05/10/2023
PCR review	Yasunari Matsuno
panel chair	Chiba University

#### Third party verifier\*

Yasuo Koseki

Independent verification of data & declaration in accordance with ISO14025

internal

external

\*Auditor's name is stated if system certification has been performed.

Registration number: JR-AW-23018E



### EcoLeaf

Registration number : JR-AW-23018E

Japan El	PD Progr	am by	SuMPO
----------	----------	-------	-------

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan

https://ecoleaf-label.jp

1. Results of life cycle	impact ass	essment	(LCIA)				
Stage       Parameter	(1)+(2)+(3)	(1)+(2)	Unit	(1)Raw m	Table Legend (1)Raw material supply (2)Production (3)Recycling potential (1)+(2):sum of (1)and(2) (cradle to gate) (1)+(2)+(3): sum of (1),(2)and(3) (cradle to gate with allocation for scrap recycling)		
Global warming IPCC2013 GWP100a	1600	2800	kg-CO <sub>2</sub> eq	(3)Recycl			iate)
Acidification	0.19	2.1	kg-SO <sub>2</sub> eq	(1)+(2)+			adle to
Photochemical ozone	0.034	0.057	kg-PO4 <sup>3-</sup> eq				
stage							
Parameter	Unit	(1)+(2)	(1)	(2)			(3)
Global warming IPCC2013 GWP100a	kg-CO <sub>2</sub> eq	2.8E+03	6.2E+02	2.2E+03			-1.2E+03
Ozone layer destruction	kg-CFC-11eq	1.2E-07	1.3E-07	-7.5E-09			-2.2E-07
Acidification	kg-SO <sub>2</sub> eq	2.1E+00	7.3E-01	1.3E+00			-1.9E+00
Photochemical ozone	kg-C₂H₄eq	2.0E-02	8.0E-03	1.2E-02			-2.6E-01
Eutrophication	kg-PO <sub>4</sub> <sup>3-</sup> eq	5.7E-02	6.2E-03	5.0E-02			-2.2E-02

2. Life cycle inventory analysis (LCI)			
Parameter		Unit	
Non-renewable material resources	7.9E+02	kg	
Renewable material resources	1.1E+03	kg	
Non-renewable energy resources	3.0E+04	MJ	
Renewable primary energy	8.8E+01	MJ	
Consumption of freshwater	1.9E+00	m <sup>3</sup>	

3. Material composition		
Material		Unit
Fe	94.7	%
С	0.55	%
Si	0.55	%
Mn	1.65	%
Ρ	0.04	%
S	0.05	%
Cu	0.30	%
Ni	0.25	%
Cr	1.20	%
Мо	0.30	%
Nb	0.15	%
V	0.15	%
Ti	0.10	%
В	0.01	%

## 4. Waste to disposal

Parameter		Unit
Hazardous waste	0.00E+00	kg
Non-hazardous waste.	2.9E+00	kg

\*Data derived from LCA and not assigned to the impact categories of LCIA

#### 5. Additional explanation

 Each LCI includes allocation for scrap recycling as an optional supplementary information(3) at table.1. Recycling rate (RR) used in this calculation is 93.0% (calculated based on ISO 20915/JIS Q20915 and using Japan data in 2018 from Japan Iron and SteelFederation and Japan Steel Can Recycling Association).
Scenarios of transport to site follow the PCR.
Each item (except iron) in table 3 is the maximum value of all product standards covered by this EPD.However, the iron content in each product is never less than 94.7%, and the contents of other components are adjusted.
Primary data collected in 2018. The source of the unit power consumption is the average of 10 electric power suppliers of Japan in 2014.

5. For the transport of metallurgical coal, the amount is double counted due to the characteristics of the inventory database on which this estimation is based.



## EcoLeaf

Registration number: JR-AW-23018E

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp

6-1. Supplementary environmental information

Each production site is certified to ISO 14001.

6-2. Regulated hazardous substances		
Substance	CAS No.	Reference to standards or regulations
Manganese [Mn]	7439-96-5	Industrial Safety and Health Act
Cupper [Cu]	7440-50-8	Industrial Safety and Health Act
Chromium [Cr]	7440-47-3	Industrial Safety and Health Act
Nickel [Ni]	7440-02-0	Industrial Safety and Health Act

7. Assumptions of secondary data used

The IDEA2.1.3 data and steel scrap data(JP-AJ-0001) from the Japan Iron and Steel Federation are used.

8. Remarks

\_

- For data quantification, please refer to PCR and Rules on quantification and declaration.

- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied. (Reference URL : https://ecoleaf-label.jp/regulation/)

Registration number: JR-AW-23018E