EcoLeaf Type III Environmental Declaration (EPD) Registration number : JR-AI-23340E

Japan EPD Program by SuMPO Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/





Functional unit

Per unit of product

System boundary

■ final products □ intermediate products Raw material acquisition,Production,Distribution, Use & maintenance,End-of-Life

Main specifications of the product

Model name : DS-C480W Main Specifications

- Sheet-fed scanner(Without Flat-bed) For Parsonal
- Scanning Speed : Simplex or Duplex, 30ppm(60ppm)
- Scanning Size : 215.9mm × 5,588mm
- Scanning Resolution : 50~1200dpi (1dpi pitch)
- Scanning Method CIS
- *This product is destined for North America

Company Information

Seiko Epson Corporation http://www.epson.com/ http://www.epson.jp/contact/(Japanese) 3-3-5 Owa, Suwa-Shi, Nagano,392-0001, Japan TEL 81-266-52-5353 (Japan)

Registration#	JR-AI-23340E
PCR number	PA-590000-AI-8
PCR name	Imaging input and/or output equipment
Publication date	11/2/2023
Verification date	10/16/2023
Verification method	Product-by-product
Verification#	JV-AI-23340
Expiration date	10/15/2023
PCR review was	conducted by:
Approval date	9/1/2023
PCR review	Masayuki Kanzaki
panel chair	(Sustainable Management Promotion Organization)

Third party verifier*

Tetsuya Okuyama

Independent verification of data & declaration in accordance with ISO14025

□internal

external

*Auditor's name is stated if system certification has been performed.

Registration number : JR-AI-23340E



EcoLeaf

Type III Environmental Declaration (EPD)

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

Registration number : JR-AI-23340E

1. Results of life cycle	impact as	sessmen	t (LCIA)					
			0%	20% 4	0% 60	0% 80	% 100%	
Global warming IPCC2013 GWP100a	47	kg-CO2eq		66%			25% <mark>4%</mark>	
Acidification	0.026	kg-SO2eq			87%	2% J 0%	<mark>8% 1</mark> %	
Resources consumption	0.0034	kg-Sbeq			97%	0%		
	Raw material acquisition Production Distribution Use & maintenance End-of-Life							
stage Parameter	Unit	Total	Raw material acquisition	Production	Distribution	Use & maintenance	End-of-Life	
Global warming IPCC2013 GWP100a	kg-CO ₂ eq	4.7E+01	3.1E+01	1.2E+00	1.2E+00	1.2E+01	1.7E+00	
Acidification	kg-SO ₂ eq	2.6E-02	2.3E-02	9.3E-05	2.0E-03	9.1E-04	3.7E-04	
Resources consumption	kg-Sbeq	3.4E-03	3.3E-03	2.9E-06	4.9E-06	8.3E-05	1.1E-06	

2. Life cycle inventory analysis (LCI)				
Parameter		Unit		
Non-renewable material resources	2.2E+00	kg		
Renewable material resources	4.5E+00	kg		

3. Material composition					
Material		Unit			
Steel	11	%			
SUS	0	%			
Aluminum	0	%			
Other metal	13	%			
Plastic	39	%			
Rubber	1	%			
Glass	1	%			
Paper and wood	18	%			
Circuit Board	6	%			
Others	11	%			

5. Additional explanation

- Product destination: North America

- Calculation method of use stage (scenario)*

- Expected usage : 5 years
- Scans per day : 64 sheets / day (8 scans / day)
- Workdays per month : 20 days / month
- Working days per year : 240 days / year

- Total scans : 9,600 times (76,800 sheets) / 5 years

*For the load calculations during the Use & maintenance stage, scenarios were set up under the above conditions to match the user's actual usage conditions.

6-1. Supplementary environmental information

- This product and main compornents are produced in our ISO 14001 certified factories.

- Compliant with the International Energy Star Program Ver.3.0.

- It also complies with the European RoHS Directive.

7. Assumptions of secondary data used

We used IDEA v2.1.3 and SuMPO Environmental Label Program registration intensity v1.13.

8. Remarks

- For data quantification, please refer to PCR and Rules on quantification and declaration.

- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied. (Reference URL : https://ecoleaf-label.jp/regulation/)

Registration number : JR-AI-23340E