



EcoLeaf

Type III Environmental Declaration (EPD)

Registration number : JR-AI-24178E

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization

14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan

<https://ecoleaf-label.jp/>

Canon Inc.

imageRUNNER ADVANCE DX 617iZ(For AU)



Functional unit

Per unit product

System boundary

final products intermediate products
Raw Material acquisition, Production, Distribution,
Use & maintenance, and End-of-Life stage

Main specifications of the product

Model name

imageRUNNER ADVANCE DX 617iZ(For AU)

Specifications

- Multi Functional Printer (Electrophotography)
- BW
- Print Speed : Up to 61 ipm (A4)
- Max paper size : A4
- Print/copy/scan/FAX/Duplex printing/ADF
- Weight: approx.43.00kg(All in one Cartridge not included)

Company Information

Canon Inc.

30-2, Shimomaruko 3-chome, Ohta-ku,
Tokyo 146-8501, Japan +81-3-3758-2111

Registration#	JR-AI-24178E
PCR number	PA-590000-AI-08
PCR name	Imaging input and/or output equipment
Publication date	4/17/2024
Verification date	4/12/2024
Verification method	Product-by-product
Verification#	JV-AI-24178
Expiration date	4/11/2029
PCR review was conducted by:	
Approval date	9/1/2023
PCR review panel chair	Masayuki Kanzaki Sustainable Management Promotion Organization

Third party verifier*

internal external
Kazuo Naito

Independent verification of data & declaration in
accordance with ISO14025


internal external

*Auditor's name is stated if system certification has been performed.

Registration number : JR-AI-24178E



1. Results of life cycle impact assessment (LCIA)



Parameter	stage		LCIA Results				
	Unit	Total	Raw material acquisition	Production	Distribution	Use & maintenance	End-of-Life
Global warming IPCC2013 GWP100a	kg-CO ₂ eq	1.2E+03	5.5E+02	1.0E+02	2.9E+01	4.1E+02	6.5E+01
Ozone layer destruction	kg-CFC-11eq	1.1E-04	5.2E-05	4.3E-08	2.1E-10	5.9E-05	5.4E-07
Acidification	kg-SO ₂ eq	7.9E-01	4.3E-01	1.7E-02	4.7E-02	2.8E-01	2.7E-02
Resources consumption	kg-Sbeq	5.0E-02	4.1E-02	1.8E-04	1.2E-04	8.7E-03	3.7E-05

2. Life cycle inventory analysis (LCI)

Parameter	Value	Unit
Non-renewable energy resources	1.7E+04	MJ
Renewable primary energy	3.2E+02	MJ

3. Material composition

Material	Value	Unit
Common Steel	26	%
Stainless Steel	0.51	%
Aluminium	0.22	%
Other Metal	2.3	%
Plastic	35	%
Rubber	1.0	%
Glass	1.4	%
Paper/Wood	25	%
Circuit Board	4.1	%
Others	4.0	%



EcoLeaf

Type III Environmental Declaration (EPD)

Registration number : JR-AI-24178E

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization
14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan
<https://ecoleaf-label.jp/>

5. Additional explanation

Calculated in the following conditions;

- Printing paper is not considered.
- Expected use period is 5 years.
- The standard scenario for Multifunction Device (EP type).
- Australia market.
- Print volume: 556,800 sheets.
- The applied Energy Star program version is 3.0.

6-1. Supplementary environmental information

Complies with the EU RoHS Directive (2011/65/EU) and its amendments including 2015/863/EU.

Manufactured at ISO 14001 certified factories.

7. Assumptions of secondary data used

IDEA v2.1.3, and registered data v1.13 of Japan EPD Program by SuMPO are used.

8. Remarks

- For data quantification, please refer to PCR and Rules on quantification and declaration.
- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied.
(Reference URL : <https://ecoleaf-label.jp/regulation/>)

Registration number : JR-AI-24178E