Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/



EPSON

WorkForce Enterprise
WF-C21000 (Europe)

Seiko Epson Corporation

Functional unit

Per product

System boundary

■ final products □intermediate products
Raw material
acquisition,Production,Distribution,
Use & maintenance,End-of-Life

Main specifications of the product

Model name: WorkForce Enterprise WF-C21000 Main Specifications

■ Multifunction device (High Performance Inkjet)

■ Color

■ Print speed: 100ppm (single-sided A4 sheets)

■ Maximum paper size (standard cassette): A3

■ Automatic duplex printing

%This product is destined for Europe

Company Information

Seiko Epson Corporation http://www.epson.com/ http://www.epson.jp/contact/ (Japanese) 3-3-5 Owa, Suwa-shi, Nagano-ken, Japan TEL 81-266-52-5353 (Japan)

Registration#	JR-AI-24012E		
PCR number	PA-590000-AI-08		
PCR name	Imaging input and/or output equipment		
Publication date	1/30/2024		
Verification date	1/23/2024		
Verification method	Product-by-product		
Verification#	JV-AI-24012		
Expiration date	1/22/2029		
PCR review was conducted by:			
Approval date	9/1/2023		
PCR review	Masayuki Kanzaki		
panel chair	(SuMPO)		

Third party verifier*

Yuki Sakamoto

Independent verification of data & declaration in accordance with ISO14025

□internal	■ external
-----------	------------

Registration number: JR-AI-24012E

^{*}Auditor's name is stated if system certification has been performed.

EcoLeaf Type III Environmental Declaration (EPD) Registration number: JR-AI-24012E

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

1. Results of life cycle impact assessment (LCIA)							
			0%	20% 4	0% 60)% 80%	% 100%
Global warming IPCC2013 GWP100a	1800	kg-CO2eq		66%	6% —	3%	18% <mark>7%</mark>
Acidification	1.6	kg-SO2eq		69%		13%	6 13%
Urban area air pollution	0. 32	kg-SO2eq		72%	0%	0% -	28% 0%
■ Raw material acquisition ■ Production ■ Distribution ■ Use & maintenance ■ End-of-Life							
stage Parameter	Unit	Total	Raw material acquisition	Production	Distribution	Use & maintenance	End-of-Life
Global warming IPCC2013 GWP100a	kg-CO₂eq	1.8E+03	1.0E+03	9.4E+01	5.4E+01	5.4E+02	1.1E+02
Acidification	kg-SO₂eq	1.6E+00	9.1E-01	8.6E-03	5.3E-02	4.2E-01	1.8E-01
Resources consumption	kg-Sbeq	3.2E-01	1.8E-01	2.4E-04	2.3E-04	1.3E-01	8.0E-05

2. Life cycle inventory analysis (LCI)					
Parameter		Unit			
Non-renewable material resources	1.7E+02	kg			
Renewable material resources	4.2E+02	kg			

3. Material composition				
Material		Unit		
Steel	1.0E+02	kg		
SUS	4.2E+00	kg		
Aluminum	3.3E+00	kg		
Other metal	1.1E+01	kg		
Plastic	6.5E+01	kg		
Rubber	1.0E+00	kg		
Glass	1.4E+00	kg		
Paper and wood	2.0E+01	kg		
Circuit Board	2.0E+00	kg		
Other	1.5E+01	kg		

5. Additional explanation

- Product destination: Europe

- Calculation method of use stage (scenario)

- Expected usage period: 5 years
- Estimated number of use: 1,497,600 sheets*
- Print measuring method (pattern): ISO/IEC 19752
- Inventory of the print paper is not included
- Products selected in the scenario used for inventory calculation
 - Multifunction device (High Perfomance IJ)
- * In accordance with the ENERGY STAR® Ver.3.0.
- 1,497,600sheets = (32 pages x 156 jobs/day x 5 days)
- / 4 x 4 weeks x 12 months x 5 years

6-1. Supplementary environmental information

- This product and main compornents are produced in our ISO 14001 certified factories.
- Compliant with the International Energy Star Program Ver.3.0.It also complies with the European RoHS Directive.

7. Assumptions of secondary data used

We used IDEA v2.1.3 and SuMPO Environmental Label Program registration intensity v1.13.

8. Remarks

- For data quantification, please refer to PCR and Rules on quantification and declaration.
- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied. (Reference URL : https://ecoleaf-label.jp/regulation/)

Registration number: JR-AI-24012E