



EcoLeaf

Type III Environmental Declaration (EPD)

Registration number : JR-AI-22188E

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization

2-1, Kaji-cho 2 chome, Chiyoda-ku, Tokyo Japan


<https://ecoleaf-label.jp/>

**TOSHIBA**

Toshiba Tec Corporation

Multifunctional Digital Color Systems

**e-STUDIO3025AC**



### Functional unit

Per unit of product

### System boundary

- final products  intermediate products

Raw material acquisition - Production -

Distribution - Use & maintenance - End-of-Life

### Main specifications of the product

Model name: e-STUDIO3025AC

- Digital Color MFD (EP Type)
- Print speed: Color 30ppm (LT)  
Monochrome 30ppm (LT)

- Maximum paper size: LD

- Automatic duplex printing

### Company Information

Toshiba Tec Corporation

Engineering Planning Group

Engineering Planning Dept.

TEL: +81-55-976-7011

<https://www.toshibatec.co.jp/>

Registration#	JR-AI-22188E
PCR number	PA-590000-AI-04
PCR name	Imaging input and/or output equipment
Publication date	8/31/2022
Verification date	8/18/2022
Verification method	Product-by-product
Verification#	JV-AI-22188
Expiration date	8/17/2027
<b>PCR review was conducted by:</b>	
Approval date	4/1/2022
PCR review panel chair	Masayuki Kanzaki (Sustainable Management Promotion Organization)

### Third party verifier\*

Hiroyuki Nakamura

Independent verification of data & declaration in accordance with ISO14025


internal  external

\*Auditor's name is stated if system certification has been performed.

Registration number : JR-AI-22188E



**1. Results of life cycle impact assessment (LCIA)**



Parameter	stage	Unit	Total	Raw material acquisition	Production	Distribution	Use & maintenance	End-of-Life
Global warming IPCC2013 GWP100a		kg-CO <sub>2</sub> eq	8.8E+02	5.1E+02	1.4E+01	7.9E+01	1.7E+02	1.1E+02
Ozone layer destruction		kg-CFC-11eq	6.4E-05	5.2E-05	3.1E-08	6.1E-10	1.0E-05	1.3E-06
Acidification		kg-SO <sub>2</sub> eq	6.8E-01	3.8E-01	2.3E-03	1.7E-01	6.6E-02	5.9E-02
Urban area air pollution		kg-SO <sub>2</sub> eq	3.9E-01	2.6E-01	1.1E-03	6.4E-02	3.8E-02	2.5E-02
Photochemical ozone		kg-C <sub>2</sub> H <sub>4</sub> eq	7.3E-03	5.9E-03	2.5E-05	3.4E-04	8.3E-04	2.0E-04
Toxic chemicals(cancer)		kg-C <sub>6</sub> H <sub>6</sub> eq	1.3E-01	1.2E-01	2.7E-06	2.4E-08	4.0E-03	3.1E-05
Toxic chemicals(chronic disease)		kg-C <sub>6</sub> H <sub>6</sub> eq	7.0E-04	6.6E-04	4.0E-07	3.5E-09	3.3E-05	4.6E-06
Aquatic toxicity		kg-C <sub>6</sub> H <sub>6</sub> eq	8.6E-01	8.1E-01	6.1E-04	5.4E-06	4.6E-02	7.0E-03
Biological toxicity		kg-C <sub>6</sub> H <sub>6</sub> eq	3.8E+01	3.6E+01	1.5E-02	1.3E-04	1.4E+00	1.7E-01
Eutrophication		kg-PO <sub>4</sub> <sup>3</sup> -eq	3.3E-03	4.1E-05	2.9E-03	5.3E-13	2.1E-04	1.9E-04
Land use(Occupation)		m <sup>2</sup> /year	3.9E+01	3.3E+01	4.7E-02	4.1E+00	1.9E+00	2.8E-01
Land use(Transformation)		m <sup>2</sup>	5.8E-01	4.5E-01	9.5E-04	8.2E-02	3.5E-02	5.6E-03
Resources consumption		kg-Sbeq	8.1E-02	6.3E-02	2.9E-05	3.3E-04	1.7E-02	6.6E-05

**2. Life cycle inventory analysis (LCI)**

項目	Value	単位
Non-renewable material resources	5.7E+01	kg
Non-renewable energy resources	1.3E+04	MJ
Renewable material resources	1.2E+02	kg
Renewable primary energy	2.5E+02	MJ

**3. Material composition**

Material	Value	Unit
Ordinary steel	4.0E+01	kg
SUS	6.7E-01	kg
Other metals	1.5E+00	kg
Aluminium	4.6E-01	kg
Glass	2.8E+00	kg
Thermoplastic resin	2.7E+01	kg
Thermosetting resin	2.1E-01	kg
Rubber	9.4E-01	kg
Paper	8.6E+00	kg
Wood	5.3E+00	kg
Circuit Board	2.0E+00	kg
Medium-sized motor	2.7E+00	kg



### 5. Additional explanation

- Product destination: North America
  - Calculation method of use stage (scenario)
    - Expected usage period: five years
    - Estimated number of use: 135,000 sheets\*
    - Print measuring method (pattern): ISO/IEC 19798
    - Automatic Document Feeder and Paper Feed Pedestal is optional, its impact is not included.
    - Inventory of the print paper is not included
  - Products selected in the scenario used for Inventory
    - Multifunction device (EP type)
- \* Electric power in the use and maintenance stage is evaluated using TEC value according to International ENERGY STAR program Version3.1 and the public electric-power-consumption-rate in the United States.  
(30 jobs/day) x (15 sheets/job) x (1/4) x 5days x 4weeks x 12months x 5years = 135,000 sheets

### 6-1. Supplementary environmental information

- This product is produced in our ISO 14001 certified factories.
- ENERGY STAR®Ver.3.1 qualified.
- EU RoHS2 compliant.

### 7. Assumptions of secondary data used

- Inventory Database:LCI Database IDEA v2.1.3,Japan EPD Program by SuMPO registered data v1.10.

### 8. Remarks

-

- For data quantification, please refer to PCR and Rules on quantification and declaration.
- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied.  
(Reference URL : <https://ecoleaf-label.jp/regulation/>)