



Yamato Steel Co., Ltd.

H-Beams/Steel H piles



Functional unit		Registration#	JR-AJ-20001C	
1t		PCR number	PA-180000-AJ-03	
		PCR name	Steel products for construction	
System boundary		Publication date	8/23/2020	
\Box final products	■intermediate products	Verification date	7/31/2020	
Production Stage and optional supplementary infomation		Verification method	Product-by-product	
		Verification#	JV-AJ-20001	
		Expiration date	7/30/2025	
Main specifications of the product Production sites : Head office (Himeji) Main standareds :SS400,SS490,SM400A.B.C,SM490A.B.C, SM490YA.YB,SM520B,SN400A.B.C,SN490B.C,SMA400AW. BW.CW,SMA400AP.BP.CP,SMA490AW.BW.CW,SMA490AP. BP.CP,SHK400,SHK490 Main sizes(unit:mm,t:thickness) H-Beams : H150(t7) × B150(t10)~H912(t18)×B302(t34) Steel H piles : H200(t8)×B200(t12)~H400(t13)×B400(t21) Company Information		PCR review was conducted by:		
		Approval date	10/1/2019	
		PCR review panel chair	Yasunari Matsuno	
			(Chiba University)	
		Third party verifier*		
		Tomoko Fuchigami		
		Independent verification of data & declaration in accordance with ISO/TS14067		
		∏internal ■external		
	, Lu.			
<u>nttp://www.yamatokogyo.co.jp/steel/</u> *Auditor's name is state		ated if system certification has been performed.		
		Registration nu	Imber: JR-AJ-20001C	

Carbon Footprint of Products CFP Declaration

Ecoleaf Environmental Labeling Program

Sustainable Management Promotion Organization 2-1, Kaji-cho 2 chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

Registration number : JR-AJ-20001C

1. Quantification results, and contents of the declaration					
CFP quantification unit :					
	Parameter		Unit		
CFP Quantification results		570	kg-CO ₂ eq		
c	[A1] Raw material acquisition stage	100	kg-CO ₂ eq		
akdowi	[A2] Distribution stage	25	kg-CO ₂ eq		
	[A3] Production stage	440	kg-CO ₂ eq		
e e					
	[D] scrup recycling effect for steel products	250	kg-CO2eq		
Value on CFP mark		570	kg-CO ₂ eq		
Unit for the value on CFP mark		1t			

*Quantification results may slightly differ from the sum of the breakdown due to rounding of fractions.

3. Supplementary environmental information

Manufactured at ISO 14001 certified factories.

Manufactured at medical waste disposal certified factories.

2. Additional information



3 Transport to site scienario is based on PCR.

4. Interpretation

By this evaluation, the CO2 emission at the [A3]stage of production became 80% degree and the dominant contribution degree. At the [A3]stage of production, The electric energy to use in the electric furnace, the electric energy and the burning of city gas to use in the rolling process were main discharge sources. Then, [A1]stage had a big contribution degree. At the [A1] stage, sub-raw materials production was a main discharge source. But this evaluation calculates it using company's quantity of raw materials and energy input. And, this evaluation calculates the manufacturing load of raw materials and energy load at the time of the production using the general values such as databases. This evaluation may not reflect a characteristic peculiar to our product. For example, this evaluation uses a PCR mention scenario at the time of the raw materials procurement transportation. Therefore, please understand that this result is an approximate value.

5. Assumptions of secondary data used

We use the IDEA2.1.3 data and scrup iron data from the Japan Iron and Steel Federation(J.I.S.F).

6. Remarks

- For data quantification, please refer to PCR and Rules on quantification and declaration.
- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied. (Reference URL : https://ecoleaf-label.jp/regulation/)
- The CFP only addresses the single impact category of climate change and does not assess other potential social, economic and environmental impacts arising from the provision of a product.