

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

Canon Inc.

imageRUNNER ADVANCE DX 717iZ(For AU)



Functional unit

Per unit product

System boundary

■ final products □intermediate products Raw Material acquisition, Production, Distribution, Use & maintenance, and End-of-Life stage

Main specifications of the product

Model name

imageRUNNER ADVANCE DX 717iZ(For AU)

Specifications

- Multi Functional Printer (Electrophotography)
- ۰BW
- \cdot Print Speed : Up to 71 ipm (A4)
- Max paper size : A4
- Print/copy/scan/FAX/Duplex printing/ADF
- Weight: approx.43.00kg(All in one Cartridge not included)

Registration#	JR-AI-24182E			
PCR number	PA-590000-AI-08			
PCR name	Imaging input and/or output equipment			
Publication date	4/17/2024			
Verification date	4/12/2024			
Verification method	Product-by-product			
Verification#	JV-AI-24182			
Expiration date	4/11/2029			
PCR review was conducted by:				
Approval date	9/1/2023			
PCR review	Masayuki Kanzaki			
panel chair	Sustainable Management Promotion Organization			
Third party verifier*				
	Kazuo Naito			

Independent verification of data & declaration in accordance with ISO14025

□internal

external

*Auditor's name is stated if system certification has been performed.

Registration number : JR-AI-24182E

Company Information

Canon Inc. 30-2, Shimomaruko 3-chome, Ohta-ku, Tokyo 146-8501, Japan +81-3-3758-2111



EcoLeaf

Japan EPD Program by SuMPO

Type III Environmental Declaration (EPD) Registration number : JR-AI-24182E Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

1. Results of life cycle	impact as	ssessmer	nt (LCIA)						
			0%	20% 4	0% 60	9% 80%	6 100%		
Global warming IPCC2013 GWP100a	1300	kg-CO₂eq		43%	<mark>8%2</mark> %	42%	<mark>5%</mark>		
Acidification	0.90	kg-SO₂eq		47%	2% 5%	43%	<mark>3%</mark>		
Resources consumption	0.054	kg-Sbeq		759	%	0% 0%	24% 0%		
Raw material acquisition Distribution End-of-Life									
stage Parameter	Unit	Total	Raw material acquisition	Production	Distribution	Use & maintenance	End-of-Life		
Global warming IPCC2013 GWP100a	kg-CO₂eq	1.3E+03	5.5E+02	1.0E+02	2.9E+01	5.4E+02	6.5E+01		
Ozone layer destruction	kg-CFC-11eq	1.3E-04	5.2E-05	4.3E-08	2.1E-10	8.2E-05	5.4E-07		
Acidification	kg-SO₂eq	9.0E-01	4.3E-01	1.7E-02	4.7E-02	3.9E-01	2.7E-02		
Resources consumption	kg-Sbeq	5.4E-02	4.1E-02	1.8E-04	1.2E-04	1.3E-02	3.7E-05		

2. Life cycle inventory analysis (LCI)					
Parameter		Unit			
Non-renewable energy resources	1.9E+04	MJ			
Renewable primary energy	3.4E+02	MJ			

3. Material composition					
Material		Unit			
Common Steel	26	%			
Stainless Steel	0.51	%			
Aluminium	0.22	%			
Other Metal	2.3	%			
Plastic	35	%			
Rubber	1.0	%			
Glass	1.4	%			
Paper/Wood	25	%			
Circuit Board	4.1	%			
Others	4.0	%			



EcoLeaf

Registration number : JR-AI-24182E

Japan EPD Program by SuMPO

Sustainable Management Promotion Organization 14-8, Uchikanda 1-chome, Chiyoda-ku, Tokyo Japan https://ecoleaf-label.jp/

5. Additional explanation

Calculated in the following conditions;

- $\boldsymbol{\cdot}$ Printing paper is not considered.
- $\boldsymbol{\cdot}$ Expected use period is 5 years.
- \cdot The standard scenario for Multifunction Device (EP type).
- Australia market.
- Print volume: 748,800 sheets.
- \cdot The applied Energy Star program version is 3.0.

6-1. Supplementary environmental information

Complies with the EU RoHS Directive (2011/65/EU) and its amendments including 2015/863/EU. Manufactured at ISO 14001 certified factories.

7. Assumptions of secondary data used

IDEA v2.1.3, and registered data v1.13 of Japan EPD Program by SuMPO are used.

8. Remarks

- For data quantification, please refer to PCR and Rules on quantification and declaration.

- Comparative assertion is permitted only when Rules on quantification and declaration are satisfied. (Reference URL : https://ecoleaf-label.jp/regulation/)

Registration number : JR-AI-24182E